

## Options Headers (Hop-by-Hop Options and Destination Options)

### Bit Number

0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1

Next Header	Hdr Ext Len		4	
Options				8

### Next Header

8-bit identifier for the header immediately following this one. Uses the same codes as the main IPv6 header.

### Hdr Ext Len

8-bit length of the Hop-by-Hop Options header in 8-octet units not including the first 8 octets, i.e. (length *in* octets-8)/8.

### Options

Variable-length field, containing the options.

NOTE: length **must** be a multiple of 8 octets long.

### Option Encoding:

0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 ...

Option Type	Opt Data Len	Option Data
W	C	T T T T T

### Option Type

### 8-bit Identifier

WW	indicate what to do if this option is not recognized:
00	skip this option and continue processing the header.
01	discard packet.
10	discard packet and send an ICMP Parameter Problem code 2 back to the source address pointing to the unrecognized Option Type.
11	discard packet and, if destination is not a multicast address, behave like type 10.
C	indicates whether the option data for this option can change en-route to the destination. Relevant if, in particular, an AH is present.
0	no change
1	can change
TTTT	rest of the option type code

### Opt Data Len

8-bit length of the Option Data field of this option, in octets.

### Option Data

Variable-length field.

### Options which must be implemented:

#### i) Pad1 option, special case:

0 1 2 3 4 5 6 7

0
---

NOTE: no length or field values!

#### ii) PadN option:

0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5

1	Opt Data Len	Option Data
---	--------------	-------------

## Routing Header (similar to IPv4 LSRR and RR options)

### Bit Number

0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1

Next Header	Hdr Ext Len	Routing Type	Segments Left	4
type-specific data				

### Next Header

8-bit identifier for the header immediately following this one. Uses the same codes as the main IPv6 header.

### Hdr Ext Len

8-bit length of the Hop-by-Hop Options header in 8-octet units not including the first 8 octets, i.e. (length *in* octets-8)/8.

### Routing Type

8-bit identifier

### Segments Left

8-bit integer giving the number of listed intermediate nodes which still need to be visited.

### type-specific data

Variable-length field which depends on the routing type. Must be a multiple of 8 octets.

### Only one routing header type has been defined, type 0:

#### Type 0:

0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1

Next Header	Hdr Ext Len	Routing Type = 0	Segments Left	4
Reserved (MBZ)				
Address[1]				
Address[2]				
Address[n]				



## IPv6 TCP/IP and tcpdump

POCKET REFERENCE GUIDE



incidents@sans.org • +1 317.580.9756 • <http://www.sans.org> • <http://www.incidents.org>

### tcpdump Usage

```
tcpdump [-aenStvx] [-F file]
[-i int] [-r file] [-s snaplen]
[-w file] ['filter_expression']
```

- e Display data link header.
- F Filter expression in file.
- i Listen on int interface.
- n Don't resolve IP addresses.
- r Read packets from file.
- s Get snaplen bytes from each packet.
- S Use absolute TCP sequence numbers.
- t Don't print timestamp.
- v Verbose mode.
- w Write packets to file.
- x Display in hex.
- X Display in hex and ASCII.

### Acronyms

AH	Authentication Header (RFC 2402)	ISAKMP	Internet Security Association & Key Management Protocol (RFC 2408)
ARP	Address Resolution Protocol (RFC 826)	L2TP	Layer 2 Tunneling Protocol (RFC 2661)
BGP	Border Gateway Protocol (RFC 1771)	NNTP	Network News Transfer Protocol (RFC 977)
CWR	Congestion Window Reduced (RFC 2481)	OSPF	Open Shortest Path First (RFC 1583)
DF	Don't Fragment bit (IP)	POP3	Post Office Protocol v3 (RFC 1460)
DHCP	Dynamic Host Configuration Protocol (RFC 2131)	RFC	Request for Comments
DNS	Domain Name System (RFC 1035)	RIP	Routing Information Protocol (RFC 2453)
ECN	Explicit Congestion Notification (RFC 3168)	LDAP	Lightweight Directory Access Protocol (RFC 2251)
EIGRP	Extended IGRP (Cisco)	SKIP	Simple Key-Management for Internet Protocols
ESP	Encapsulating Security Payload (RFC 2406)	SMTP	Simple Mail Transfer Protocol (RFC 821)
FTP	File Transfer Protocol (RFC 959)	SNMP	Simple Network Management Protocol (RFC 1157)
GRE	Generic Routing Encapsulation (RFC 2784)	SSH	Secure Shell
HTTP	Hypertext Transfer Protocol (RFC 1945)	SSL	Secure Sockets Layer (Netscape)
ICMP	Internet Control Message Protocol (RFC 792)	TCP	Transmission Control Protocol (RFC 793)
IGMP	Internet Group Management Protocol (RFC 2236)	TFTP	Trivial File Transfer Protocol (RFC 1350)
IGRP	Interior Gateway Routing Protocol (Cisco)	TOS	Type of Service field (IP)
IMAP	Internet Message Access Protocol (RFC 2060)	UDP	User Datagram Protocol (RFC 768)
IP	Internet Protocol (RFC 791)		

All RFCs can be found at <http://www.rfc-editor.org>

## DNS

### Bit Number

0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5

ID.							
QR	Opcode	AA	TC	RD	RA	Z	RCODE
QDCOUNT							
ANCOUNT							
NSCOUNT							
ARCOUNT							
Question Section							
Answer Section							
Authority Section							
Additional Information Section							

### Query/Response

0 Query  
1 Response

### Opcode

0 Standard query (QUERY)  
1 Inverse query (IQUERY)  
2 Server status request (STATUS)

### AA

(1 = Authoritative Answer)

### TC

(1 = TrunCation)

### RD

(1 = Recursion Desired)

### RA

(1 = Recursion Available)

### Z

(Reserved; set to 0)

### Response code

0 No error  
1 Format error  
2 Server failure  
3 Non-existent domain (NXDOMAIN)  
4 Query type not implemented  
5 Query refused

### QDCOUNT

(No. of entries in Question section)

### ANCOUNT

(No. of resource records in Answer section)

### NSCOUNT

(No. of name server resource records in Authority section)

### ARCOUNT

(No. of resource records in Additional Information section.)

## IPv6 Header

### Bit Number

1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2 2 2 3 3  
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1

Version	Traffic Class	Flow Label	4
Payload Length		Next Header	Hop Limit

Source Address			
----------------	--	--	--

Destination Address			
---------------------	--	--	--

**Version**  
4-bit Internet Protocol version number = 6.

**Traffic Class**  
8-bit traffic class field (Experimental)  
Default = 0  
To be used for QoS and traffic prioritisation

**Flow Label**  
20-bit flow label (Experimental)  
Default = 0  
Used in association with "traffic class" to label packets for QoS.

**Payload Length**  
16-bit integer.  
Payload length in octets (packet - header)  
NOTE: extension headers are considered part of the payload!

**Next Header**  
8-bit "selector". Identifies the type of header immediately following the IPv6 header.  
Some examples:  
0 Hop-by-Hop Options (NOTE: special processing)  
43 Routing (Type 0)  
44 Fragment  
50 Encapsulating Security Payload  
51 Authentication  
58 ICMPv6  
59 No next header  
60 Destination Options

Standard headers inherited from IPv4:  
6 TCP  
17 UDP

**Hop Limit**  
8-bit unsigned integer. Decremented by 1 by each node that forwards the packet.  
The packet is discarded if Hop Limit is decremented to zero.

**Source Address**  
128-bit source address

**Destination Address**  
128-bit destination address  
NOTE: not necessarily the final destination if a Routing header is present!

## TCP Header

### Bit Number

1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2 2 2 3 3  
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1

Source Port	Destination Port	4
-------------	------------------	---

Sequence Number	8
-----------------	---

Acknowledgment Number	12
-----------------------	----

Offset (Header Length)	Reserved	Flags	Window	16
------------------------	----------	-------	--------	----

Checksum	Urgent Pointer	20
----------	----------------	----

Options (optional)	24
--------------------	----

**Common TCP Well-Known Server Ports**

7	echo	110	pop3
19	chargen	111	sunrpc
20	ftp-data	119	nntp
21	ftp-control	139	netbios-ssn
22	ssh	143	imap
23	telnet	179	bgp
25	smtp	389	ldap
53	domain	443	https (ssl)
79	finger	445	microsoft-ds
80	http	1080	socks

**Offset**  
Number of 32-bit words in TCP header; minimum value = 5

**Reserved**  
4 bits; set to 0  
ECN bits (used when ECN employed; else 00)  
CWR (1 = sender has cut congestion window in half)  
ECN-Echo (1 = receiver cuts congestion window in half)

**Flags (UAPRSF)**  
U (1 = Urgent pointer valid)  
A (1 = Acknowledgement field value valid)  
P (1 = Push data)  
R (1 = Reset connection)  
S (1 = Synchronize sequence numbers)  
F (1 = no more data; Finish connection)

**Checksum**  
Covers pseudoheader and entire TCP segment

**Urgent Pointer**  
Points to the sequence number of the byte following urgent data.

**Options**

0	End of Options list	3	Window scale
1	No operation (pad)	4	Selective ACK ok
2	Maximum segment size	8	Timestamp

## UDP Header

### Bit Number

1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2 2 2 3 3  
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1

Source Port	Destination Port	4
-------------	------------------	---

Length	Checksum	8
--------	----------	---

**Common UDP Well-Known Server Ports**

7	echo	138	netbios-dgm
19	chargen	161	snmp
37	time	162	snmp-trap
53	domain	500	isakmp
67	bootps (DHCP)	514	syslog
68	bootpc (DHCP)	520	rip
69	tftp	33434	traceroute
137	netbios-ns		

**Length**  
(Number of bytes in entire datagram including header; minimum value = 8)

**Checksum**  
(Covers pseudo-header and entire UDP datagram)

## ICMPv6 (header type 58)

### Bit Number

1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2 2 2 3 3  
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1

Type	Code	Checksum	4
------	------	----------	---

Message Body			
--------------	--	--	--

**Type**    **Code**

1	0	no route to destination
	1	communication administratively prohibited
	2	(not assigned)
	3	address unreachable
	4	port unreachable

2    0    packet too big message, message body contains MTU of next hop link.

3    0    hop limit exceeded in transit  
1    fragment reassembly time exceeded

4    0    erroneous header field encountered  
1    unrecognized "Next Header" type encountered  
2    unrecognized IPv6 option encountered

128    0    echo request

129    0    echo reply

## Fragment Header

### Bit Number

Note: fragmentation can only be performed by the source nodes, not routers!

1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2 2 2 3 3  
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1

Next Header	Reserved	Fragment Offset	Res	M	4
-------------	----------	-----------------	-----	---	---

Identification					8
----------------	--	--	--	--	---

**Next Header**  
8-bit identifier for the header immediately following this one. Uses the same codes as the main IPv6 header.

**Reserved**  
8-bit reserved field. Initialized to zero for transmission; ignored on reception.

**Fragment Offset**  
13-bit unsigned integer. The offset, in 8-octet units, of the data following this header, relative to the start of the data which can be fragmented of the original packet. Note that the IPv6 header and extensions headers which need to be processed at every hop **cannot** be fragmented! [This is known as the "Unfragmentable Part" in IPv6 jargon].

**Res**  
2-bit reserved field. Initialized to zero for transmission; ignored on reception.

**M flag**  
1 = more fragments; 0 = last fragment.

**Identification**  
32 bits identifier for reassembly.

## Checksums

The IPv6 header does **not** include checksums on the assumption that if checksumming is required then it will be done via an AH header which provides cryptographically strong authentication (and hence a checksum) of the whole packet. There remains an issue with upper-layer protocols, for example TCP and UDP which include a checksum calculation. In particular the "pseudo-header" to be used in IPv6 TCP/UDP checksum calculations is:

### Bit Number

1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2 2 2 3 3  
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1

Source Address			
----------------	--	--	--

Destination Address			
---------------------	--	--	--

Upper-Layer Packet Length			
---------------------------	--	--	--

Must be Zero (MBZ)			Next Header
--------------------	--	--	-------------

Note: unlike IPv4 the UDP checksum is compulsory when carried over IPv6!