

TORQUE SPECIFICATION

| Part Tightened | | N-m | kgf·cm | ft·lbf |
|---|---------|-------|--------|------------|
| Park/neutral position switch x Transaxle | Bolt | 5.5 | 56 | 49 in.·lbf |
| | Nut | 5.5 | 56 | 49 in.·lbf |
| Control shaft lever x Park/neutral position switch | | 12.5 | 127 | 9 |
| Battery carrier x Body | | 13 | 132 | 10 |
| Engine hanger x Engine | | 38 | 387 | 28 |
| Drain plug x Oil pan | | 17.5 | 178 | 13 |
| Transaxle x Engine | Bolt A: | 64 | 650 | 47 |
| | Bolt B: | 46 | 470 | 34 |
| | Bolt C: | 23 | 235 | 17 |
| Torque converter clutch x Drive plate | | 28 | 285 | 20 |
| Engine mounting bracket RR x Transaxle | | 64 | 652 | 47 |
| Center member x Body | Bolt A: | 39 | 398 | 29 |
| | Bolt B: | 52 | 530 | 38 |
| Engine mounting insulator RR x Engine mounting bracket RR | | 87 | 887 | 64 |
| Engine mounting insulator RR x Suspension member | | 52 | 530 | 38 |
| Engine mounting insulator FR x Engine mounting bracket FR | | 52 | 530 | 38 |
| Engine mounting bracket LH x Transaxle | | 52 | 530 | 38 |
| Engine mounting insulator LH x Body | Bolt A: | 52 | 530 | 38 |
| Engine mounting insulator LH x Engine mounting bracket LH | Nut B: | 80 | 815 | 59 |
| Engine mounting bracket FR x Transaxle | | 64 | 652 | 47 |
| Starter x Transaxle | | 39 | 400 | 29 |
| Starter wire x Starter | | 13 | 132 | 10 |
| Transmission case protector x Transaxle | | 18 | 182 | 14 |
| Oil filler tube x Transaxle | | 5.5 | 56 | 49 in.·lbf |
| Oil cooler tube clamp x Oil filler tube | | 5.5 | 56 | 49 in.·lbf |
| Oil cooler outlet tube x Transaxle | | 34.5 | 350 | 25 |
| Oil cooler inlet tube x Transaxle | | 34.5 | 350 | 25 |
| Wire harness clamp bracket x Transaxle | | 12.75 | 130 | 9 |
| Wire harness x Transaxle | Bolt A: | 25.5 | 260 | 19 |
| | Bolt B: | 10 | 102 | 7 |
| | Bolt C: | 13 | 132 | 10 |
| Control cable bracket x Transaxle | | 12 | 122 | 9 |
| Control cable support x Transaxle | | 12 | 122 | 9 |
| Air cleaner assy x Body | | 7.0 | 71 | 62 in.·lbf |
| Cylinder head cover No. 2 x Engine | | 7.0 | 71 | 62 in.·lbf |
| Speedometer sensor x Transaxle | | 11.3 | 115 | 9 |
| Solenoid valve x Valve body | Bolt A: | 11 | 110 | 8 |
| | Bolt B: | 11 | 110 | 8 |
| | Bolt C: | 6.5 | 66 | 58 in.·lbf |
| Valve body x Transaxle | | 10 | 100 | 7 |
| Manual detent spring x Valve body | | 10 | 100 | 7 |
| Oil strainer x Valve body | | 10 | 100 | 7 |
| Oil pan x Transaxle | | 5.3 | 55 | 48 in.·lbf |
| Transmission wire x Transaxle | | 5.4 | 55 | 48 |
| Floor shift assy x Body | | 12 | 122 | 9 |
| Control cable x Control shaft lever | | 12 | 122 | 9 |
| Control cable x Body | Bolt | 5.0 | 50 | 43 in.·lbf |
| | Nut | 12 | 122 | 9 |