

**TORQUE SPECIFICATION**

| Part Tightened   | N-m   | kgf-cm | ft-lbf       |
|--|-------|--------|--------------|
| Bleeder plug   | 8.3   | 85     | 74 in.-lbf   |
| Brake booster clevis lock nut                          | 26    | 265    | 19           |
| Brake pedal support sub-assy x Brake pedal sub-assy    | 36.8  | 375    | 27           |
| Brake booster x Body                                   | 12.7  | 130    | 9            |
| Brake pedal support sub-assy x Body                    | 23.6  | 240    | 17           |
| Brake master cylinder x Piston stopper bolt            | 10    | 102    | 7            |
| Brake master cylinder x Reservoir                      | 1.8   | 18.4   | 15.9 in.-lbf |
| Brake master cylinder x Brake booster                  | 12.5  | 127    | 9            |
| Brake line union nut                                   | 15.2  | 155    | 11           |
| Wheel nut  | 103   | 1,050  | 76           |
| Cruise control actuator bracket x Body                 | 43    | 438    | 32           |
| Front brake cylinder mounting x Steering knuckle       | 106.8 | 1,089  | 79           |
| Front brake cylinder x Front brake cylinder mounting   | 34.3  | 350    | 25           |
| Front disc brake caliper x Flexible hose               | 29    | 296    | 21           |
| Rear drum brake wheel cylinder x Backing plate         | 10    | 102    | 7            |
| Proportioning valve assy x Body                        | 5.4   | 55     | 48 in.-lbf   |
| Brake actuator assy x Actuator bracket                 | 4.7   | 48     | 42 in.-lbf   |
| Brake actuator bracket x Body                          | 19    | 194    | 14           |
| Front speed sensor x Steering knuckle                  | 8.0   | 82     | 71 in.-lbf   |
| Front speed sensor wire harness clamp x Shock absorber | 29    | 296    | 21           |
| Front speed sensor wire harness clamp x Body           | 8.0   | 82     | 71 in.-lbf   |