



Jane's
POCKET GUIDE
**MODERN MILITARY
HELICOPTERS**

TIM RIPLEY

Jane's
POCKET GUIDE
MODERN MILITARY
HELICOPTERS

TIM RIPLEY



HarperCollins Publishers

Contents

- | | | | |
|--------------------------------------|---------------|---------------------------------------|--------------|
| 4. Introduction | | 40. Agusta-Bell AB 212 | Italy |
| 6. Aerospatiale Alouette II | France | 41. Kawasaki OH-1 | Japan |
| 7. Aerospatiale Alouette III | France | 42. PZL Swidnik W-3 Sokol | Poland |
| 9. Aerospatiale Super Frelon | France | 44. Kamov Ka-25 | Russia |
| 10. Eurocopter Gazelle | France | 45. Kamov Ka-27/28/32 | Russia |
| 14. Eurocopter Dauphin/Panther | France | 46. Kamov Ka-29 | Russia |
| 17. Eurocopter Ecureuil/Fennec | France | 47. Kamov Ka-50/52 Werewolf/Alligator | Russia |
| 20. Eurocopter Puma | France | 49. Mil Mi-2 | Russia |
| 22. Eurocopter Super Puma/Cougar | France | 52. Mil Mi-6 | Russia |
| 26. Eurocopter BO105 | Germany | 53. Mil Mi-8/17 | Russia |
| 28. HAL Advanced Light Helicopter | India | 58. Mil Mi-14 | Russia |
| 29. Eurocopter Tiger | International | 59. Mil Mi-24 | Russia |
| 31. EH Industries EH.101 Merlin | International | 64. Mil Mi-26 | Russia |
| 34. NATO helicopter Industries NH 90 | International | 65. Mil Mi-28 | Russia |
| 36. Agusta A 109 | Italy | 66. Mil Mi-34 | Russia |
| 38. Agusta A 129 | Italy | 67. Mil Mi-38 | Russia |
| | | 68. Mil Mi-40 | Russia |
| | | 69. Denel Aviation CSH-2 Rooivalk | South Africa |

71. Denel Aviation Oryx	South Africa	104. Boeing CH-46 Sea Knight	USA
72. Westland Wasp	UK	106. Boeing/Sikorsky RAH-66 Comanche	USA
73. Westland Lynx (Army)	UK	108. Boeing OH-6 Cayuse/MD500/MD530	USA
75. Westland Lynx (Navy)	UK	112. Boeing MD 520N Explorer	USA
78. Kaman Seasprite	USA	114. Boeing AH-64 Apache	USA
80. Bell Model 47 Sioux	USA	118. Sikorsky S-58 Choctaw/Wessex	USA
81. Bell Model 204/UH-1	USA	119. Sikorsky S-61/SH-3 Sea King	USA
83. Bell Model 205/UH-1	USA	126. Sikorsky S-61N-1 Silver	USA
85. Bell Model 212/UH-1N	USA	127. Sikorsky S-61/HH-3	USA
87. Bell Model 214	USA	128. Sikorsky S-65A/CH-53 Sea Stallion	USA
88. Bell Model 412	USA	131. Sikorsky S-80/CH-53E Super Stallion	USA
90. Bell 206 JetRanger	USA	134. Sikorsky S-70/UH-60 Black Hawk	USA
92. Bell 206/OH-58 Kiowa	USA	139. Sikorsky S-70/SH-60 Seahawk	USA
93. Bell 406/OH-58D Kiowa Warrior	USA	142. Sikorsky S-76	USA
94. Bell Model 209/AH-1F/G Huey Cobra	USA		
96. Bell Model 209/AH-1W SuperCobra	USA		
98. Boeing V-22 Osprey	USA	143. Glossary	
100. Boeing CH-47 Chinook	USA	144. Photocredits/acknowledgements	

Introduction

"Death from Above" was the famous insignia on the nose of Lieutenant Colonel Kilgore's UH-1 Huey gunship in Francis Ford Coppola's Vietnam War epic *Apocalypse Now*. The 25-minute long section of the movie where the 1/9th 'Air Cav' take a Vietcong-held village to the sound of Wagner's *Ride of the Valkyries* captured perfectly the essence of going to war by helicopter.

Since the Vietnam War the helicopter has been an integral part of every armed force, and rotary-winged aircraft have seen action in every major conflict and many small wars. This rapid acceptance of helicopters into the mainstream of military organisations in attack, reconnaissance, liaison, transport, medical and maritime roles has led one commentator to term them 'rotary-winged fighting vehicles.'

However, when helicopters first saw action during the Korean War, they were used by US armed forces for casualty evacuation and VIP transport only. Indeed, it was left to the French to first demonstrate the combat potential of the armed helicopter during their colonial conflict in Algeria. The 1950s and 60s also coincided with revolutionary developments in helicopter design, such as the tandem rotor and turboshaft powerplants.

The success of US Army and Marine Corps gunships in Vietnam spurred the Soviet, British, French, Italian, Israeli, German and numerous other armed forces to field their own fleets of helicopters for anti-tank and assault work. By the mid-1970s most armies had begun programmes to procure specialist attack helicopters, leading to the development of the

current generation of Cobras, Apaches, Tigers, A 129s, Mi-24s, Ka-50s and Boiwalks. It must be duly noted that these developments were often made in the face of stiff opposition from air force 'blue suiters', who saw the armed helicopter as a direct rival to their own fleets of fixed-wing close air support aircraft.

No such argument was put forward by the navies of the world, however, as they had been quick to embrace the armed helicopter for the anti-submarine and anti-surface vessel roles, as well as more conventional air transport duties.

Indeed, the 1982 Falklands War proved the worth of the helicopter in naval warfare, protecting the British fleet from Argentine submarine attack, decoying Exocet missiles with electronic jamming devices and sinking enemy shipping with guided missiles. Five years later US Army and Navy helicopters provided vital protection against Iranian fast patrol boats in Persian Gulf.

The 1991 Gulf War saw helicopters employed successfully in a wide range of roles by Coalition forces, whilst in the aftermath of the conflict, multi-national relief efforts to help Kurdish refugees in Northern Iraq depended on helicopters to fly in supplies to remote mountain camps.

In the post-Cold War world, humanitarian aid and peacekeeping missions have seen ostensibly military helicopters put to extensive use. Media images of United Nations relief operations in Somalia, Haiti, Rwanda, Bosnia and elsewhere are dominated by swarms of helicopters. NATO peace enforcing missions in Bosnia have seen the Apache

attack helicopter intimidating local forces into keeping the peace.

From a communist standpoint, Soviet forces used helicopter gunships to great effect during their long conflict in Afghanistan from 1979 onwards. The simple, but rugged, Mil Mi-8 and Mi-24 assault helicopters became familiar images on snatched footage shot by western television crews covering with the Mujhadeen guerrillas at the bottom of parched Afghan valleys. In 1994 Russian helicopters were again in action against Islamic guerrillas in Chechnya. Combat helicopters from the former Soviet Union are much in demand because of their low cost and reliability. Proof of this has come very recently when, in a remarkable vote of faith in their former opponents' equipment, the South African-based mercenary organisation Executive Outcomes has become a regular user of Mi-8 and Mi-24s during its operations in Angola and Sierra Leone.

This Jane's guide aims to describe the major combat helicopters in service today, or in the final stages of development. We have classified combat helicopters as rotary-winged aircraft designed specifically for military use, or civilian machines adopted for use by military forces.

Increasingly, armed forces are making use of chartered civilian helicopters as a means to cut costs, and we have enclosed the types used by contractors in this study, particularly those chartered by the United Nations for humanitarian and peacekeeping missions.

We also take note of a number of major changes in the

helicopter industry. For example, the consolidation of helicopter manufacturers into a smaller number of larger companies is reflected in the usage of new company titles. We have, however, included details of what are termed 'heritage companies' for reference. As a rule, we have used the current name of the manufacturer, or last name manufacturer before production ceased.

The opening up of the Russian defence industry since the demise of the Soviet Union has meant that it is now possible to attribute long-established designs to their real manufacturers, rather than just link products to design bureaux (known as OKB). Actual Russian helicopter and weapon designations are also used to supplement NATO reporting names.

Helicopter production continues around the world in large numbers in spite of the general down turn in global defence spending. This trend will continue as combat helicopters continue to be in the forefront of military thinking and actual operations well into the 21st Century. New technical developments such as the introduction of tilt rotors and advanced compound helicopters also offer military helicopter users significant improvements in both performance and operational capabilities.

Tim Ripley

Lancaster, October 1997

Aérospatiale Alouette II (France)

Type: Light helicopter

Accommodation: One pilot; four passengers

Development/History

After its first flew in 1955, the Alouette II became the world's first turboshaft powered helicopter to enter production.

Variants

SE 3130: Two prototype Alouette IIs, powered by the 268 kW (360 shp) Turbomeca Artouste I turboshaft.

SE 3138: Designation after Sud-Est merged with Gourdou Laroche in 1957, later re-named Sud-Aviation.

SE 3140: Alouette II development, powered by a 298 kW (400 shp) Turbomeca Tama II engine, but never produced.

SA 3100: Alouette II derivative powered by the more economical Artouste III with a new centrifugal clutch.

SA 318C: Production version of SA 3100.

SA 315B Lama: Powered by Turbomeca Artouste IIIb. Assembled in India (Chetani) and Brazil (HB 3160 Govco).

Status

French production ended 1975. Indian production continues.

Operators

Argentina, Belgium, Benin, Bolivia, Cameroon, Chile, Congo, Ecuador, El Salvador, Dominican Republic, Germany, Guinea-Bissau, India, Lebanon, Mauritania, Senegal, Togo, Tunisia.

Manufacturers

Sud-Est/Sud-Aviation/Aérospatiale (France), Hindustan Aeronautics Ltd (India), Bristow (Brazil), Saab (Sweden), Republic Aviation (USA).



Aérospatiale Alouette II

(Tim Ripley)

Specifications (for SA 318C)

Powerplant

One Turbomeca Artouste III turboshaft
Power: 520 shp (380 kW) de-rated to 360 shp (265 kW)

Dimensions

Length: 39 ft 8 in (12.10 m)
Rotor diameter: 33 ft 5.6 in (10.20 m)
Height: 9 ft (2.75 m)

Weights

Empty: 1901 lb (863 kg)
Max TO: 3600 lb (1630 kg)
Payload: 1323 lb (600 kg)

Performance

Max speed: 127 mph (205 kmh)
Range: 388 nm (720 km)

Armament

AS11 and 17 wire-guided anti-tank missiles; free-flight rockets; machine guns

Aérospatiale Alouette III (France)

Type: Light helicopter

Accommodation: Two pilots, five passengers

Development/History

The best-selling Alouette III grew out of the smaller Alouette II. The first prototype flew in 1959 and rapidly became a best-selling machine with 2,762 built and 74 countries operating the helicopter at the height of its popularity. Originally intended for service with the French armed forces in Algeria, that conflict came to an end before it was in widespread use. Portuguese, Rhodesian and South African forces used the helicopter extensively in their long bush wars with Nationalist guerrillas throughout Southern Africa. It has been used extensively in conflicts on the Indian sub-continent by Indian and Pakistani forces, performing well in the high Himalayas. Versions have been used for liaison, observation, attack, assault transport, anti-submarine warfare, anti-surface warfare, anti-armor, combat search and rescue, counter-insurgency and armed reconnaissance work.

Sud-Aviation, later Aérospatiale, were keen to use license production deals to foster business relationships in the Eastern Bloc and Third World. They were one of the first western aviation companies to offer technology transfer and work on the Alouette family helped establish the Indian, Romanian and South African helicopter industries.

Variants

SE 3160: Alouette III powered by one 640 kW (870 shp) Turbomeca Artouste III turboshaft, de-rated to 470 kW (650 shp).

SA 316A: Production version of SE 3160.

SA 316B: Featured strengthened main and tail rotor to allow



Aérospatiale Alouette III

(Tim Ripley)

Specifications (for SA 319B)

Powerplant

One Artouste XIV turboshaft

Power: 800 shp (640 kW) de-rated to 600 shp (447 kW)

Max T/O: 4620 lb (2100 kg)

Payload: 1650 lb (750 kg)

Performance

Max speed: 136 mph (220 km/h)

Range: 325 nm (605 km)

Dimensions

Length: 33 ft 4 in (10.2 m)

Rotor diameter: 36 ft 1 in (11 m)

Height: 9 ft 9 in (2.9 m)

Armament

AS12 guided missiles; M4-44 ASW torpedoes; machine guns (pad or door mounted); free-flight rocket pods

Weights

Empty: 2430 lb (1105 kg)

Aerospatiale Alouette III (France)



Aerospatiale Alouette III of Royal Netherlands Air Force

(Tim Ripley)

for greater performance. Produced in Romania as IAR-316B and in India as Chetak, SA 316C: Aerospatiale IIIID powered variant built in limited numbers.

SA 319B: Direct development of the SA 316B, powered by a more efficient and more

economical 649 kW (870 shp) Turbomeca Astazou XV turboshaft, de-rated to 447 kW(600 shp).

G-Car: Rhodesian Air Force gunship version with two side-mounted Browning machine guns. Gunship with single port firing 20 mm

Mosier cannon in cabin known as E-Car.

IAR-317 Skyfox: Prototype Romania gunship version, armed with anti-tank missiles, free-fall rockets and machine gun pods which did not enter production.

Atlas Aviation XH-1 Alpha: South Africa weapon system demonstrator for Boenck attack helicopter.

Status

Production in France ceased in 1983 after 1455 built. Some 230 built in Romania until 1989. Limited production continued only in India, with 300 built to date.

Operators

Algeria, Angola, Argentina (navy), Austria, Belgium (navy), Botswana, Brazil, Burkina Faso, Cameroon, Chad, Congo Republic, Ecuador (air force), Equatorial Guinea, France (army/navy/air force), Ghana, Greece (navy), Guinea, Guinea-Bissau, India (army/navy), Iraq, Ireland, Jordan, Lebanon, Libya, Malaysia (army), Mexico (navy), Morocco, Mozambique, Myanmar, Namibia, Nepal, Netherlands, Nicaragua, Pakistan (army/navy/air force), Peru (army/navy/air force), Portugal, Romania, Rwanda, South Africa, Suriname, Switzerland, Togo, Tunisia, UAE (Abu Dhabi), Venezuela (army), Congo (former Zaire) and Zimbabwe.

Manufacturers

Sud-Aviation/Aerospatiale (France), ICA Brno (Romania), Federal Aircraft Factory (Switzerland) and Hindustan Aeronautics Ltd (India).

Aérospatiale Super Frelon (France)

Type: Heavy lift helicopter

Accommodation: Two pilots, up to 37 passengers

Development/History

First flown in the 1960 to meet French Navy requirements for a maritime helicopter armed with anti-ship guided missiles and ASW weapons. Some remain in French service for logistic support and vertical replenishment at sea.

Variants

- SA 321: Pre-production aircraft
- SA 321G: French ASW version, later able to fire Exocet
- SA 321Gc: French navy cargo-carrying and assault transport
- SA 321GM: Export version for Libya.
- SA 321F: Civilian version.
- SA 321H: Version sold to Iraq with Turbomeca engines, Omega ORB-310 rotor and Exocet missiles.
- SA 321F B Jc: Civilian version.
- SA 321K: Export transport version to Israel.
- SA 321L: Export transport version to South Africa.
- SA 321M: Export transport/assault version to Libya.
- Changhe Z-8: Chinese-built naval and combat version.

Status

Production continues in China only.

Operators

France (navy), China (navy), Iraq and Libya.

Manufacturer

Sud-Aviation/Aérospatiale (France) and Changhe Aircraft Factory (China).



Aérospatiale SA 321 Super Frelon

(Tim Ripley)

Specifications (for SA321G)

Powerplant

Three Turbomeca Turmo III turbo shafts
Power: 4710 shp (3540 kW)

Dimensions

Length: 63 ft 7 in (19.4 m)
Rotor diameter: 62 ft (18.9 m)
Height: 16 ft 2 in (4.9 m)

Weights

Empty: 15 130 lb (6863 kg)
Max TO: 28 660 lb (13 000 kg)
Payload: 11 023 lb (5000 kg)

Performance

Max speed: 171 mph (275 km/h)
Range: 549 nm (1020 km)

Armament

ASW torpedoes; depth charges; machine guns

Eurocopter Gazelle (France)

Type: Light helicopter

Accommodations: One pilot, four passengers

Development/History

Sud-Aviation began work on the Gazelle in the mid-1960s as a replacement for its Alouette family. By 1967 it had been put into the melting pot of the Anglo-French Helicopter Agreement, which was to see the joint development of the Gazelle, Lynx and Puma families of helicopters by Sud-Aviation (later Aerospatiale) and Britain's Westland. This agreement gave France the lead in Gazelle exports, and Aerospatiale was soon leading a major foreign sales drive. Exports and co-production deals resulted in more than 400 sales, 294 being ordered for construction in Britain (all except 12 for the UK armed forces) while France bought just under 400. Total production was some 1254.

A year later the Gazelle made its first flight, and soon the version with the revolutionary 'boomstron', or fan-in-lin tail, rotor was airborne. By the mid-1970s the aircraft was in widespread use with the British and French armed forces. From 1973 the French began to field the new SA 342 version, which sported an improved engine. Britain chose not to adopt the new engine for its Gazelles.

British versions saw combat in the Falklands in 1982, but it was in the 1982 Lebanese war that a Syrian version armed with HOT anti-tank missiles showed the Gazelle's true potential as an armed helicopter. French HOT and Mistral missile-armed versions were used extensively during the 1991 Gulf War in the air cavalry role on the extreme left flank of the Coalition forces. Three Kuwaiti Gazelles fought alongside US Marine Corps forces to liberate Kuwait City. Yugoslavian-built versions have been used extensively in armed and unarmed roles during the civil war that broke out



Westland Gazelle AH.66A 1 of the British Army Air Corps

(Tim Alpley)

Specifications (for SA 341)

Powerplant

One Turbomeca Astazou B1A turboshaft
Power: 580 shp (440 kW)

Dimensions

Length: 39 ft 3 in (11.9 m)
Rotor diameter: 34 ft 5 in (10.5 m)
Height: 10 ft 2 in (3.2 m)

Weights

Empty: 2002 lb (917 kg)
Max T/O: 3590 lb (1600 kg)
Payload: 1540 lb (700 kg)

Performance

Max speed: 153 mph (247 km/h)
Range: 361 nm (670 km); 193 nm (360 km)
with max payload

Armament

AS11, AS12, HOT, TOU and 9M14M Malyska (AT-3 Sagger) wire-guided anti-tank missiles; 9M32M Sirena (SA-7 Grail) and Mistral air-to-air missiles; one M621 20 mm cannon; door- and pod-mounted machine guns; three-flight rockets.

In 1991, with Serbia-operated Gazelles seeing action against Slovenian, Croat and Bosnia forces.

British and French Gazelles have been used in the former Yugoslavia to support United Nations and NATO peacekeeping forces since 1992. British Army Gazelles operating in Northern Ireland have been fitted with a variety of specialist observation and close circuit television systems.

Variants

SA 340: Two prototypes, first with conventional rotors and T-tail; second fitted with eight main rotors and fenestron, Astazou II powerplant of 288 kW (390 shp).

SA 341: Four pre-production helicopters with enlarged cabin, semi-articulated rotors, 440 kW (590 shp) Astazou III and 2800 lb (1260 kg) maximum weight.

SA 341B: British Army Air Corps Gazelle AH 1, 212 built.

SA 340C: British Royal Navy (Fleet Air Arm) Gazelle HC 2, 40 built.

SA 341D: British Royal Air Force Gazelle HT 3, 29 built.

SA 341E: British Royal Air Force VIP transport Gazelle HCC A, one built and three converted from HT 3s.

SA 341G: Civilian.

SA 341I: French Army Aviation version, 968 built.

SA 341F(Cannon): French Army Aviation MG21 20 mm cannon armed version, 62 converted from original Fs.

SA 341R: Initial French military export version.

SA 341H Partizan: Yugoslav-built version.

SA 341M: French Army Aviation H03 armed version, 40 converted from original Fs.

SA 342R: Civilian.



Eurocopter SA 342 L1 Gazelle

(Aerospaiale)



SA 342K: Up-rated military export version with 650 kW (870 shp) Astazou XR41 Powerplant and 4189 lb (1900 kg) maximum weight.

SA 342L: Military export model with improved forestion. Some 129 built in Yugoslavia, including SA 342L2 GAMA attack and SA 342L2 HERA scout versions armed with Soviet bloc anti-armor and air-to-air missiles.

SA 342L1: Military export version with Astazou XR41 and 4469 lb (2030 kg) maximum weight.

SA 342M Viviane: final production version for French Army Aviation, with Astazou XR41 and HOT missiles. More than 200 produced. Some 30 fitted with Mistral missile to SA 342M/Celtic standard and later SA 342M/AM standard.

Status

No longer in production.

Operators

Angola, Bosnian Serb Republic, Burundi, Cameroon, Croatia, Cyprus, Ecuador, Egypt, France (Army), Guinea Republic, Iraq, Iceland, Jordan, Kenya, Kuwait, Lebanon, Libya, Morocco, Qatar, Senegambia, Slovakia, Syria, Tunisia, UAE (Abu Dhabi), United Kingdom (Army/Cavalry), Yugoslavia (Serbia/Montenegro).

Manufacturer

Sud-Aviation/Aérospatiale/Eurocopter (France), Westland Helicopters (UK), SOHO (Yugoslavia), Arab-British Helicopter Company (Egypt).

Above:

Eurocopter SA 342M Gazelle for French Army Aviation
(Tom Ripley)

Right:

Eurocopter SA 342 Gazelle fires a HOT wire guided anti-tank missile
(Aérospatiale)



Eurocopter Dauphin/Panther (France)

Type: Light helicopter

Accommodation: Two pilots, 10 troops

Development/History

Agusta began development of the Dauphin (Dolphin) as a replacement to the Alouette III in the early 1970s, with the first flight taking place in 1972. The twin-engined version first flew three years later, and it has remained in production ever since, with worldwide sales and a number of licence production agreements being reached. A version with Allison engines entered service with the US Coast Guard in 1987 after a troubled programme to integrate the US-sourced powerplant. Some have since been passed on to local forces. From 1990 onwards, military versions have been christened the Panther, with designations in the 565 series adopted simultaneously. The Dauphin/Panther has proven to be a versatile and reliable light helicopter, which looks set to remain in production and service until well into the next century.

Variants

AS 300: Initial prototype powered by single Turbomeca Astazou XM powerplant.

AS 361H: Initial military version powered by single Turbomeca Astazou XMBA powerplant.

AS 365C Dauphin 2: Twin-engined version powered by 485 kW (650 shp) Turbomeca Arriel turboshaft. In 1990 re-designated as AS 365N3 Dauphin 2. C1, C2, C2 versions.

AS 365H: Improved version with retractable undercarriage.

AS 365N1: Panther improvement with TI-bladed Irotron and up-rated Arriel 1C1 powerplant.

AS 365M2: Civil version with Turbomeca 1 C2 powerplants.

AS 365Q/M: First military version of twin-engined



Eurocopter SA 360/M1-05 Dauphin

(DfW Spokesman)

Specifications (for AS 565 Panther)

Powerplant

Two Turbomeca Arriel 1M1 turboshafts

Power: 1560 shp (1149 kW)

Payload: 1527 lb (690 kg)

Performance

Max speed: 164 mph (286 kmh)

Range: 477 nm (875 km)

Dimensions

Length: 38 ft 1 in (11.6 m)

Rotor diameter: 29 ft 8 in (9.1 m)

Height: 13 ft 1 in (3.99 m)

Armament

One M621 20-mm cannon pods; Mistral air-to-air missiles; HOT wire-guided anti-tank missiles; free-flight rockets; AS15H and Exocet anti-ship missiles; Marine torpedoes

Weights

Empty: 4835 lb (2193 kg)

Max TO: 9360 lb (4250 kg)

AS300B2, for attack and troop transport. This was renamed the Panther, powered by turboshafts TM1 and marketed under the following versions: AS 305MA fire-flight rocket and gun armed; AS 348MA utility; AS 348CA anti-tank; AS 348F navalised version with retractable undercarriage; AS 348T1 navalised version; AS 348SA anti-shipping; AS 348MA unarmed rescue; AS 348SC Saudi Arabia rescue.

AS 348V3: Upgraded version with two turboshafts Arriel 2C turboshafts. Panther versions were designated SA 345 B3 utility; SA 345 AB cannon/rocket armed; SA 345 M3 shipborne utility; SA 345 SB shipborne armed.

AS 345M4: Civil wide body version, seating 14 and powered by Arriel 2C.

AS 345 Panther: Brazilian version of E model designated HM-1 by Brazilian army.

Panther 800: Proposed US Army version, did not enter production.

AS 36621: Version produced for US Coast Guard under designation HH-65A, with Westinghouse Lycoming LTS1-1-750A-1 engines, specialist night vision and rescue equipment. Also used by Israel.

Harbin Z-9 Haitian: Chinese version assembled from French kits.

Harbin Z-9A-100: Chinese-made version with WZ-8A powerplant, rated to 540 kW (734 hp), which can be armed.

Status

In production in France, Brazil and China.



Eurocopter AS 345 Panther

(AeroSpace)

Eurocopter Dauphin/Panther (France)



Operators

Angola, Botswana, Brazil (Army), Burkina Faso, Cameroon, China, Congo, Côte d'Ivoire, Dominican Republic, Fiji, France (Army, Air Force), India (Air Force), Ireland, Israel, Romania, Saudi Arabia (Army), Sri Lanka, Taiwan, Thailand (Army), UAE (UAE Air Force), USA (Coast Guard).

Manufacturers

Avicopter/Eurocopter (France), Helibras (Brazil) and Harbin Aircraft Manufacturing (China).

**Eurocopter AS 66SF
Panther**
(Tim Ryley)

Eurocopter Ecureuil/Fennec (France)

Type: Light helicopter

Accommodation: Two pilots, two/three passengers

Development/History

The three-rotor bladed Ecureuil (Squirrel) first flew in 1974 and has remained in production ever since, attracting several thousand military and civilian customers around the globe. The single-engined 350 series version was soon supplanted by the twin-engined 355 series aircraft, which provided greater performance. Since 1990 specialist military versions of the Ecureuil have been marketed under the Fennec (Fox) name, using the series 555 series designation.

Versions

AS 350 Ecureuil: First prototype with single Textron Lycoming LTS 101 turboshaft.

AS 350BA/B2/B3: Civilian/military version with single Turbomeca Arriel 1B; B2 with Arriel 1D1; B3 with Arriel 2.

AS 350B: Civilian version with single Textron Lycoming LTS 101 turboshaft. Known as ASAR in USA.

AS 350 Firefighter: Specialised version.

AS 350L2: First armed version, powered by 540 kW (732 shp) Turbomeca Arriel 1D1, known as Fennec; AS 550A2/C2 anti-tank version. Other Fennec versions include: AS

550B2/U3 unarmed utility; AS 550A2/P3 armed, cannon or rocket; AS 550V2 unarmed naval; AS 550S2 armed naval anti-shipping; AS 550U3/A2/C2 air Arriel 2B powered.

HB 350B81 Espalès: Unarmed Brazilian version, designated CH-50 and TH-50 by Brazilian Air Force, UH-12 by Brazilian Navy.

HB 350L1 Espalès: Armed Brazilian version, designated HA-1 by Brazilian army.

Squid HT 1/HT 2: UK training version of AS 350B3.



Eurocopter AS 355 Ecureuil

(Tim Ripplert)

Specifications (for AS 350B)

Powerplant

One Turbomeca Arriel 1B turboshaft

Power: 641 shp (470 kW)

Max TQ: 4630 lb (2100 kg)

Performance

Max speed: 178 mph (287 km/h)

Range: 394 nm (730 km)

Dimensions

Length: 35 ft 10 in (10.9 m)

Rotor diameter: 35 ft (10.7 m)

Height: 10 ft 11 in (3.3 m)

Armament

One M621 20 mm cannon pod; 7.62 mm machine gun pod; free-flight rockets; TOW wire-guided anti-tank missile; Mistral air-to-air missile; anti-submarine torpedoes.

Weights

Empty: 2325 lb (1146 kg)

Eurocopter Ecureuil/Fennec (France)



AS 350B4 in service with the Australian Army
LAPW

AS 350E Ecureuil: first production version with two 313 kW(420 shp) Allison 250-C20F turboshafts.
AS 350N Ecureuil 2: improved version with two 340 kW (460 shp) Turbomeca Armois 1A. Civil version known as AS 350F2 Twin Star in USA.
AS 350F: Improved rotor blade version.

AS 350F1: French training version. F2 has upgraded transmission.

AS 350A2: French armed version.

AS 555 Fennec: Twin-engine version. AS 555AN armed version with 20 mm cannon; AS 555AN training and utility version; AS 555AR armed naval version; AS 555AR cannon/rocket armed version; AS 555AR utility version; AS 555BR naval utility version; AS 555BN unarmed naval version; AS 555BN armed naval version.

Z-11: Chinese produced copy with WC-8D Powerplant, rated to 510 kW (685 shp).

AS/HB 555F2: Brazilian version, designated CH-55 and 501-55, or Opinel B1, by Brazilian air force, UH-12B by Brazilian navy.

Twin Squérel: US VIP transport version of AS 555F1.

Status

In production in France, China and Brazil.

Operators

Argentina (coast guard), Australia (army, navy, air force), Benin, Botswana, Brazil (army, navy, air force), Central African Republic, Denmark (army), Djibouti, Ecuador (army), Fiji, France (army, navy, air force), Iceland, Ireland, Malawi, Paraguay, Peru (air force), Sierra Leone, Singapore, Tunisia, UAE (Abu Dhabi), UK (air force, army).

Manufacturers

Arrospatiak/Eurocopter (France), Chang (China) and Helibras (Brazil).



Eurocopter AS 550 CS Fennec

(Eurocopter)

Eurocopter Puma (France)

Type: Medium lift helicopter

Accommodation: Two pilots, loadmaster, 20 troops

Development/History

Work on the SA 330 began in 1963 but the programme became multi-national as a result of the 1967 Anglo-French helicopter agreement. This resulted in Westland building 40 for the British Royal Air Force. Under this arrangement future development and export work on the design was the responsibility of Aerospatiale, later Eurocopter, who began a vigorous sales drive in the 1970s. British and French Pumas have seen action in the 1991 Gulf War and supporting peacekeeping missions in the former Yugoslavia. South African forces used the Puma extensively in their bush wars in Angola and South West Africa. French production ceased in 1987 after 667 built. The design was superseded by Super Puma (Cougar) versions from the late 1980s. The main centres of Puma development are now in South Africa (see Dyn entry) and Romania, where extensively upgraded versions are produced.

Variants

SA 330C: First eight French prototypes.

SA 330BB: French Army Aviation version.

SA 330C: Military export version.

SA 330B: Royal Air Force version, designated Puma HC 1.

SA 330B 00: Civilian versions with 1174 kW (1575 shp) Turmo HC powerplant.

SA 330B: Military version with 1174 kW (1575 shp) Turmo HC powerplant. Designated SA 330B by French air force, even though different from the French army's SA 330B.

SA 330B L: Upgraded G II H version with glass-fibre rotor blades.



Westland Puma HC Mk 1

(Tim Ripley)

Specifications (for SA 330)

Powerplant

Two Turbomeca Turmo HC turboshafts

Power: 3150 shp (2350 kW)

Payload: 7055 lb (3200 kg)

Performance

Max speed: 160 mph (271 km/h)

Range: 300 nm (572 km)

Dimensions

Length: 48 ft 1 in (14.7 m)

Rotor diameter: 49 ft 2 in (15 m)

Height: 16 ft 10 in (5.1 m)

Armament

Machine guns; Romanian versions sported fire-flight rocket pods; 9M14M Malyska (AT-3 'Sagger') wire-guided anti-tank missiles; Hull-mounted 20 mm cannons; 220 lb (100 kg) fuel tanks; A-93 air-to-air missiles

Weights

Empty: 8000 lb (3766 kg)

Max TO: 16 315 lb (7400 kg)

SA 330S: Portuguese version with OIB 11 radar for maritime surveillance and Måbils powerplant.
IAH-330A: Romanian-built version. Systems upgrade underway including installation of SOCAT (Optic Search and Combat Anti-Tank) weapon package.
Puma 3000: Proposed Romanian version with glass cockpit.
NSA 330: Indonesian-built version.
AS 330B Gréhalée: Experimental French test bed for Gréhalée ground surveillance radar.

Status

Production continues only in Romania.

Operators

Argentina (coast guard/arms), Algeria, Cameroon, Chile (army), Congo (Zaire), Côte d'Ivoire, Ecuador, Ethiopia, France (army/air force), Gabon, Guinea Republic, Indonesia (air force), Iraq, Kenya, Kuwait, Lebanon, Malaysia, Morocco, Nepal, Nigeria, Pakistan (army/air force), Philippines, Portugal, Romania, Senegal, South Africa, Spain, Sudan, Togo, UAE (Abu Dhabi), United Kingdom (air force).

Manufacturer

Sud-Aviation/Aérospatiale/Eurocopter (France), Westland Helicopters (UK), IPTN (Indonesia), IAR SA Ibrail (Romania).



Eurocopter Super Puma/Cougar (France)

Type: Medium lift helicopter

Accommodation: Two pilots, loadmaster, 25 passengers

Development/History

A "growth" development of the basic Puma, the Super Puma first flew in 1976 boasting more powerful Makila powerplants. Although aimed mainly at the civilian market, Aerospatiale (now Eurocopter) have marketed specific military versions under the brand name Cougar, using the series 532 designation. Stretched versions with greater seating capacity have been fielded, and a wide range of armament options are available. Recent developments have included a number of night vision options and in-flight refuelling for combat-search and rescue. The French Army are also planning to use the Cougar as the platform for their *BOBROD* ground surveillance radar system.

Variants

AS 332B1: First military version with Makila powerplants.

AS 332C: First civil version.

AS 332F1: Naval version.

AS 332L1: "Stretched" civilian version.

AS 332L2 Super Puma Mk 2: Civil transport.

AS 332L3 Super Puma Mk 2 VIP: Civil VIP transport.

AS 332M: Stretched military version, production ceased.

AS 332M1: "Stretched" military version.

AS 532 Cougar Mk 1: In 1980 B, F and M versions re-designated and the name Cougar adopted for military sales.

AS 532AC, UB and UC for short fuselage and military armament; AS 532AL and UL for long fuselage,

military armament; AS 532SC naval, armed anti-submarine/anti-ship.



Eurocopter AS 332 M1 Super Puma

(Eurocopter)

Specifications (for AS 532UL Cougar Mk 1)

Powerplant

Two Turbomeca Makila 1A1 free turbines

Power: 3754 shp (2800 kW)

Max T/O: 15 840 lb (7000 kg)

Fueload: 5000 lb (4500 kg)

Dimensions

Length: 50 ft 11 in (15.5 m)

Rotor diameter: 51 ft 2 in (15.6 m)

Height: 15 ft 9 in (4.8 m)

Performance

Max speed: 173 mph (278 km/h)

Range: 334 nm (618 km)

Weights

Empty: 9540 lb (4330 kg)

Armament

20 mm or 7.62 mm guns; free-flight rockets; naval versions can carry the AM 39 Exocet anti-ship missile or homing torpedoes.



Eurocopter AS 532 UL Cougar Mk 1 with Horizon battlefield surveillance system

(Eurocopter)

Eurocopter Super Puma/Cougar (France)

AS 532 Cougar Mk 2: Stretched version with 1560 kW (2104 shp) M618 1A2 powerplant, Civilian counterpart designated Super Puma II, in-flight refuelling optional, AS 532A2 armed combat rescue version; AS 532U2 unarmed utility with stretched fuselage; AS 532M naval, armed anti-submarine.

Cougar 100: Reduced capability export version.

AS 532UL HGWZDM: Ground surveillance version developed from Gazelle system.

NAS 332B: Indonesian utility designation.

NAS 332F: Indonesian naval designation.

CH-34: Brazilian designation for 332M.

HT-17: Spanish Army designation for 332B.

HD-21: Spanish Air Force search and rescue designation.

HT-21(A): Spanish VIP designation.

Hkp 10: Swedish search and rescue designation.

Status

In production in France and Indonesia.

Operators

Argentina (coast guard, army), Brazil (navy/air force), Cameroon, Chile (army/navy/air force), China, Congo (air), Côte d'Ivoire, Ecuador, France (air force/army), Gabon, Indonesia (navy/air force), Iraq, Japan, Jordan, Kuwait, Malaysia, Mexico (air force), Nepal, Netherlands, Nigeria, Panama, Peru (army), Qatar, Saudi Arabia (navy/air force), Singapore, South Korea (air force), Spain (army), Sweden (air force), Switzerland, Thailand (air force), Iraq, Turkey (army), UAE (Abu Dhabi), Venezuela.



Manufacturer

Avicopter/Eurocopter (France), IPTN (Indonesia) and Singapore models were assembled in country from kits. TAI (Turkey) has signed a deal for co-production.

Eurocopter AS 532SC

Cougar
(Two Raptor)



Eurocopter AS 332A2 Cougar rescue version with in-flight refuelling probe

(Tim Ripley)

Eurocopter BO 105 (Germany)

Type: Light helicopter

Accommodation: Two pilots, three passengers

Development/History

This German light helicopter made its first flight in 1962, and by the mid-1970s was in widespread service with the German Army – some 96 light observation and 200 HOT missile armed anti-tank versions were eventually delivered. Delays in the Franco-German Tiger programme mean it will have to soldier on in these roles until well into the next decade. It has been widely exported to civilian and military customers around the world.

Variants

BO 105C: Initial version.

BO 105CB: Basic light observation/utility version.

BO 105CBS: Stretched utility version, with capacity for five passengers.

BO 105CBS: Stretched utility version, with capacity for six passengers. Designated Hkp-88 by Swedish Army.

BO 105LS: Canadian produced version with up-rated Allison 250-C28C powerplant.

BO 105M (VBM): German scout version.

BO 105PAM-1: Basic German anti-armor version fitted with six HOT missile tubes.

BO 105PAM-1A1: Improved German anti-armor versions with new rotors.

BO 105PAM-1 Phase 2: Proposed German night attack version.

BO 105PAM4: Proposed German scout version with four Stinger air-to-air missiles.

BO 105Sphæria: Trials aircraft with mast-mounted sight.

BO 105ATHA 15: Spanish anti-armor version.



Eurocopter BO 105 CBS

(Eurocopter)

Specifications (for BO 105C)

Powerplant

Two Allison 250-C20B turboshafts

Power: 340 shp (251 kW)

Max TFO: 5511 lb (2500 kg)

Payload: n/a

Dimensions

Length: 28 ft 11 in (8.8 m)

Rotor diameter: 32 ft 3 in (9.8 m)

Height: 9 ft 11 in (3 m)

Performance

Max speed: 145 mph (240 km/h)

Range: 550 nm (1020 km)

Weights

Empty: 2000 lb (1300 kg)

Armament

HOT and TOW wire-guided anti-tank missiles;

20 mm Bicoaxial cannon

BO 105GS4/HR(A.1): Spanish armed scout version with 20 mm cannon.

BO 105LD/HR(L): Spanish observation version.

NBO 105: Basic Indonesian-built version.

NBO 105&: Stretched Indonesian version.

BO 105CBS-S/MSS: Search and rescue/maritime version with surveillance radar.

BO 105 LS-A-1: Powered by two Allison 250-C 28C engines. Super Lifter, optimised for under-slung loads.

EC-Super Five: High performance version of CBS for civil market.

Status

In production.

Operators

Bahrain (Army), Brazil (Army/Air Force), Chile, Colombia (Army), Germany (Army), Indonesia (Army/Air Force), Iraq, Jordan, Kenya, Lesotho, Mexico (Army), Netherlands (Army), Nigeria, Peru (Army), Philippines (Army), Spain (Army), Sweden (Army), Trinidad, UAE (Dubai).

Manufacturer

Messerschmitt-Bölkow-Blohm/Eurocopter (Germany), HPH (Indonesia), OSA (Spain), Eurocopter Canada (Canada).



HAL Advanced Light Helicopter (ALH) (India)

Type: Light multi-role helicopter

Accommodation: Two pilots, 12-14 passengers

Development/History

India's indigenous light helicopter programme was slowed by financial problems throughout the 1980s, delaying the first flight until August 1992. Three prototypes are now flying, but question marks still remain over when it will enter service with the Indian armed forces. The first order for eight was placed in 1997, and the second order is expected in 1998. A production rate of 20 per year is expected from 2002 onwards.

Variants

Army/Air Force: skid landing gear

Naval: wheels and folding tail

Light Attack Helicopter: Proposed gunship version.

Status

In pre-production.

Operators

Nil.

Manufacturer

Helicopter Aeronautics Limited (HAL) (India).



HAL Advanced Light Helicopter

(Jane's Information Group)

Specifications

Powerplant

Two Turboshaes TMO33-20

Power: 2000 shp (1452 kW)

Dimensions

Length: 42.0 ft 4 in (12.80 m)

Rotor diameter: 43.0 ft (13.2 m)

Height: 16 ft 2 in (4.98 m)

Weights

Empty: 5511 lb (2500kg)

Max TO: 11 023 lb (5000kg)

Payload: underslung n/a

Performance

Cruising speed: 152 mph (245 km/h)

Range: 496.8 nm (900 km)

Armament

20 mm cannon turret; five-flight rockets; four air-to-surface guided missiles; two air-to-air missiles; mine dispensers; dipping sonar; two hoisting hoistropes

Eurocopter Tiger (International)

Type: Attack helicopter

Accommodation: Pilot (front), weapons operator (rear) in tandem

Development/History

Intended to replace the Gazelle in French service and the BO 105 in German service, the Tiger has its origins in a memorandum of understanding signed by the two countries in 1984. After a protracted process, a development contract was signed in November 1989 and work began in earnest to produce five prototypes.

In the early years of the programme both France and Germany were keen supporters of the Tiger, but defence cutbacks in the 1990s have forced the delivery programme to be stretched out, with the first batch of 80 airframes for each country not entering service until the next century (Germany in 2001 and France in 2003). Initially, Germany will receive only MH9 close support version, while the French are to receive 20 scout/close support and 16 anti-tank models. Production of the remaining aircraft will then last until 2025, with a total of 216 being built for France and 213 for Germany.

Anti-tank versions are armed with HOT or Trigat anti-tank missiles; a mast-mounted forward looking infra-red sight and air-to-air missiles are also optional. The scout/close support versions are armed with a turret-mounted 30 mm G11 cannon under the nose, air-to-air missiles and rocket pods.

Variants

MH9 Gerlant: Initial German escort version.

MH9: French escort version.

MHC-20tiger: French anti-tank version.

PMH-2 Tiger: Initial German anti-tank version.



Eurocopter Tiger

(Eurocopter)

Specifications

Powerplant

Two MTU/Rolls-Royce/Turbomeca MTR 390 turbo shafts

Power: 3370 shp (2466 kW)

Dimensions

Length: 45 ft 11 in (14 m)

Rotor diameter: 42 ft 7 in (13 m)

Height: 14 ft 2 in (4.3 m)

Weights

Empty: 7275 lb (3299 kg)

Max TO: 12 787 lb (5800 kg)

Performance

Max speed: 174 mph (280 kmh)

Endurance: 2 hours 50 min

Armament

[MH9] G11 AVI-30/761 30 mm cannon; Mistral air-to-air missiles; 68 mm rockets; [PMH-2/MHC] HOT 3/3 wire-guided anti-tank missiles; long-range Trigat infra-red guided anti-tank missiles; AGM-114 laser-guided anti-tank missiles; Stinger or Mistral air-to-air missiles; machine gun pods

Eurocopter Tiger (International)

UH1: German multi-role close support version, originally designated UH1L.
HCP: Export multi-role version, without roof-mounted sight.
U-Tiger: Export anti-tank version.

Status

In pre-production.

Operators

Nil.

Manufacturer

Eurocopter (France/Germany)



Eurocopter Tiger
(Eurocopter)

EH Industries EH.101 Merlin (International)

Type: Shipborne ASW helicopter/utility helicopter

Accommodation: Two pilots, observer, sonar operator

Development/History

This joint British-Italian collaborative programme began in 1979 to develop a Sea King replacement for both countries' navies. Funding was agreed in 1984 to proceed with building nine prototypes and subsequent development. The first prototype flew in the UK in 1987, and since then, the programme has led to the development of dedicated maritime, utility, airborne early war and civil passenger versions. Current order books stand at 44 maritime versions for the British Royal Navy and 22 utility for the Royal Air Force in Wessex and Puma replacement. Italy's Navy has ordered eight maritime, four airborne early warning and four utility versions.

Major orders were expected from Canada but the programme was cancelled in 1993 after a change of government. Export orders now being keenly sought from Canada (Japan), Portugal, Japan and the Middle East. The Merlin programme for the Royal Navy is unique because Westland – the airframe manufacturer – is not the prime contractor. Lockheed Martin is prime contractor, being responsible for integrating the complex anti-submarine sensor and weapon systems with the airframe.

Variants

Merlin HMS 1: Royal Navy maritime helicopter.
EH.101 ASW/ASAW: Italian maritime helicopter.
EH.101 AEW: Italian airborne early warning version.
EH.101 Utility: Italian naval transport version.
Merlin HC 3: RAF support helicopter.
HelGliner: Civilian version.



EH Industries EH.101 Merlin

(GKN Westland)

Specifications (Basic Naval version)

Powerplant

Three Bell-Boycce Turbomeca RM 322
turboshafts (UK); General Electric T700-GE-16A
(Italy)
Power: 6800 shp (5172 kW) - 5142 shp (3824 kW)

Dimensions

Length: 74 ft 10 in (22.8 m)
Rotor diameter: 61 ft (18.6 m)
Height: 21 ft 10 in (6.6 m)

Weights

Empty: 15 700 lb (7121 kg)
Max T/O: 28 640 lb (13 000 kg)
Payload: 6500 lb (2900 kg)

Performance

Max speed: 150 mph (240 km/h)
Range: 625 nm (1158 km)

Armament

Mk 46, Sting Ray torpedoes; Sea Skua nuclear-guided anti-ship missiles; depth charges



CH-148 Petrel: Proposed Canadian maritime version.

CH-149 Chinook: Proposed Canadian rescue version.

Commanche: Proposed Canadian rescue version.

Status

In production.

Operators

Italy (navy), UK (navy/air force).

Manufacturer

Agusta (Italy) and Westland Helicopters/GKN Westland (UK).

Left

EH Industries EH.101 Merlin
(GKN Westland)

Right

EH Industries EH.101 Merlin
(GKN Westland)



NATO Helicopter Industries NH 90 (International)

Type: Multi-role medium-lift/maritime helicopter

Accommodation: Two pilots, (NFH) three systems operators, (TTH) 20 troops

Development/History

This multi-national project began in 1986 and originally involved five nations. However, Britain pulled out in 1987, leaving France, Germany, Italy and the Netherlands to continue building the NATO Frigate Helicopters (NFH) and Tactical Transport Helicopter (TTH). Full scale development began in 1992, and the first prototype flew in 1995. The second prototype equipped with fly-by-wire flight control systems flew in 1997.

Defence cutbacks in Western Europe have led to the programme being scaled down and delivery dates slipped. In mid-1997 the funding for the production/delivery schedule was agreed. The Netherlands is taking 20 NFH versions from 2000, Germany wants 205 tactical transports from 2003 and 18 NFH from 2002, France has ordered 27 NFHs from 2005 and 133 TTHs from 2011, and Italy requires 60 NFHs and 143 TTHs from 2004. In total, 647 helicopters are on order, but few commentators expect the programme to survive future European defence budget cuts.

Variants

NFH 90: NATO Frigate Helicopter for maritime anti-submarine and utility tasks.

TTH: Tactical Transport Helicopter.

Status

In production.

Operators

None.



NH Industries NH 90

Specifications (For NFH)

Powerplant

Two Rolls-Royce Eurotomec/Paggle RTM 322-01/0 or General Electric (Mitsubishi) T800-GE-401X turbo shafts

Power: Respectively 4200 shp (3100 kW) or 4800 shp (3578 kW)

Dimensions

Length: 52 ft 10 in (16.11 m)

Rotor diameter: 53 ft 5 in (16.3 m)

Height: 13 ft 0 in (4.22 m)

Weights

Empty: 14 741 lb (6428 kg)

Max T/O: 20 062 lb (9100 kg)

Payload: 4409 lb (2000 kg)

Performance

Max speed: 186 mph (300 km/h)

Cruise range: 650 nm (1204 km)

Armament

Anti-submarine torpedoes; anti-ship missiles; depth charges; 7.62 mm or 12.7 mm door guns.

Manufacturer

NHI, with Eurocopter
(France/Germany), Agusta (Italy)
and Fokker (Netherlands).



Right:
NH Industries NH90
(Jeremy Fack/MPI)

Agusta A 109 (Italy)

Type: light helicopter (for A 109CM)

Accommodation: Two pilots, six passengers

Development/History

Agusta's stylish light helicopter first flew in 1970 and has sold well around the world since 1975. Armed military versions first entered service with the Italian Army in 1980, although Belgium is the only export customer for this model. To date, more than 570 have been produced in all military and civil versions.

Variants

A 109: Initial production version.

A 109A Mk II: Civil version.

A 109C: "Wide body" version with improved transmission.

A 109EDA: Basic Italian army version.

A 109ECM: Current production military version with sensor weapon improvements.

A 109BA: Belgian Army version with Hellfire wire-guided anti-tank missiles.

A 109E: Improved transmission and longer nose for more visibility.

A 109E2: Swiss export version.

A 109EM: Fixed endocarriage, with 550 kW (738 shp)

Turbomeca Assiil 1K3 Powerplant for 'hot and high' operations.

A 109EN: Naval version.

A 109MA: Medical evacuation version.

A 109GAF: Coast guard version.

A 109 Power: Two Pratt & Whitney 300C powerplant, each rated to 732 shp (546 kW).

Status

In production.



Italian army Agusta A109

(Jeremy Flack/APU)

Specifications

Powerplant

Two Allison 250-C20B1 turboshafts

Power: 600 shp (670 kW)

Max Wt: 5907 lb (2726 kg)

Payload: Underwing 2000 lb (907 kg)

Dimensions

Length: 35 ft 1 in (10.7 m)

Rotor diameter: 35 ft 1 in (10 m)

Height: 11 ft 5 in (3.5 m)

Performance

Max speed: 193 mph (311 km/h)

Range: 420 nm (778 km)

Weights

Empty: 3503 lb (1580 kg)

Armament

TOW-2A wire-guided anti-tank missiles;
machine gun pods; free-flight rocket pods;
Stinger air-to-air missiles.

Operators

Argentina (Army), Belgium,
Italy (Army), Malaysia, Peru
(Army), Slovenia, UK (Army),
Venezuela (Army).

Manufacturer

Agusta (Italy).



Right

Agusta A109 Mangusta

(Tim Ripley)

Agusta A 129 Mangusta (Italy)

Type: Light attack helicopter

Accommodation: Two pilots in tandem

Development/History

Italy's distinctive Mangusta (Mongoose) is the first custom-designed Western European attack helicopter to enter frontline service with a NATO country. With a track record in helicopter construction dating back to 1952, Agusta began working on the Mangusta in the mid-1970s in response to an Italian Army requirement for a specialist anti-armor helicopter.

US experiments with the Cobra and early versions of the Apache obviously influenced the design of the Mangusta, which made its first flight in 1983. Five prototypes were flying by 1985, with a delivery date scheduled for the end of 1987. However, the first production aircraft were not delivered until 1990, with 1.5 being subsequently produced per month. The delay in deliveries was due to funding problems with the Hughes/Emerson/Saab Heli-TOW nose-mounted anti-tank missile sight system.

The initial Italian Army order for 60 aircraft has since been followed by plans to develop a multi-role scout/gunship version. This variant boasts a chin-mounted turret armed either with 12.7 mm (0.50 in) or 15.5 mm (0.61 in) machine guns. If a new-build version is not ordered, then 20 of the original airframes may be converted. Despite the A129 seeing combat service with the Italian United Nations contingent in Somalia during 1993, export orders have not been forthcoming – it has lost out in British, Dutch, Malaysian and several Middle Eastern attack helicopter competitions.



Agusta A129 Mangusta

(Tim Ripley)

Specifications

Powerplant

Two Rolls-Royce 1001D turboshafts
Power: 1650 shp (1230 kW)

Dimensions

Length: 40 ft 3 in (12.3 m)
Rotor diameter: 39 ft (11.9 m)
Height: 11 ft (3.3 m)

Weights

Empty: 5675 lb (2529 kg)
Max T/O: 9033 lb (4090 kg)
External workload: 2645 lb (1200 kg)

Performance

Max speed: 183 mph (294 km/h)
Endurance: 3 hours 5 minutes

Armament

Four hard points; Heli-TOW 2 or 24 wire-guided anti-tank missiles; Hellfire laser-guided anti-tank missile; A129-9L Sidewinder, Stinger, Javelin, Mistral air-to-air missiles; machine gun pods; free-flight rocket pods; 20 mm Gatling gas chin turret; or 12.7 mm (0.5 in) chin gun (tested but not in service).

Variants

A 129: Basic Italian Army anti-tank version.

A 129 Scout: Proposed reconnaissance version with mast-mounted sight and chin gun turret.

A 129 International: Export version with two UH6C 1600 engines, five main rotor blades and improved weapon systems.

A 129 Shipborne: Proposed navalized version.

A 129 Multi-Role: Proposed follow-on to current in-service version, similar in capability to International version, and armed with turret-mounted 20 mm Gatling gun.

Status

In production.

Operators

Italy (armed).

Manufacturer

Agusta (Italy).

Right

Agusta A 129 Mangusta

(Tim Ripley)



Agusta-Bell AB 212 (Italy)

Type: shipborne anti-submarine helicopter

Accommodation: two pilots, sonar operator, radar operator, or seven passengers

Development/History

This specialist anti-submarine version of the popular 412 airframe has become the standard shipborne helicopter for many NATO navies. They are easily identified by the large radar housings above the cockpit and under the forward hull. A variety of surface surveillance radars have been installed, including MEL AB1-5055A, MMWPS-300A or Farnant Scorspray Bendix. MMWOS-15MF dunking sonars have been fitted for anti-submarine work. All weapon carriage is external, with either a mix of anti-submarine torpedoes or anti-ship missiles. Iraqi and Iranian versions saw action during the 1980-88 Gulf War, while Italian, Greek, Spanish and Turkish versions were used to enforce UN sanctions against the former Yugoslavia.

Variants

AB 212 ASW: Basic version.

AB 212EDV: Turkish electronic warfare version.

HA, HB: Spanish designation.

Status

In production

Operators

Greece (navy), Iran (navy), Italy (navy), Peru (navy), Spain (navy), Turkey (navy), Venezuela (navy).

Manufacturer

Agusta (Italy).



Agusta-Bell AB 212ASW

(Tim Alpley)

Specifications (for AB 212 ASW)

Powerplant

one Pratt & Whitney PT6T-6 Turbo Twin Pac

Power: 1875 shp (1388 kW)

Max TD: 11 176 lb (5070 kg)

Payload: 5000 lb (2270 kg)

Dimensions

Length: 42 ft 4 in (12.9 m)

Rotor diameter: 48 ft 2 in (14.7 m)

Height: 14 ft 10 in (4.5 m)

Performance

Max speed: 122 mph (196 km/h)

Range: 300 nm (567 km)

Weights

Empty: 7450 lb (3370 kg)

Armament

AS-12, Sea Killer 2, Sea Skua radar-guided anti-ship missiles; Mk 44, 46 or MD 44 torpedoes; depth charges; machine guns.

Kawasaki OH-1 (Japan)

Type: Light attack and observation helicopter

Accommodation: Pilot, gunner/observer

Development/History

The first military helicopter developed entirely in Japan is intended to replace the OH-6 in Japanese Ground Self Defence Force service in the early part of the next century. A mock up was revealed in 1994, and the first prototype flew two years later. Similar in appearance to the Agusta A 129, but the OH-X features a fenestron tail rotor and 1990s generation materials, sensors and weapon systems. The 1997 defence budget included funding for the first three production aircraft.

Variants

Nil.

Status

In pre-production.

Operators

Nil.

Manufacturer

Kawasaki and Fuji Heavy Industries (Japan).



Kawasaki OH-1

Specifications

Powerplant

Two MHU 511 -10 turboshaft

Power: 1318 shp (1168 kW)

Dimensions

Length: 39 ft 4 in (12 m)

Rotor diameter: 37 ft 9.6 in (11.5 m)

Height: 12 ft 5 in (3.8 m)

Weights

Empty: n/a

Max T/O: 7716 lb (3500 kg)

Payload: n/a

Performance

Cruising speed: 151 mph (243 km/h)

Range: 124 min (200 km)

Armament

Toshiba Type 91 air-to-air missiles; anti-tank guided missiles; free-flight rockets; turret- and pod-mounted cannons/guns

PZL Swidnik W-3 Sokol (Poland)

Type: Medium-lift multi-purpose helicopter

Accommodation: Two pilots, 12 passengers

Development/History

PZL Swidnik began to work on upgrading the old Mi-2 design during the 1970s, and the result of that work, the W-3, began test flying in 1979. Production began in 1985, and it has since entered service with the Polish armed forces.

Development to field armed versions is underway, with the help of South Africa and Israel, to improve the export potential of the helicopter by giving customers western and eastern weapons options.

Variants

W-3 Sokol: Standard civil and military version.

W-3L Huszka: Stretched version with up-rated engine to 740kW (1000 shp) and capacity for 14 passengers.

W-3Bd Arakonda: Polish Navy search and rescue version.

W-3D Salarsandra: Search version.

W-3D-1 Alligator: Proposed anti-submarine version.

W-3W: Low cost armed version for Poland.

W-3SW: Proposed naval strike version.

W-3A: Improved avionics version for western markets.

W-3M: As W-3A with flotation bags.

W-3WB Hazer: Armed version upgraded with assistance from South Africa's Denel using the Newwalk weapon system.

W-3 Salora: VIP transport.

W-3 EW: Proposed electronic warfare version.

W-3 MSJMW: Proposed gunship version with tandem cockpit.

SW-5c: Proposed up-engined with Pratt & Whitney PT6C-07B turboshafts.

Specifications (for Sokol)

Powerplant

Two WS6-PZL Recrow PZL-10W turboshafts

Power: 1000 shp (734 kW)

Dimensions

Length: 46 ft 7 in (14.2 m)

Rotor diameter: 51 ft 6 in (15.7 m)

Height: 13 ft 6 in (4.12 m)

Weights

Empty: 7275 lb (3300 kg)

Max T/O: 14 110 lb (6400 kg)

Payload: 4600 lb (2100 kg)

Performance

Max speed: 158 mph (255 km/h)

Range: 661 sm (760 km)

Armament

(W-3L) twin 20 mm GSh-23L cannon pod; 20 mm cannon in nose turret; 21-3 Grot and Hellfire laser-guided missiles; M414 Sitara (M-4 Spizal) radio- and laser beam-guided anti-tank missiles; 9M32M Strzala (SA-7 Grail) air-to-air missiles; free-flight rockets; mine dispensers

Status

In production.

Operators

Czech Republic, Poland (army/navy/air force), Myanmar.

Manufacturer

PZL Swidnik (Poland).

PZL Swidnik W-3 Sokol

(Tom Ripley)



Kamov Ka-25 (Russia) NATO reporting name 'Hormone'

Type: Shipborne anti-submarine helicopter

Accommodation: Two pilots, [optional] 12 passengers

Development/History

Some 460 Ka-25s were built for service aboard Soviet Navy ships from 1966. It has now been withdrawn from Russian Navy service, but a few are operational elsewhere.

Variants

Ka-25PL: Basic version.

Ka-25F: Proposed land-based attack helicopter.

Ka-25B 'Hormone-A': Original ASW version with search radar, MAD sensor, dipping sonar and sonobuoy launchers.

Ka-25B 'Hormone-B': Specialist version to provide target acquisition mid-course guidance for submarine- and ship-launched cruise missiles. Partially retractable undercarriage.

Ka-25H, H, H: Missile tracking version.

Ka-25PS 'Hormone-C': Specialist search and rescue version, without anti-submarine warfare equipment.

Ka-25Bsh: Mine warfare version.

Ka-25K: Prototype flying crane.

Status

No longer in production.

Operators

India (navy), Russia (navy), Syria (navy), Vietnam, Nagasaki (navy).

Manufacturer

Kamov Aviaton (Bashkortostan/Russia) and Ulan Ude (Russia) to Kamov OKB (Russia) design.



Ka-25B 'Hormone-A' on the Minsk

James

Specifications (for Ka-25Bsh)

Powerplant

Two Kam GTD-3F turboshafts

Power: 1776 shp (1324 kW)

Weights

Empty: 10 505 lb (4765 kg)

Max TOC: 15 875 lb (7200 kg)

Dimensions

Length: 32 ft (9.7 m)

Rotor diameter: 51 ft 7 in (15.7 m)

Height: 17 ft 7 in (5.4 m)

Performance

Max speed: 130 mph (210 km/h)

Range: 351 nm (650 km) with external tanks

Armament

Anti-submarine torpedoes; depth charges

Kamov Ka-27/28/32 (Russia) NATO reporting name 'Helix'

Type: Shipborne anti-submarine helicopter

Accommodation: two pilots, systems operator

Development/History

The Ka-27 series has a larger fuselage than the Ka-25. The first prototype flew in 1974 and it entered frontline service with the Soviet Navy in the early 1980s. Its robust design and rugged construction have proven popular with crews.

Variants

Ka-27PL 'Helix-A': Basic version for Soviet Navy, also known as Ka-252PL.

Ka-27PS 'Helix-B': Naval search and rescue version.

Ka-27PM: Armed version of PS.

Ka-28 'Helix-A': Export version of PL.

Ka-32S 'Helix-C': Civilian utility and rescue version, with up-graded avionics and search radar.

Ka-32T 'Helix-C': Civil utility version.

Ka-32R: Civil flying crane.

Ka-32E: Civil utility version.

Ka-31A1: Fire fighting version.

Ka-32G: Civil version.

Status

In production.

Operators

India (navy), Russia (navy), Vietnam, Yugoslavia (navy).

Manufacturer

Kamov Aviation (Bashkortostan/Russia) or Kamov OJSC (Russia) design.



Kamov Ka-32 'Helix'

(Tom Ripley)

Specifications (Ka-28)

Powerplant

Two Klimov TV3-117V turboshafts

Power: 4380 shp (3206 kW)

Dimensions

Length: 37 ft 1 in (11.3 m)

Rotor diameter: 52 ft 3 in (15.5 m)

Height: 17 ft 8 in (5.4 m)

Weights

Empty: 14 330 lb (6500 kg)

Max TO: 24 250 lb (11 000 kg)

Payload: 11 025 lb (5000 kg)

Performance

Max speed: 160 mph (270 km/h)

Range: 432 nm (800 km)

Armament

Anti-submarine torpedoes; depth charges

Kamov Ka-29 (Russia) NATO reporting name 'Helix-B'

Type: Assault helicopter

Accommodation: Two pilots, 16 troops

Development/History

Capitalising on the success of the Ka-27 family, Kamov fielded this specialist assault helicopter version in the late 1980s. It was designed to operate off the Soviet Navy's amphibious landing ships, and is considered to be the 'naval Mi-24', combining firepower with a troop-carrying capability.

Variants

Ka-290B 'Helix-B': Basic assault transport version, also known as Ka-252TB.

Ka-294B: Airborne early warning and surface surveillance version, redesignated Ka-31

Ka-27K: prototype anti-submarine version based on Ka-29 airframe.

Status

In production.

Operators

Russia (navy).

Manufacturer

Kamov Aviation (Kamovskoye) (Russia) to Kamov OJSC (Russia) design.



Kamov Ka-29

(Rosvoenavtomat)

Specifications

Powerplant

Two Klimov TV3-117V turboshafts

Power: 4380 shp (3206 kW)

Dimensions

Length: 37 ft 1 in (11.3 m)

Rotor diameter: 52 ft 3 in (15.9 m)

Height: 17 ft 8 in (5.4 m)

Weights

Empty: 12 130 lb (5520 kg)

Max T/O: 27 775 lb (12 600 kg)

Payload: 8810 lb (4000 kg)

Performance

Max speed: 174 mph (280 km/h)

Range: 240 nm (440 km)

Armament

Two 7.62 mm Gatling type machine guns in doors; four hard points; 9M114 Shturm (AT-6 Spiral) radio- and laser-guided anti-tank missiles; free-flight rockets; 23 mm or 30 mm gun pods.

Kamov Ka-50/52 (Russia) NATO reporting name 'Hokum'

Type: Attack helicopter

Accommodation: One pilot

Development/History

The Kamov OKB has had an interest in attack helicopters since the mid-1950s, when its design led out to the Mi OKB's Mi-24 in the contest for the Soviet army's battlefield assault helicopter; Kamov resumed work in the 1970s, again with Mi as a rival, to fulfil a requirement for the Mi-24 replacement.

The Kamov Ka-50 first flew in 1982, and won the contest against the Mi's Mi-28 design due to its better agility, heavier armour and firepower. However, the military establishment remained sceptical about the Ka-50's single-seat concept, so work continued on the two-seat Mi-28. First unveiled in public in 1992, the Ka-50 is now being offered for export as the 'Wolverine' or 'Helicopter Saboteur', although it has also been called the 'Black Shark' in promotional material.

The collapse of the Russian defence budget in recent years has left Russian army aviation in limbo: neither the Ka-50 nor Mi-28 have entered frontline service, although 12 production versions of the Ka-50 have been completed and work continues on new versions, with a night-attack and two-seater variant flying in prototype form.

The Ka-50 design is revolutionary, with the coaxial rotor allowing the traditional tail rotor to be dispensed with. By going for a single-seat design, Kamov OKB had to incorporate a significant number of automation devices, such as helmet-mounted sight, head-up displays and computer navigation devices. Defensive equipment includes self-sealing fuel tanks and armoured engines. The pilot has an ejection seat, which



Kamov Ka-50/52 Wolverine

(Tim Ripley)

Specifications (for Ka 50)

Powerplant

Two Kamov TV3-117VK turboshafts

Power: 4380 shp (3266 kW)

Dimensions

Length: 52 ft 6 in (16 m)

Rotor diameter: 47 ft 7 in (14.5 m)

Height: 16 ft 2 in (4.9 m)

Weights

Empty: n/a

Max TO: 23 610 lb (10 690 kg)

Maxload: 6610 lb (3000 kg)

Performance

Max speed: 193 mph (310 km/h)

Endurance: four hours with auxiliary tanks

Armament

One 30 mm 2A42 cannon; 9M130 Vihla-M (AT-16) laser beam riding guided anti-tank missile;

9M114 Shtroum (AT-6 Spiral) radio- and laser-guided anti-tank missiles; Ka-25MP (AS-12

Knight) air-to-surface missiles; free-flight rocket pods; 23 mm and 30mm gun pods; R-60M AA-8 Archer or R-73 (AA-11 Archer) heat-seeking air-to-air guided missiles

Kamov Ka-50/52 Werewolf/Alligator (Russia) NATO reporting name 'Hokum'



First triggers an explosive device to blow off the rotor blades prior to firing the pilot safely away from the fuselage.

Variants

V.001: Initial prototype.

Ka-50 Werewolf/Black Shark/Helicopter Soldier (unofficially 'Hokum-A') (N-005h1): Basic single-seat version.

Ka-52 Alligator (unofficially 'Hokum-B') (N-005h2): Two-seat version.

Status

In limited production.

Operators

Russia (many).

Manufacturer

Progress Aerodyne Aviation Co (Russia) to Kamov OKB (Russian design).

Kamov Ka-50/52 Werewolf

(Tim Ripley)

Mil Mi-2 (Russia/Poland) NATO reporting name 'Hoplite'

Type: Light helicopter

Accommodation: One or two pilots, eight passengers

Development/History

Under Warsaw Pact centralized defence plans, the PZL Svidnik plant was nominated as the sole production site for the Mil 040 Mi-2 design. The first Polish-built Mi-2 flew in 1965, and more than 5200 were built up until production ceased in 1991. The light utility helicopter saw extensive service with Soviet and Warsaw Pact armed forces, including combat operations in Afghanistan and other trouble spots. Civil versions have been licence produced in the USA.

Variants

Mi-2T: Unarmed utility/transport version.

Mi-2TU: Dual control trainer.

Mi-2TU: Agricultural crop sprayer.

Mi-2S: Medical evacuation version.

Mi-2MS Adder: Armed version with 23 mm cannon pod and cabin machine guns.

Mi-2000 Salamandrac: Armed reconnaissance version with 23 mm cannon and free-flight rocket pods.

Mi-200P Azakendac: Anti-tank version with Malyutka guided missiles.

Mi-200PQ: ap-gunner version with 9M32 Strela 2.

Mi-2C Chokla: Chemical and nuclear survey and smoke layer.

Mi-2E: Upgraded version with improved electronics for export to Middle East.

Mi-2RM: naval rescue version.

Mi-2Rac: Reconnaissance version.

Mi-2RS: Chemical reconnaissance version.

Mi-2S: Dual control trainer.



Mil Mi-2 'Hoplite'

(Tom Ripley)

Specifications (for Mi-2T)

Powerplant

Two Klimov GTD-350 turboshafts

Power: 800 shp (595 kW)

Dimensions

Length: 37 ft 4 in (11.4 m)

Rotor diameter: 47 ft 6 in (14.5 m)

Height: 12 ft 3 in (3.7 m)

Weights

Empty: 5295 lb (2400 kg)

Max T/O: 8157 lb (3700 kg)

Payload: 1763 lb (800 kg)

Performance

Max speed: 124 mph (200 km/h)

Range: 237 nm (440 km)

Armament

Free-flight rockets; gun and cannon pods;
9M14M Malyutka (AT-3 Sagger) wire-guided
anti-tank missile; 9M32 Strela 2 (SA-7 Grail)
air-to-air missiles



Mi-2FM: Survey version.

Mi-2D: Airborne command post.

Mi-2 Platani: Mine-laying version.

Mi-2: Reconnaissance trainer.

Variant 51: East German reconnaissance version.

Variant 55: East German maritime version.

Variant 56: East German version.

Kania/Kitty Hawk: Version with Allison 250-C20B turboshaft, also known as Kania Model 1.

Spittler Icarus: US-built version.

Status

Production suspended.

Operators

Bulgaria (air force), Czech Republic, Estonia, Ghana, Guinea Republic, Iraq, Latvia, Libya, Lithuania, Nicaragua, Poland (army/navy/air force), Romania (air force), Russia (army/air force), Slovakia, Syria (air force), Ukraine, USA (army).

Manufacturer

PL: Swoboda (Poland) and Spittler Helicopter Company (USA) to a Mi-02B (Poland) design.

Left

MM Mi-2 'Hoplite'

(Tim Ripley)

Right

MM Mi-2 'Hoplite'

(Tim Ripley)



Mil Mi-6 (Russia) NATO reporting name 'Hook'

Type: Heavy-lift helicopter **Accommodation:** Two pilots, flight engineer, navigator, radio operator, 65-75 troops, 41 stretchers

Development/History

Mil's giant heavy-lift helicopter made its first flight in 1957, and quickly set new standards in load-carrying capacity. The largest helicopter of its generation, the Mi-6 saw widespread service with the Soviet army in Europe and Afghanistan.

Variants

- Mi-6 'Hook-A': Basic version.
- Mi-6P: Civilian passenger version.
- Mi-6U: Military utility version.
- Mi-6MPP/MPPa 'Hook-B': Command/ECW version.
- Mi-6BIS/WYa 'Hook-C': Command type also called Mi-22.
- Mi-6PS: Military rescue version.
- Mi-6PZh/PZhe: Fire-fighting version.
- Mi-6S: Medical evacuation version.
- Mi-6Lp: Convertible version.
- Mi-6RE: Fuel transporter.

Status

No longer in production.

Operators

Algeria, Egypt, Ethiopia, Iraq, Iran, Peru (army/air force), Poland (air force), Russia (army), Syria (air force), Vietnam.

Manufacturer

Rebercol (Factory 160) (Russia) and Factory No 23 (Russia) to Mil 60B (Russia) design.



Mil Mi-6 'Hook'

(Tom Ripley)

Specifications (for Mi-6T)

Powerplant

Two Axial/propeller/Sokolov D-26AM turboshafts
Power: 10 850 shp (8000 kW)

Dimensions

Length: 108 ft 10 in (33.2 m)
Rotor diameter: 114 ft 10 in (35 m)
Height: 32 ft 4 in (9.86 m)

Weights

Empty: 69 055 lb (27 240 kg)
Max TO: 84 657 lb (38 400 kg)
Payload: 26 459 lb (12 000 kg)

Performance

Max speed: 186 mph (300 kmh)
Range: 540 nm (1000 km)

Mil Mi-8/17 (Russia) NATO reporting name 'Hip'

Type: Medium-lift helicopter

Accommodation: Two pilots, optional flight engineers, 24 troops, 12 stretchers

Development/History

The Mi-8 was the work horse of both the Soviet Union's armed forces and their Communist Bloc allies from the mid-1960s. Since the demise of the Soviet Union, the basic soundness of the design, and its low price, has enabled it to carve a major niche for itself in the world helicopter market. Although lacking the avionics of western machines, the glass-nosed Mi-8 combines a useful carrying capacity with the performance to allow it to operate in the most extreme climatic regions.

The Mi-8 first flew in 1961, and has been continually upgraded throughout its long production life. The most significant improvement was the fielding of the up-engined Mi-8MT/W versions, which was designated Mi-17 for export customers – this version proved its worth in the 'hot and high' conditions experienced during the 1979-89 Afghan war. The bloody conflicts on the fringes of the old Soviet empire and in the former Yugoslavia have seen the Mi-8 employed extensively in European war zones since 1991. The United Nations has also hired numerous Mi-8s to support its peace-keeping and humanitarian operations. To date, some 13,000 have been built for home and more than 60 export customers.

Variants

Mi-8 Hip-C: Single engine prototype.

Mi-8 Hip-B: Twin-engine prototype powered by Klimov TV2 turbo shafts.

Mi-8T Hip-C: Standard production version, powered by two Klimov engines, each rated to 1288 kW (1,700 shp). Capable



Mil Mi-8TV 'Hip-B' on UN duty in Croatia

(Tom Ripley)

Specifications (for Mi-SMT)

Powerplant

Two Klimov TV3-117MT turboshafts
Power: 3846 shp (2808 kW)

Dimensions

Length: 69 ft 7 in (21.17 m)
Rotor diameter: 68 ft 10 in (21.3 m)
Height: 18 ft 6 in (5.65 m)

Weights

Empty: 14 500 lb (6700 kg)
Max TO: 26 455 lb (12 000 kg)
Payload: 10 000 lb (4000 kg)

Performance

Max speed: 155 mph (250 kmh)
Range: 510 nm (940 km) with auxiliary tanks

Armament

Door-mounted 12.7 mm machine gun; 9M17 Falanga (AT-2 Swatter) and 9M14 Malyska (AT-3 Sagger) wire-guided anti-tank missiles; 9M114 Strela V (AT-6 Spinal) radio- and laser-guided anti-tank missiles; 9M120 Mtkhr (AT-12) laser beam riding guided anti-tank missile; 9M39 Igla V (SA-18 Grouse) air-to-air missile; fire-flight socket ports

Mil Mi-8/17 (Russia) NATO reporting name: 'Hip'

of being armed with free-flight rocket pods, Aljfi Ulan Ulan-built version.

MS-8PS: Passenger and VIP transport version, also known as Mi-8PP, S or P.

Mi-8TPS: Airborne liaison and command version.

Mi-8MT/7P: Russian military designation for up-engined version with TV3-117M1 turboshafts. TV has minor equipment changes. Ulan Ulan-built version known as Mi-8M/8MS-171. Mi-8 M(M)MTV-1/-2/-3 are conversions to Mi-17 standard with port tail rotor.

Mi-8MTV: TV3-117MA powered version, with pressurized cabin.

Mi-8TBTV 'Hip-E': Armed version with 12.7 mm machine gun in nose and pylon-mounted Falanga missiles.

Mi-8TBK 'Hip-F': Armed export version with six launch rails for Malyska missiles.

Mi-8TL: Air accident investigation version.

Mi-8RW: Reconnaissance/artillery spotting version.

Mi-8MPS: Search and rescue version.

Mi8/2PU or YTC: Airborne radio or command post version.

Mi-8PS 'Hip-D': Airborne command post version.

Mi-8FS: 'Hot & high' desert version.

Mi-8M2N/PU 'Hip-G': Airborne command post and radio relay version.

Mi-8SAV 'Hip-J': Communications jammer(DUM) version.

Mi-8PPA 'Hip-K': Export electronic warfare version.

Mi-8FD: Polish airborne command post version.

Mi-8MA: Arctic/polar exploration version.

Mi-8MB: Military ambulance versions, also known as Mi-8B variants.



Mil Mi-8TV 'Hip-H' of the Ukrainian Army Aviation on UN duty in Croatia
(Tom Ripley)



Mil Mi-8M 'Hip-H' of Iraqi Air Force

(Tom Ripley)

Mil Mi-8/17 (Russian) NATO reporting name "Hip"



Mil Mi-17M "Hip-M"

(Tim Ripley)



Mi-8TD: Liquid-methane fuel version, with external tanks.
Mi-8BAMSh: Night attack and combat rescue version with Sitium and Vicer guided missiles.
Mi-17 "Hip-M": Export designation for up-engined Mi-8MTVMM version with TV3-117M turbo shafts.
Mi-17P/PGP/P "Hip-HMP": Export radar jamming version with large fairings for antennas on either side of fuselage.
Russian versions designated Mi-8MTS/MIFS/MIUM/MIFSMT/MTM/MTM/MTM.
Mi-17Z-2: Czech electronic warfare version.
Mi-17MB: Export version, with TV3-117M engines, arc clamshell rear cargo doors and loading ramp.
Mi-17K: Export version with new avionics.
Mi-17-1M: High altitude operations version with TV3-117M engines.
MS-30: Proposed Korean-built Mi-17-1 version.
Mi-17-N: Military transport and gunship version, with TV3-117M engines.
Mi-17-1VA: Flying hospital version.
Mi-17Z (Mi-17MP): Export version to Mi-8 MTV-3 standard.
Mi-17P: export passenger version.
Mi-8H: Re-used designation for original prototype, new cargo version.
Mi-13: Similar to Mi-9 airborne command post.

Mil Mi-8T "Hip-C" of Croat Air Force seen over Bosnia

(Tim Ripley)

Status

In production

Operators

Afghanistan, Algeria, Angola, Armenia, Azerbaijan, Bangladesh, Belarus, Bosnia-Herzegovina, Burkina Faso, Bulgaria (air force), Cambodia, China, Colombia, Croatia, Cuba, Czech Republic, Executive Outcomes (South Africa), Egypt, Eritrea, Ethiopia, Finland, Germany (army), Hungary, India (air force), Indonesia (air force), Iraq, Kazakhstan, Laos, Libya (air force), Lithuania, Macedonia, Mali, Moldova, Mongolia, Mozambique, Mexico (army), Nicaragua, North Korea, Pakistan (army), Peru (army/air force), Poland (army/air force), Serbia/Republic (Bosnia), Romania (air force), Russia (army/navy/air force), Sierra Leone, Slovakia, Sri Lanka, Sudan, Syria (air force), Tajikistan, Turkey (army), Uzbekistan, Ukraine (army/air force), Venezuela, Vietnam, Yemen, Yugoslavia (air force), Zambia, Georgia, USA (army), United Nations.

Manufacturer

Kazan Helicopter Plant (Tatarstan), MI Moscow Helicopter Plant (Russia), Progress Aviamyev Aviation Co (Russia), Ulan Ule Aviation Plant (Russia), Darwaz (Kazak) to OKB MI (Russia) design.



Mil Mi-8 AMTSA

(Tim Ripley)



Mil Mi-17MD

(Tim Ripley)

Mil Mi-14 (Russia) NATO reporting name 'Haze'

Type: Land-based ASW helicopter

Accommodation: Two pilots, sonar helicopter, MAD operator

Development/History

The Mi-14 is an amphibious version of the Mi-8 developed for the Soviet Navy as a shore-based ASW and rescue helicopter. The first prototypes flew in 1973, and it has since been exported to a number of pro-Soviet states.

Variants

Mi-14: Prototype.

Mi-14PL 'Haze-A': ASW version with dipping sonar, search radar, retractable search radar and sonobuoy dispensers. The TV3-117 engine, rated to 1417 kW (1900 shp), was adopted during the later stages of production.

Mi-14PLM: Later version with better engines and systems.

Mi-14BT 'Haze-B': Mine-sweeper version produced.

Mi-14PS 'Haze-C': Search and rescue version, with nose search light and anti-submarine gear removed.

Mi-14PK 'Haze-A': Polish rescue training version.

Mi-14 Eliminator Mi: Mi converted to fire bomber.

Status

No longer in production.

Operators

Belarus (navy), Cuba, Ethiopia, Libya (navy), North Korea, Poland (navy), Romania (navy), Russia (navy), Syria (navy), USA (army), Yugoslavia (navy).

Manufacturer

Kolomna Helicopter Plant (Tartarstan) to Mil MOB (Russia)



Mil Mi-14PS 'Haze-C'

(Polish MoD)

Specifications (for Mi-14PL)

Powerplant

Two Klimov TV3-117A turboshafts

Power: 3400 shp (2536 kW)

Max T/O: 30 865 lb (14 000 kg)

Payload: n/a

Dimensions

Length: 60 ft 3 in (18.4 m)

Rotor diameter: 69 ft 10 in (21.3 m)

Height: 22 ft 9 in (6.9 m)

Performance

Max speed: 140 mph (226 km/h)

Range: 612 nm (1125 km)

Armament

Anti-submarine torpedoes, depth charges, flare machine guns

Weights

Empty: 25 500 lb (11 750 kg)

Mil Mi-24 (Russia) NATO reporting name 'Hind'

Type: Attack/assault helicopter

Accommodation: Pilot (rear), weapons operator (front), optional flight engineer, eight troops

Development/History

This distinctive Soviet assault helicopter was developed by Mil OKB in response to American experiences in Vietnam. Sometimes called a 'flying tank' because it was the first attack helicopter to feature heavy armour and be armed with a large calibre cannon. In Soviet/Russian service it is nicknamed the 'hunchback'.

The first prototype made its maiden flight in 1970, but this version boasted a full glass, or 'green house', cockpit, rather than the more-familiar tandem layout of latter models. In 1974 the first production versions were spotted operating with Soviet troops in East Germany, and they were soon in widespread service throughout Eastern Europe.

The invasion of Afghanistan in 1979 gave the Mi-24 its first combat experience, and Soviet pilots soon came to value its heavy armoured protection. Only the arrival of US-made Stinger missiles in the hands of Mujahideen rebels threatened Soviet air supremacy, so a crash programme to fit defensive systems to the Mi-24 was begun.

With the fall of the Soviet Union, the Mi-24 has seen extensive service in the wars in the Caucasus - Russian Army Aviation used them to spearhead their invasion of Chechnya in 1994. Budget cuts mean Russian plans to replace the Mi-24 have yet to come to fruition, so it will have to soldier on for many years to come. To boost the Mi-24's appeal to export customers, western sensors and avionics have been integrated into the latest new-build versions.

Variants

V-24(A), 10 'Hind-B': Pre-production versions, with TV-2-117



Mil Mi-24P 'Hind-G2' of the Ukrainian Army Aviation

(Tim Ropley)

Specifications (for Mi-24P)

Powerplant

Two Klimov TV3-117 series II turboshafts
Power: 4380 shp (3206 kW)

Dimensions

Length: 57 ft 5.5 in (17.51 m)
Rotor diameter: 56 ft 9 in (17.3 m)
Height: 13 ft (3.97 m)

Weights

Empty: 14 078 lb (6200 kg)
Max Wt: 26 455 lb (12 000 kg)
Warload: 5290 lb (2400 kg)

Performance

Max speed: 308 mph (325 km/h)
Range: 540 nm (620 km) with auxiliary tanks

Armament

12.7 mm Gatling type gun or twin 23 mm cannon in nose; 9M17 Falanga (AT-2 Swatter) wire-guided anti-tank missile; 9M114 Shturm (AT-6 Spira) radio- and laser-guided anti-tank missile; 9M120 Vihor (AT-16) laser anti-tank guided missile; 9M20 Iglu-V (SA-18 Grouse) and 9A 2300 air-to-air missiles; free-flight rocket pods; 23 mm or 12.7 mm gun pods; twin 30 mm Gsh-30-2 cannon; 30 mm grenade launcher; bombs; chemical weapons; mine dispenser.



engines, rated to 1700 shp.

MI-24A/B 'Wind-W': Original production version with 'green house' front cabin, starboard tail rotor, TV-3-117 engines and Falanga missiles.

MI-24U 'Wind-C': Unarmed training version of 'Wind-W'.

MI-24D 'Wind-D': First version to have tandem cockpit, 13.7 mm cannon and Falanga missiles.

MI-24DU: Dual-control trainer with turret deleted.

MI-25: Export version of MI-24D.

MI-24V 'Wind-E': Introduced radio command-guided Stinger missiles. Powered by TV-3-117A engines. Known as MI-24W in Polish service. Export version MI-35.

NE-24P 'Wind-F': Version of MI-24D armed with ball-mounted twin 30 mm cannon. MI-35P export version.

MI-24MP: MI-24V with twin 23 mm cannon in nose turret.

MI-35P export version.

MI-24R, RR, Rk (Rk) or MR 'Wind G': Chemical and nuclear surveillance version.

MI-24K 'Wind G-2': Artillery fire correction version.

MI-24MM: Night attack version with western sensor and new titanium rotor head.

MI-35M: Export night attack version with western sensor, avionics and new MI-28-style titanium rotor head.

MI-35U: Unarmed export trainer.

MI-24PS: Police/civilians-military version.

MI-24E: Environmental research version.

Left: MI MI-24V 'Wind-E'

(Tim Ripley)

Right: MI MI-24V 'Wind-E'

(Tim Ripley)





Status

In production.

Operators

Afghanistan, Algeria, Angola, Armenia, Azerbaijan, Belarus, Bulgaria (air force), Cambodia, Croatia, Czech Republic, Executive Outcomes (South Africa), Ethiopia, Finland, Hungary, India (air force), Iraq, Kazakhstan, Laos, Libya (air force), Mongolia, Mozambique, Peru (air force), Poland (army), Russia (army), Rwanda, Sierra Leone, Slovakia, Sri Lanka, Sudan, Syria (air force), Tajikistan, Uzbekistan, Ukraine (army), Vietnam, Yemen, Georgia, USA (army).

Manufacturer

Reserval (Russia) and Progress Avionics Aviation Co (Russia) to MI-OKB (Russia) design.

Left: **MM MI-24W 'Hind-E'** of the
Polish Air Force

(Tim Ripley)

Right: **AM MI-38**

(Tim Ripley)



Mil Mi-26 (Russia) NATO reporting name 'Halo'

Type: Heavy-lift helicopter

Accommodation: Two pilots, flight engineer, navigator, 80 troops, 60 stretchers

Development/History

Designed to replace the Mi-6, the Mi-26 is the most powerful helicopter in the world. It has a cargo carrying capacity equivalent to that of the C-130 transport aircraft. First flown in 1977, the Mi-26 entered Soviet Army Aviation service in 1985. The UN has chartered a number to support operations in Somalia and the former Yugoslavia.

Variants

Mi-26: Basic version.

Mi-26B: Civil version with D-136 engines.

Mi-26MB: Flying hospital version.

Mi-26M: Planned upgrade.

Mi-26M2: Tanker.

Mi-26M3: Upgraded version with D-137 engines.

Mi-26P: Proposed 30-seat passenger version.

Mi-26TS: Export version.

Mi-26A: Upgraded navigation systems.

Mi-26RC: Wide-bodied version with D-136 engines.

Status

In production.

Operators

India (Army), Peru, Russia (Army), Ukraine (Army), United Nations.

Manufacturer

Rosenthal (Russia) to Mil (Russia) design.



Mil Mi-26 'Halo'

(Tom Ripley)

Specifications (for Mi-26)

Powerplant

Two ZMKB Progress D-135 turbo-turbine turbo shafts.

Power: 22172 shp (16534 kW)

Dimensions

Length: 110 ft 8 in (33.7 m)

Rotor diameter: 105 ft (32 m)

Height: 26 ft 8 in (8.2 m)

Weights

Empty: 62 170 lb (28 200 kg)

Max lift: 123 450 lb (56 000 kg)

Payload: 44 990 lb (20 000 kg)

Performance

Max speed: 183 mph (295 km/h)

Range: 432 nm (800 km)

Mil Mi-28 (Russia) NATO reporting name 'Havoc'

Type: Attack helicopter

Accommodation: Pilot (rear) and gunner (front)

Development/History

Superficially similar in appearance to the American Apache, the Mi-28 made its first flight in 1983. Since the aircraft lost the Soviet Army Aviation attack helicopter contest to the Ka-50, the Mi-28 has had a troubled history. The Russian Army Aviation has reportedly been persuaded to place an order for the aircraft, but funding difficulties have so far prevented series production taking place. The aircraft has been undergoing almost continuous development for over 15 years to allow it to fly armed attack missions at very low altitudes. Latest versions on display at western airshows include state-of-the-art night vision sensors and mast-mounted sights.

Variants

Mi-28: Basic version.

Mi-28N: Night attack version with improved sensors and mast-mounted sight.

Status

In low rate production.

Operators

Russia (army)

Manufacturers

Kozeravl (Russia) to a Mil OKB design.



Mil Mi-28N 'Havoc' with rotor mounted sight

(Two Biplay)

Specifications (for Mi-28)

Powerplant

Two Klimov TV3-117VM turboshafts

Power: 4300 shp (3200 kW)

Dimensions

Length: 55 ft 3 in (16.85 m)

Rotor diameter: 56 ft 5 in (17.2 m)

Height: 15 ft 9 in (4.87 m)

Weights

Empty: 15 432 lb (7000 kg)

Max T/O: 25 350 lb (11 500 kg)

Maxload: 4000 lb (1814 kg)

Performance

Max speed: 168 mph (300 km/h)

Range: 240 mi (400 km)

Armament

One 2A42 30 mm nose-mounted cannon; 9M30 Iglu V (SA-18 Geosul) and 9A 2200 air-to-air missiles; 9M114 Shturm (AT-6 Spiral) anti-tank guided missile; 9M120 Wither-M (AT-16) laser beam riding guided anti-tank missile; free-flight rockets

Mil Mi-34 (Russia) NATO reporting name 'Hermit'

Type: Light utility helicopter

Accommodation: Two pilots, two passengers

Development/History

Designed as a light utility, observation, training and liaison helicopter for military, police, border guard and civil use, the Mi-34 made its maiden flight in 1988. It was the first Soviet helicopter to be capable of executing a loop or roll.

Production began in 1993, but funding problems slowed deliveries after six had been built. In 1997 production resumed after a corporate restructuring.

Variants

Mi-34: Basic version.

Mi-34v or VA2: Twin-engine version, fitted with VA2-430 twin rotary engines, each rated to 160 kW (217 shp).

Status

In production.

Operators

Russia (air force/army).

Manufacturer

Progress Aerovye Aviation Co (Russia) and VAZ Motor Car Works (Russia) to Mil OKB (Russia) design.



Mi-34

(Mil/TASS)

Specifications (for Mi-34)

Powerplant

VAZB (Kodovoye) M-14V-26 air-cooled radial engine.

Power: 330 shp (239 kW)

Dimensions

Length: 38 ft 7 in (11.71 m)

Rotor diameter: 37ft 9 in (11.6 m)

Height: 10 ft 1 (3.2 m)

Weights

Empty: n/a

Max T/O: 2970 lb (1350 kg)

Performance

Cruising speed: 112 mph (180 km/h)

Range: 224 nm (380 km)

Mil Mi-38 (Russia)

Type: Medium lift helicopter

Accommodation: Two pilots, 32 passengers

Development/History

Conceived as the replacement for the Mi-8/17 in the medium transport role, the Mi-38 programme has not really got beyond the prototype stage because of lack of funding. Development began back in the mid-1980s, and a maiden flight was expected for 1993, but did not occur. It bears many similarities to the EH101 Merlin.

The helicopter has many unique features, including a six-bladed main rotor, a delta 3 type tail similar to the Mi-26's, CRT cockpit displays and extensive use of composite materials. Cargo can be carried under-slung or positioned in the cabin via clam-shell rear doors and a loading ramp. Eurocopter are working jointly with Mil OKB and Kazan Helicopters on the programme.

Variants

Nil.

Status

In pre-production.

Operators

Nil.

Manufacturer

Kazan Helicopter Plant (Bartanstan) to Mil OKB (Russia) design.



Model of the proposed Mi-38

(Paul Jackson)

Specifications (for Mi-38)

Powerplant

Two Klimov TV3-117V turboshafts

Power: 4636 shp (3456 kW)

Dimensions

Length: 64 ft 2.5 in (19.70 m)

Rotor diameter: 64 ft 7 in (21.30 m)

Height: 16 ft 10 in (5.13 m)

Weights

Empty: n/a

Max T/O: 31 000 lb (14 500 kg)

Payload: 11 000 lb (5000 kg)

Performance

Cruising speed: 155 mph (250 km/h)

Range: 700 nm (1300 km)

Armament

Nil

Mil Mi-40 (Russia)

Type: Assault transport helicopter

Accommodation: Two pilots, 10 troops

Development/History

Intended as an assault transport version of the Mi-28 attack helicopter, it shares many of the systems of the Mi-28, including engine transmission, main and tail rotors.

Variants:

Mi-

Status

In pre-production.

Operators

RU.

Manufacturer

Assumed to be Mil OMS (Russia) design.



Model of the proposed Mi-40

(Paul Jackson)

Specifications (for Mi-40)

Powerplant

Two Klimov TV3-117MA turboshafts

Power: 4380 shp (3266 kW)

Dimensions

Length: 54 ft 5 in (16.60 m)

Rotor diameter: 56 ft 5 in (17.20 m)

Height: 14 ft 5 in (4.40 m)

Weights

Empty: 16 920 lb (7675 kg)

Max T/O: 25 137lb (11 480 kg)

Payload: 20 601 lb (9300 kg)

Performance

Cruising speed: 183 mph (295 km/h)

Range: n/a

Armament

Anti-tank guided missiles; two-flight rockets; gun pods.

Denel Aviation CSH-2 Rooivalk (South Africa)

Type: Attack helicopter

Accommodation: Pilot (rear), co-pilot/gunner (front)

Development/History

South Africa's Rooivalk (Red Kestrel) has its origins in an attack helicopter programme that commenced in 1991 in order to develop a successor to the Alouette III gunships then being used in Angola and South West Africa. The South African Air Force has ordered a squadron's worth, but defence cuts have put the order in doubt. Malaysia's new army aviation command may well be the first customer for the Rooivalk.

Variants

XDM: Experimental Development Model

CSH-2: Basic production model.

ADM: Advanced development model.

Status

In pre-production.

Operators (proposed)

Malaysia (army), South Africa (air force).

Manufacturer

Atlas Aviation/Denel Aviation (South Africa).



Denel Aviation Rooivalk

(Denel Aviation)

Specifications (for CSH-2)

Powerplant

Two Turax turboshafts

Power: 4000 shp (2982 kW)

Weighted: 3022 lb (1371 kg)

Dimensions

Length: 54 ft 7 in (16.5 m)

Rotor diameter: 40 ft 5 in (12.08 m)

Height: 15 ft (4.6 m)

Performance

Max speed: 152 mph (245 km/h)

Range: 507 nm (940 km); 720 nm (1335 km) with external fuel

Weights

Empty: 11 610 lb (5270 kg)

Max T/O: 20 723 lb (9400 kg)

Armament

One 20 mm GA-1 Fattler cannon; 21-3 Swift, 21-35 or 21-6 Molekpa laser-guided anti-tank missiles; VSC Darter or Rukh air-to-air missiles, free-flight rockets

Denel Aviation CSH-2 Rooivalk (South Africa)



Denel Aviation Rooivalk

(Denel Aviation)

Denel Aviation Oryx (South Africa)

Type: Transport helicopter

Accommodation: Two pilots, 20 passengers

Development/History

This South Africa-developed version of the Puma is being aggressively marketed by Denel to users needing helicopters optimized for 'hot and high' bush conditions. In many ways it is similar to the Super Puma because it uses Makila powerplants, but Denel have gone further by modifying the tail section, plus building in the provision for an extensive array of armance. Previously known as Gembok.

Variants

Option 1: Gun turret version.

Option 2: Side-mounted free-flight rocket launchers.

Option 3: Nose-mounted free-flight rocket armament.

Option 4: Anti-armor gunship.

Status

In production.

Operators

South Africa.

Manufacturer

Atlas Aviation/Denel Aviation (South Africa)



Mock up of the stabilised sighting system fitted to an Oryx (AFI)

Specifications (for Oryx)

Powerplant

Two Turbomeca Makila 1A1 free turbines

Power: 3754 shp (2800 kW)

Max UO: n/a

Payload: n/a

Dimensions

Length: 59 ft 6 in (18.15 m)

Rotor diameter: 49 ft 2.5 in (15 m)

Height: 16 ft 10.5 in (5.14 m)

Performance

Cruising speed: n/a

Range: 303 nm (561.6 km)

Armament

Free-flight rockets: 8 or 16 ZT-3 Swift or ZT-35 laser-guided anti-tank missiles; Barter or Wiper air-to-air missiles; 20 mm cannon-gun turret

Weights

Empty: n/a

Westland Wasp (UK)

Type: Light general-purpose helicopter

Accommodation: One pilot, three passengers

Development/History

Once the primary shipborne small helicopter of the British Royal Navy, the Wasp is now obsolete and is in the process of being phased out of service by its last remaining users.

Variants

Wasp HAS 1: Shipborne version

Status

No longer in production

Operators

Indonesia (navy), Malaysia (navy), New Zealand (air force)

Manufacturer

Saunders-Roe/Westland Helicopters (UK)



Westland Scout AH.Mk 1

(Tim Ripley)

Specifications

Powerplant

One Rolls-Royce Bristol Nimbus 503 turboshaft
Power: 710 shp (520 kW)

Dimensions

Length: 30 ft 4 in (9.2 m)
Rotor diameter: 32 ft 3 in (9.8 m)
Height: 11 ft 8 in (3.6 m)

Weights

Empty: 3452 lb (1566 kg)

Max T/O: 5500 lb (2485 kg)
Payload: 1500 lb (680 kg)

Performance

Max speed: 120 mph (193 km/h)
Range: 263 nm (488 km)

Armament

Mk 46 torpedoes; AS12 wire-guided missiles;
Mk 44 depth charges

Westland Lynx (Army version) (UK)

Type: Light multi-purpose military helicopter

Accommodation: Pilot, observer/gunner, 10 troops

Development/History

The British Army's primary light helicopter is another product of the Anglo-French Helicopter Agreement of 1967. Britain's Westland brought Lynx design to the table, and it duly became responsible for its development, production and marketing. Some 112 AH 1s were built for the British Army with skid landing gear, but export sales proved elusive. The British Army Air Corps and Royal Marines (Royal Navy later converted their fleets to armed helicopters (HELARM) by fitting US-made TOW anti-tank missiles. A further 24 AH 1 light battlefield helicopter versions were produced from 1988 to equip 24 Airmobile Brigade.

Variants

AH 1: Original British Army utility version. Some examples armed with TOW missiles.

AH 1GE: Interim armed version until AH 7 developed.

AH 5: Experimental version.

AH 6: Proposed Royal Marines version, not produced.

AH 7: British Army upgraded armed helicopter (HELARM) version with eight TOW missile tubes.

AH 8: British Army light battlefield helicopter version with Rolls-Royce Gem 42-1 powerplant, each rated at 846 kW (1135 shp), tricycle under carriage and BHP rotor blades.

Battlefield Lynx: Proposed export version with provision for Hellfire or HOT anti-tank missiles.

Battlefield 800: Proposed export version with LH8EC 1000 engines.

Mk.24/25: Proposed Iraqi export versions.

Mk.82: Proposed Egyptian export version.



Westland Lynx AH Mk 9

(Tim Ripley)

Specifications (for AH 1)

Powerplant

Two Rolls-Royce Gem 2 turboshafts

Power: 1800 shp (1342 kW)

Max 1FD: 10 000 lb (4536 kg)

Payload: 2000 lb (907 kg)

Dimensions

Length: 49 ft 9 in (15.2 m)

Rotor diameter: 42 ft (12.8 m)

Height: 11 ft 6 in (3.5 m)

Performance

Cruising speed: 161 mph (258 km/h)

Range: 340 nm (630 km)

Weights

Empty: 6040 lb (2740 kg)

Armament

TOW and improved TOW wire-guided anti-tank missiles; 12.7 mm or 20 mm door or pod-mounted machine guns; free-flight rockets.

Westland Lynx (Army version) (UK)

Mk 81: Proposed Saudi export version.

Mk 84: Proposed Qatar export version.

Mk 85: Proposed UAE export version.

Lynx ACH: Experimental advanced compound helicopter with wings for additional lift.

Status

No longer in production.

Operators

UK (Army/Royal).

Manufacturer

Westland Helicopters (UK).



Westland Lynx AH.Mk 7
(Tom Ripley)

Westland Lynx (Navy version) (UK)

Type: Light multi-purpose naval helicopter

Accommodation: Pilot, observer/gunner, 10 troops

Development/History

Westland's development of the naval Lynx has proved far more success than its effort with the army versions. In addition to the 11 bought by the British Royal Navy, more than 200 have been sold for export, with new orders continuing to be secured.

Armed with the Sea Skua missile, the Lynx proved a potent ship killer both during the Falklands conflict and the 1991 Gulf War. After the Falklands, the Royal Navy began major upgrade programmes to improve the rotor blades, powerplant, sensors, weapon systems and defensive aids. This programme has continued through to the current HAS 2 standard, which is dubbed the Super Lynx.

Variants

HAS 2(FN): French Navy anti-submarine warfare version, with Omera-Segat ORB 31W radar and Alcatel dinking screen.

HAS 2: Original British Royal Navy version, with Ferranti Scanspy radar, Bendix dipping sonar and Texas Instruments MAS.

HAS 2i: Improved British version with two Rolls-Royce Gern 41-1 101 (shp) engines.

HAS 3ICE: Specialist British version for Arctic operations from HMS Endurance.

HAS 3S: Specialist British version with surveillance and secure communications equipment.

HAS 3DM: Improved British version for Gulf War with AL-107 electronic counter-measures pod and infra-red jammers.

HAS 3CTS: Improved British version with central tactical



Westland Lynx Mk 21

(GKN Westland)

Specifications (for HAS 2)

Powerplant

Two Rolls-Royce Gern 2 turboshafts
Power: 1000 shp (1242 kW)

Dimensions

Length: 49 ft 9 in (15.2 m)
Rotor diameter: 42 ft (12.8 m)
Height: 11 ft 6 in (3.5 m)

Weights

Empty: 6000 lb (2740 kg)
Max T/O: 10 000 lb (4535 kg)

Payload: 2000 lb (907 kg)

Performance

Cruising speed: 161 mph (259 kmh)
Range: 340 nm (630 km)

Armament

Mk 44, Mk 46 or Sting Ray anti-submarine torpedoes; Mk 11 depth charges; Sea Skua radar guided anti-ship missile; AS12 wire-guided missiles; 12.7 mm or 30 mm gun pods

Westland Lynx (Navy version) (UK)

systems and flotation bag.

HAS 4 (FR): Improved French Navy version with new Gem 41-1 engine, and gearbox.

Mk 21: Export version for Brazil, designated SH-11.

Mk 21A: Export version of Super Lynx to Brazil.

Mk 23: Export version to Argentina (later sold to Brazil and Denmark).

Mk 25/SH-14A: Export utility version for Netherlands.

Mk 27/SH-14B: Export version for Netherlands with sonar.

Mk 30: Export version for Denmark.

Mk 31/SH-14C: Export version for Netherlands with MAD

Mk 36: Export version for Norway.

Mk 37: Export version for Argentina.

Mk 38: Export version for Germany.

Mk 39: Export version for Nigeria.

Mk 30: Export version for Denmark.

HAS 8: Super Lynx upgraded version, with up-rated Rolls-Royce Gem 42-1 engines, BERP rotor blades, thermal imaging sensors and improved electronic warfare systems.



Above:
Westland Lynx HAS Mk 8/Super Lynx (GKN Westland)



Left:
Westland Lynx HAS Mk 2 (FR)
(Tim Ripley)

Mk 95: Export Super Lynx for Portugal.
Mk 99: Export Super Lynx for South Korea.
SH-140: Export version for Netherlands with up-rated Rolls
Royce Gem 40-1 engines and full ASW kit.
Super Lynx Series 200/300: Export version with LHDC
CTS900, improved avionics and 'glass' cockpit.

Status

In production.

Operators

Brazil (navy), Denmark (navy), France (navy), Germany (navy),
Malaysia (navy), Netherlands (navy), Nigeria (navy), Norway
(navy), Pakistan (navy), Portugal (navy), South Korea (navy),
UK (navy).

Manufacturer

Westland Helicopters/GEH Westland (UK).

Notes:

Westland Lynx HAS Mk 8/Super Lynx
(GKN Westland)



Kaman Seasprite (USA)

Type: Shipborne anti-submarine helicopter

Accommodation: Two pilots, sonar operator, four passengers

Development/History

Making its first flight in 1959, the SH-2F version of the Sea Sprite utility helicopter was selected in 1970 by the US Navy for work on frigates, destroyers and cruisers in the anti-submarine role, under the LAMPS I programme. It lost out to the SH-60 in the LAMPS II contest, and the bulk of the US Navy's fleet have been either relegated to reserve service or retired into storage. A programme to upgrade some surplus US versions to the anti-ship missile-armed SH-2G standard is underway, and the improved helicopter has recently found export success in Australia and New Zealand.

Variants

UH-2B: Shipborne utility helicopter for US Navy.
SH-2B: Initial winner of US Navy Light Airborne Multi-Purpose System (LAMPS) platform contest for embarked small ship helicopter. Powered by two T50-GE-8 Powerplants.

SH-2F: Improved version with 701 longer life rotor blades, new search radar and towed MAD boom.

SH-2G Super Seasprite: Advanced version powered by two General Electric T700-GE-401 turboshafts, each rated to 1285 kW (1723 shp). It has improved missile sensors and weapon carriage capabilities.

SH-200E: Specialist anti-submarine warfare upgrade for Egypt.

SH-26(A): Australian export version.

SH-26(M): Proposed version for Malaysia.

Status

Work continues on SH-2G standard upgrades.



Kaman SH-2F of HSL-34

(Jeremy Flack/APU)

Specifications (for SH-2G)

Powerplant

Two General Electric T700-GE-401 turboshafts
Power: 3446 shp (2530 kW)

Payload: 4000 lb (1814 kg)

Performance

Max speed: 159 mph (256 km/h)
Range: 478 nm (885 km) with external tanks

Dimensions

Length: 80 ft 6 in (24.54 m)
Rotor diameter: 44 ft 4 in (13.5 m)
Height: 15 ft 2 in (4.6 m)

Armament

Mk 40, 50 torpedoes; depth charges; 7.62 mm door guns; Penguin Mk 2 Mod 7 radar-guided anti-ship missile; AGM-65B/SM-2 Maverick air-to-surface guided missile

Weights

Empty: 9200 lb (4173 kg)
Max T/O: 13 500 lb (6124 kg)

Operators

Argentina (navy), Australia
(navy), Pakistan (navy), New
Zealand (air force).

Manufacturer

Kaman Aerospace (US).



Right:

*Kaman SH-2F of HSL-34
(Jeremy Flack/AP)*

Bell Model 47 Sioux (USA)

Type: Light helicopter

Accommodation: Two pilots, one passenger

Development/History

One of the first helicopters to go into large-scale production after making its first flight in 1945, some 5,000 have since been built. Although it has now been withdrawn from frontline service by most NATO states, it can still be found in use in obscure corners of Asia and South America.

Variants

H-13 Sioux: Basic US Army and USAF version.

HH-13HNL-1/2/3/4/5/6/7: US Navy trainer version.

HHL-1177: US Navy version for training and ice-breaking ship operations.

OH-13: Three-seat version.

UH-13: US Navy training version.

AB-47: Italian-built version.

AB 47G-2: UK-built version, designated Sioux AH 132.

Status

No longer in production.

Operators

Columbia, Congo (Zaire), Greece (air force), Italy (army).

Lesotho, Libya (army), New Zealand, Pakistan (army).

Paraguay, Peru (air force/navy), South Korea (army), Uruguay (navy), Zambia.

Manufacturer

Bell Aircraft Corporation/Bell Helicopter Company (USA), Agusta (Italy), Westland Helicopters (UK), Kawasaki Heavy Industries (Japan).



Bell 47G operated by the British Army as the AH.1 Sioux

(AP/)

Specifications (for Model 47G-3B-2A)

Powerplant

One Lycoming TVO-425-F1A piston engine

Power: 200 hp (149 kW)

Dimensions

Length: 31 ft 7 in (9.6 m)

Rotor diameter: 37 ft 1 in (11.3 m)

Height: 9 ft 3 in (2.8 m)

Weights

Empty: 2093 lb (954 kg)

Max T/O: 2950 lb (1338 kg)

Performance

Max speed: 95 mph (160 km/h)

Range: 215 nm (397 km)

Bell Model 204/UH-1 Iroquois (Huey) (USA)

Type: Light utility helicopter

Accommodation: Two pilots, seven passengers

Development/History

The first of the famous 'Huey' family of helicopters which bore the brunt of the US Army campaign in Vietnam. Several thousand built for the US armed forces from 1954 through to the late 1960s.

Variants

HH-1A: Initial production version for US Army with Lycoming XT53-L-1 turboshaft, rated at 835 kW (1025 shp). Capacity of six passengers. Source of 'Huey' nickname.

HH-1B: Enhanced version with capacity for seven passengers and revised main rotor blades.

UH-1A: Re-designation in 1962 of HH-1A.

UH-1B: Re-designation in 1962 of HH-1B.

UH-1C: Improved version of UH-1B, with T53-L-11 powerplant.

UH-1E: US Marine Corps version with hoist and twin 7.62 mm diam gun turret.

TH-1E: US Marine Corps dual-control trainer.

UH-1F: USAF ballistic missile site security version with General Electric T58-GE-3, rated to 962 kW (1290 shp).

TH-1F: Trainer version of UH-1F.

HH-1E: US Navy rescue version with hoist and T53-L-13 powerplant, rated to 1044 kW (1400 shp).

UH-1L: US Navy utility version with T53-L-13 powerplant.

TH-1L: US Navy training version with T53-L-13 powerplant.

UH-1M: US Army version with night vision sensor fit.

AB 204: Italian-built version, with powerplant options including T53-GE-3, rated at 962 kW (1290 shp), Textron Lycoming T53-L-11A or Rolls-Royce Snecma H 1200, rated at



Agusta Bell AB 204B

(Jeremy Fleck/MPO)

Specifications (UH-1C)

Powerplant

One Textron Lycoming T53-L-11

Power: 1100 shp (820 kW)

Max Wt: 9500 lb (4309 kg)

Payload: 1361 lb (620 kg)

Dimensions

Length: 42 ft 7 in (12.98 m)

Rotor diameter: 44 ft (13.41 m)

Height: 12 ft 7.25 in (3.84 m)

Performance

Cruising speed: 140 mph (226 km/h)

Range: 332 nm (615 km)

Weights

Empty: 5071 lb (2299 kg)

Armament

Door machine gun; machine gun pod; fire-flight rocket pod; M8 44 torpedoes.

Bell Model 204/UH-1 Iroquois (Huey) (USA)



632 kW (1250 shp).

Hkp 3B: Swedish designation of AB 204.

AB 204AS: Italian-built naval version, with

T50-GE-3 powerplant, rated at 562 kW

(1250 shp)

Fuji-Bell 204B-2: Japanese-built version, also known as Hiyodori.

Huey Tag: UH-1C with up-rated engines.

HH-2: Research version.

Status

No longer in production.

Operators

Austria, Colombia (air force), Honduras, Indonesia (army), Italy (army), Japan (army), Panama, Paraguay, Somalia, South Korea (army), Spain, Sweden (army), Thailand (army), Turkey (army/navy), Yemen.

Manufacturer

Bell Aircraft Company/Bell Helicopter Company (USA), Agusta (Italy), Fuji-Bell (Japan).

The Swedish army operates the AB 204 as the Hkp 3B

(Army Fleet/APF)

Bell Model 205/UH-1 Iroquois (Huey) (USA)

Type: Medium-lift helicopter

Accommodation: Two pilots, 12 passengers, six stretchers

Development/History

The first major upgrade of the ever popular 'Huey', which featured a stretched and enlarged cabin to boost carrying capacity. The first of 2500 ordered for the US armed forces entered service in 1963, whilst the last H-model was produced as recently as 1996. It is set to continue in US military service until well into the next century.

Variants

UH-1D: Original US Army version, with Lycoming T53-L-11 powerplant, rated to 820 kW (1100 shp). Capable of carrying 12-14 passengers.

UH-1H: Updated version for US Army, uprated with T53-L-13 powerplant.

UH-1V: US Army medical and rescue version with hoist.

UH-1H: Canadian training version, designated CH-119.

EH-1H: Electronic warfare 'Quick Fix' version.

HH-1H: USAF rescue version.

UH-1HP Huey II: Commercial upgraded version with improved powerplant.

Huey 800: Commercial upgraded version with HREC T800 powerplant.

UH-1J/T800-Ultra Huey: Commercial upgraded version with General Electric T800-GE-701C powerplant, rated to 1400 kW (1900 shp).

HH-1H: Japanese-built version.

AB 205A: Italian-built military version, designated EM-2, with T53-L-13 powerplant.

AB 205A-1: Improved Italian 204A.

AB 205B0: Prototype Italian version with two Osprey H



Bell UH-1D of German Luftwaffe

(Tom Ripley)

Specifications (for UH-1H)

Powerplant

One Textron Lycoming T53-L-13 turboshaft

Power: 1400 shp (1044 kW)

Max TFD: 5500 lb (1300 kg)

Payload: 2880 lb (1309 kg)

Dimensions

Length: 41 ft 9 in (12.6 m)

Rotor diameter: 48 ft (14.6 m)

Height: 14 ft 5 in (4.4 m)

Performance

Max speed: 127 mph (204 km/h)

Range: 276 nm (511 km)

Armament

Two machine guns in door; optional rockets and machine gun pods

Weights

Empty: 5710 lb (2592 kg)

Bell Model 205/UH-1 Iroquois (Huey) (USA)



1200 powerplants.

AB 205(A): Prototype Turbomeca Astazouz powerplants.

HE 108: Spanish designation for AB 205.

Advanced 205D: Proposed Japanese upgrade.

Status

No longer in production.

Operators

Argentina (army/navy/air force), Australia (army), Bahrain, Bangladesh, Bolivia, Bosnia-Herzegovina, Brazil (air force), Brunei, Canada, Chile (army/air force), Colombia (air force), Croatia, Dominican Republic, Dubai, El Salvador, Germany (army/air force),

Green (army/air force), Guatemala, Honduras, Indonesia (army), Iran (army, navy, air force), Italy (army), Israel, Jamaica, Japan (army, justice, missile (air force), Morocco, Myanmar, New Zealand (air force), Oman, Pakistan (army), Panama, Papua New Guinea, Peru (air force) navy), Philippines, Saudi Arabia (air force), Singapore, South Korea (army/air force), Spain (army), Sarawak, Taiwan (army/air force), Tanzania, Thailand (army/navy/air force), Tunisia, Turkey (army/air force), Uganda, UAE (Dubai), USA (army/air force), Uruguay (air force), Venezuela (army/air force), Zambia, Zimbabwe.

Manufacturer

Bell Helicopter Company/Bell Helicopters Textron (USA), Agusta (Italy), AHC (Taiwan), Bolkov (Czechway), Fuji-Bell (Japan)

**Bell UH-1H of
US Army
Reserve
(Tim Ripley)**

Bell Model 212 UH-1N Iroquois (Twin Huey) (USA)

Type: Medium-lift helicopter

Accommodation: Two pilots, 14 passengers

Development/History

A twin-engine 'Huey' was first proposed by Bell Helicopters, Pratt & Whitney Canada and the Canadian Government in 1968. The USAF took delivery of the first aircraft in 1970, and it soon became the standard utility helicopter of the US Marine Corps. Foreign sales followed in large numbers, with more than 882 being built to date.

Variants

UH-1N: Basic US Navy and Marine Corps version.

WH-1N: USAF and US Marine Corps VIP transport.

CH-135: Canadian version, later designated CH-135 Twin Huey.

Twin Two-Twelve: Civil commercial version.

AB 212: Italian-built utility version, with Pratt & Whitney Canada P167-3 turbo-Twin-Pac powerplant.

AB 212ASW: Italian maritime version (described elsewhere).

HU-1H: Spanish Army designation.

UH-1N (40M): Four-blade USMC upgraded version

Status

In production.

Operators

Argentina (army/air force), Austria, Bahrain, Bangladesh, Bolivia, Brazil, Chile (air force), Dominican Republic, Ecuador (air force), El Salvador, Ghana, Greece (army/air force), Guatemala, Guyana, Iran (army/navy), Iraq, Israel, Italy (army/air force), Jamaica, Japan (army), Lebanon, Malta, Mexico (air force), Morocco, Oman, Panama, Peru (air force),



Bell UH-1N of the USAF

(USAF)

Specifications (UH-1N)

Powerplant

Two Pratt & Whitney Canada P167-3B turbo

Twin Pac

Power: 1800 shp (1342 kW)

Dimensions

Length: 42 ft 4 in (12.9 m)

Rotor diameter: 48 ft 2 in (14.7 m)

Height: 14 ft 10 in (4.53 m)

Weights

Empty: 6057 lb (2765 kg)

Max T/O: 11 200 lb (5080 kg)

Payload: 5000 lb (2268 kg)

Performance

Max speed: 117 mph (188 km/h)

Range: 343 nm (450 km)

Bell Model 212 UH-1N Iroquois (Twin Huey) (USA)



Philippines, Saudi Arabia (air force), Singapore, Slovenia, South Korea (air force), Spain (army/navy), Sri Lanka, Somalia, Sudan, Thailand (air force/navy), Tunisia, Turkey (army), Uganda, Uruguay (air force), Venezuela (army), Yemen, Zambia, UAE (Dubai), UK (army), USA (navy/marines), United Nations.

Manufacturers

Bell Helicopter Company/Bell Helicopters Textron
(USA/Canada), Agusta (Italy)

*Bell UH-1N of the USMC
(Tom Ripley)*

Bell Model 214 (USA)

Type: Medium utility and transport helicopter

Accommodation: two pilots, 16 passengers

Development/History

The first customer for this high specification version of the 'Huey' was the Imperial Iranian armed forces during the final years of the Shah's regime. Sales have followed to a number of customers who have been prepared to pay premium prices for a superior helicopter.

Variants

214A Italian: Italian-funded development, powered by Textron Lycoming T5500D, rated to 1520 shp (2050 kW).

214B BigLifter: Civilian version.

214C: Search and rescue version.

214SE: Twin-engine version, powered by CT7-2As, with stretched fuselage and composite rotor blades.

Status

No longer in production.

Operators

Brazil, Colombia (air force), Ecuador, Iran (army/navy/air force), Iraq, Oman, Peru (air force), Philippines, Thailand (navy), UAE (Dubai), Venezuela.

Manufacturer

Bell Helicopter Company/Bell Helicopters Textron (USA).



Bell 214

(Jeremy Flack/AP)

Specifications (for 214ST)

Powerplant

two General Electric CT7-2A turboshafts

Power: 1625 shp (121.2kW)

Dimensions

Length: 491 3.5 in (15.62 m)

Rotor diameter: 52 ft (15.98 m)

Height: 101 ft 10.5 in (4.84 m)

Weights

Empty: 9445 lb (4284 kg)

Max UTO: 2883 lb (1304 kg)

Payload: 2200 lb (1000 kg)

Performance

Cruising speed: 161 mph (259 kmh)

Range: 493 nm (908 km)

Armament

Door-mounted machine guns

Bell Model 412 (USA)

Type: Medium utility and transport helicopter

Accommodation: two pilots, 14 passengers

Development/History

The most recent version of the 'Huey' still manages to find customers around the world. A number of companies are also offering upgrade packages to basic versions.

Variants

412: Basic production version.

412SP: Special Performance version, with improved fuel capacity, known as Anapaho in Norwegian service.

412HP: Emergency medical services version, with improved transmission and PT6I-3BE Twin Pac.

Military 412: Armed version.

412EP: Enhanced performance version with additional fuel.

Designated Griffin HT 1 in UK service.

CH-146 Griffon: Canadian military version of 412SP.

MB6-412: Indonesian-built version.

AB412 Griffone: Italian-built military version. Designated M-4 in Italian service.

AB412 CRESO: Italian-built ground surveillance radar platform.

Hög 11: Swedish designation.

AB 412 EP: Agusta-built version.

Status

In production.

Operators

Bahrain, Botswana, Canada, Colombia (air force), Guatemala, Guyana, Finland (coast guard), Honduras, Indonesia (armed), Italy (Army/Haeytair force), Lesotho, Netherlands (air force),



Bell 412

(Tom Alamy)

Specifications (for 412HP)

Powerplant

One Pratt & Whitney Canada PT6I-3D-1 Turbo

Twin Pac

Power: 1800 shp (1342 kW)

Dimensions

Length: 42 ft 4 in (12.92 m)

Rotor diameter: 46 ft (14.02 m)

Height: 15 ft (4.57 m)

Weights

Empty: 6654 lb (3018 kg)

Max T/O: 11 900 lb (5397 kg)

Performance

Cruising speed: 140 mph (226 km/h)

Range: 400 nm (745 km)

Armament

Door-mounted machine guns; cannon pods; rocket pods; air-to-air and air-to-surface missiles

Norway, Peru (air force), Poland (air force), Saudi Arabia (air force), Slovenia, South Korea (air force), Sri Lanka, Sudan, Sweden (army), Thailand (air force/army), Uganda, UAE (Dubai), United Nations, UK (MoD), Zimbabwe.

Manufacturer

Bell Helicopters Textron (USA/Canada), Agusta (Italy), IPTN (Indonesia)



Bell 412 of Dubai Police Air Wing (Tom Ripley)

Bell Model 206 JetRanger (USA)

Type: Light helicopter

Accommodation: Two pilots; three passengers

Development/History

The best-selling JetRanger first flew in 1968, and three years later the US Army began to take delivery of the OH-58 variant (see separate entry). It has since been adopted by a large number of armed forces around the world. Some 7700 had been built by 1995.

Variants

Model 206A JetRanger: First production version, with Allison 250-C18 engine, rated to 236.54 kW (317 shp).

Model 206B JetRanger II: Second production version, with Allison 250-C20, rated to 258 kW (348 shp).

Model 206B-3 JetRanger III: Improved version with 250-C20B powerplant.

Model 206 AS: Chilean navy version, armed with torpedoes.

TH-67 Crook: US Army version of JetRanger II, adopted for basic flight training under designation H1206.

Model 206L-1 LongRanger: Stretched fuselage version of JetRanger II.

Model 206L-2 LongRanger II: Improved L-1, with Allison 250-C28B turboshaft, rated to 388 kW (520 shp).

Model 206L-3 LongRanger III: Improved version with Allison 250-C30F turboshaft rated to 486 kW (656 shp).

Model 206L-4 LongRanger IV: Canadian-built version.

Model 206LT TwinRanger: Canadian-built twin-engine version.

Model 206L TransRanger: Proposed military version of L-2.

Cancon CB 206L-III: Proposed gunship version for Iraq, built in Ohio.

TH-67A SeaRanger: US Navy training version to 206A.



Bell 206 in United Nations service in Croatia

(Tim Ripley)

Specifications (206B-3 JetRanger III)

Powerplant

One Allison 250-C20B turboshaft
Power: 420 shp (313 kW)

Dimensions

Length: 21 ft 2 in (6.5 m)
Rotor diameter: 33 ft 4 in (10.2 m)
Height: 9 ft 6 in (2.9 m)

Weights

Empty: 1625 lb (737 kg)
Max T/O: 3200 lb (1451 kg)
Payload: Under-wing 1500 lb (680 kg)

Performance

Max speed: 140 mph (225 km/h)
Range: 395 nm (732 km)

Armament

Door guns, torpedoes



standard.
TH-57B SeaRanger: US Navy training version to 2008 standard.
TH-57C SeaRanger: US Navy training version to Jet Ranger II standard.
AB 206A-1: Italian-produced military version to 206A standard, designated DB-3 by Italian military.
AB206A-2: Italian-produced military version to 206B standard, designated DB-2 by Italian military.
AB206C-1: Italian-modified A-1s upgraded to A-2 standard with -C20 engines.
Hop 6A: Swedish designation of Italian-produced 206A.
HB-128: Spanish designation of AB 206A-1.
Zafar 300: Iranian-produced version of 206B-1.

Status

In production.

Operators

Austria, Bangladesh, Brazil (navy), Brunei, Cameroon, Chile (army/navy), Columbia (air force), Cyprus, Croatia, Ecuador (air force), Greece (army/air force), Guatemala, Guyana, Jamaica, Israel, Iran (army/navy), Italy (army), Libya (army), Malta, Mexico (air force), Morocco, Oman, Pakistan (army), Peru (army/navy/air force), Saudi Arabia (air force), Slovenia, South Korea (navy), Sri Lanka, Sweden (army/navy), Tanzania, Taiwan (air force), Thailand (arms), Turkey (army), Uganda, UAE/Dubai, USA (army/navy), United Nations, Venezuela (army/police/guard), Yemen.

Bell 206L-4 LongRanger 4
(Bell Helicopters)

Manufacturer

Bell Helicopter Company/Bell Helicopters Textron (USA/Canada), Agusta (Italy), Cardon Industries (Chile)

Bell Model 206/OH-58 Kiowa (USA)

Type: Light observation and utility helicopter

Accommodation: Pilot, co-pilot side-by-side, three passengers

Development/History

The US Army bought some 2000 versions of the OH-58 Kiowa from 1969 onwards to fly scout missions with specialist equipment fitted. The basic design has since undergone a number of upgrades to enhance its battlefield survivability.

Variants

OH-58A: Original US Army scout version.

OH-58B: Export version for Austrial Army.

OH-58C: Upgraded US Army version with flat glass canopy and Allison T63-A720 turboshafts, rated to 313 kW (420 shp).

COH-58A: Canadian version to OH-58A standard, later re-designated CH-136 Kiowa.

Model 206B-1 Kiowa: Australian produced version, later renamed Kulkadee.

Status

No longer in production.

Operators

Austria, Australia (Army/Kiwoy), Canada, USA (Army).

Manufacturer

Bell Helicopter Company/Bell Helicopter Textron (USA),
Commonwealth Aircraft Company (Australia).



US Army OH-58A Kiowa

Jeremy Flack/APW

Specifications (for OH-58A)

Powerplant

One Allison T63-A-700 turboshaft

Power: 317 shp (236.5 kW)

Weights

Empty: 1580 lb (713 kg)

Max (GOW): 3000 lb (1361 kg)

Dimensions

Length: 32 ft 3.52 in (9.84 m)

Rotor diameter: 35 ft 4 in (10.77 m)

Height: 9 ft 6.5 in (2.91 m)

Performance

Cruising speed: 122 mph (196 kmh)

Range: 260 nm (481 km)

Bell Model 406/OH-58D Kiowa Warrior (USA)

Type: Light armed reconnaissance helicopter

Accommodation: Two pilots side-by-side

Development/History

The 'ultimate' version of the OH-58, the Kiowa Warrior boasts an impressive weapon and sensor fit to allow it to operate alongside the AH-64 Apache as part of joint air attack teams. The Army Helicopter Improvement Program (AHIP) began in 1989, and the first helicopters entered service in 1995.

Variants

OH-58D Kiowa Warrior: US Army armed Scout version.
Multi-Purpose Light Helicopter: US Army modification including folding rotor blades and tail to allow transport in C-130 transport aircraft.

Prime Chance: Code-name for first aircraft fitted with Hellfire and Stinger missiles for shipping escort duties in Middle East in 1987.

MH-58D/400C Combat Scout: Saudi Land Forces version. Also features provision for GMM 20 mm cannon but no main-rotorcraft sight.

OH-58D: Stealth technology demonstrator.

Status

In production.

Operators

Saudi Arabia (army), Taiwan (army), USA (army)

Manufacturer

Bell Helicopter Textron (USA)



Bell OH-58D Kiowa Warrior

(Bell Helicopter Textron)

Specifications

Powerplant

One Allison T703-AD-700 turboshaft
Power: 650 shp (485 kW)

Max L/O: 5000 lb (2265 kg)
Workload: 2000 lb (907 kg)

Dimensions

Length: 34 ft 4 in (10.5 m)
Rotor diameter: 35 ft (10.7 m)
Height: 12 ft 10 in (3.9 m)

Performance

Max speed: 147 mph (237 km/h)
Range: 250 nm (463 km)

Weights

Empty: 3045 lb (1381 kg)

Armament

Stinger air-to-air missiles; AGM-114 Hellfire laser-guided anti-tank missiles; machine gun pods; free-flight rocket pods

Bell Model 209/AH-1F/G Huey Cobra (USA)

Type: Attack helicopter

Accommodation: Pilot, gunner in tandem cockpit

Development/History

Bell Helicopters first produced a gunship version of the Huey in 1965 as a private venture. Its distinctive tandem seating and nose turret have since been copied by attack helicopter designers around the world. Some 1000 G-models were bought by the US Army, and it proved very effective when used in action during the later years of the Vietnam war. The need to counter rising Soviet armoured formations during the Cold War led to a series of upgrading programmes to provide the Cobras with the capability to fire TOW wire-guided anti-tank missiles. Sensor upgrades improved the performance at night and in bad weather. Israeli, Iranian and Turkish forces have used TOW-armed Cobras in combat in the Middle East. US Army late-model Cobras were used in the 1991 Gulf War, and in conflicts in Somalia, Haiti and Bosnia.

Variants

Model 209: Original prototype.

AH-1G: Original US Army gunship version, with T53-L-13 turboshaft rated to 1044 kW (1400 shp).

TH-1H: Dual control trainer version.

AH-1E: Enhanced Cobra armament version with TOW missiles.

AH-1P: TOW missile armed version.

AH-1Q: Upgraded version to allow TOW missile carriage.

AH-1R: Upgraded version with T53-L-703 powerplant.

Improved AH-1S: US Army common upgraded standard for its 610 models, with T53-L-703 powerplant.

Production AH-1S: New-build versions to AH-1S standard.

Up-gunned version has 20 mm cannon nose turret.



US Army AH-1G

(Jeremy Fack/AFPO)

Specifications (for AH-1F)

Powerplant

One Textron (Lycoming T53-L-703) turboshaft.

Power: 1800 shp (1342 kW)

Max TQ: 10 000 lb (4536 kg)

Performance

Cruising speed: 141 mph (227 km/h)

Range: 274 nm (507 km)

Dimensions

Length: 53 ft 1 in (16.18 m)

Rotor diameter: 44 ft (13.41 m)

Height: 13 ft 1.5 in (4.05 m)

Armament

Four hard points; eight TOW wire-guided anti-tank missiles; free-flight rockets; M107 20 mm cannon in nose turret; 20 mm grenade launcher in nose turret.

Weights

Empty: 6588 lb (2985 kg)

AH-1F: Re-designation and upgrade of US Army MH-9E model Cobras, features flat cockpit glass, nose TOW sight and T53-L-700 powerplant. Current in-service version. Advanced AH-1 (Model 300 King Cobra) Experimental version with single Lycoming T-55-L-7C powerplant.

Status

No longer in production.

Operators

Bahrain, Israel, Japan (Army), Jordan, Pakistan (Army), South Korea (Army), Thailand (Army), Turkey (Army), United Nations.

Manufacturer

Bell Helicopter Company/Bell Helicopters Division (USA), Fuji-Bell (Japan).

Right:

AH-1G Huey Cobra of the Maryland National Guard

(Jeremy Flack/AP)



Bell Model 209/AH-1W Super Cobra (USA)

Type: Attack helicopter

Accommodation: Pilot, co-pilot/gunner in tandem

Development/History

US Marine Corps requirements for a twin-engineled gunship to allow safe over sea operations led to the fielding of the AH-1J from 1971 onwards. Iran ordered an improved version but this was abandoned after the fall of the Shah in 1979. The US Marine Corps took over the programme which led to the 'Whiskey' version. It saw action during the 1990 Gulf War, claiming hundreds of kills on Iraqi tanks with its laser-guided Hellfire missiles.

Variants

AH-1J Sea Cobra: US Marine Corps version with two Pratt & Whitney Canada T400-CP-400 turboshafts, rated to 1342 kW (1800 shp) each.

AH-1J International: Export version of AH-1J.

AH-1T Improved Sea Cobra: Upgraded AH-1J for US Marines with improved T400-MV-402 powerplants, each rated at 1468 kW (1970 shp).

AH-1W Super Cobra: Basic US Marine Corps version with improved T700-GE-401 powerplants, each rated at 1586 kW (1723 shp).

Cobra Venom: Proposed UK version.

AH-1W (MRV): Proposed upgrade for US Marine Corps, providing four main rotor blades and weapon system improvements.

AH-1RD: Romanian-produced version, with customised weapon systems.

Model 309 King Cobra: Experimental upgrade with two engines and improved weapons systems.

Model 240: Experimental four-blade version.



Bell AH-1W Cobra

(Bell Helicopter Textron)

Specifications (AH-1W)

Powerplant

two General Electric T700-GE-400 turboshafts

Power: 3446 shp (2320 kW)

Workload: 4552 lb (2065 kg)

Performance

Max speed: 173 mph (278 km/h)

Range: 365 nm (667 km)

Dimensions

Length: 45 ft 6 in (13.9 m)

Rotor diameter: 48 ft (14.6 m)

Height: 13 ft 6 in (4.1 m)

Weights

Empty: 10 200 lb (4627 kg)

Max T/O: 14 750 lb (6680 kg)

Armament

One three-barrel M197 30 mm gun in nose turret; four hard points; 10W wire-guided anti-tank missiles; Hellfire laser-guided anti-tank missiles; AIM-9L Sidewinder air-to-air missiles; gun pods; cluster bombs; free-flight rocket pods

Status

In production.

Operators

USA (marines), Thailand (army), Turkey (army)

Manufacturer

Bell Helicopter Company/Bell Helicopter Textron (USA), IAR SA Brasso (Romania).



Bell AH-1W Cobra
(Bell Helicopter Textron)

Bell/Boeing V-22 Osprey (USA)

Type: Tilt-rotor transport

Accommodation: Two pilots, crew chief; 24 troops

Development/History

This revolutionary aircraft has gone through a prolonged development phase but has now progressed to production, with the first examples being delivered in 1998. The Osprey uses its rotors to take off vertically, and they then rotate to provide the power for horizontal flight. Current plans call for some 452 to be purchased by the US Marines to replace their CH-46 assault helicopters. The first unit, HMM-264 The White Knights, is scheduled to become operational at MCRAS Cherry Point, North Carolina, by 2001. The USAF has a requirement for 50 Ospreys for special operations missions to be in service by 2006. The US Navy wants 48 Ospreys for combat search and rescue. Low rate initial production began in 1997 at five aircraft a year, rising to eight in 2000, with a decision on full production due that same year.

Variants

V-22 EMD: Engineering and manufacturing development aircraft.

MV-22B: US Marine Corps assault production version.

SV-22A: Proposed initial US Navy anti-submarine warfare version.

CV-22B: USAF special operations production version.

BN-22B: US Navy combat search and rescue production version.

Bell-Boeing 609: Civilian passenger/air transport tilt rotor, built to a smaller scale.

Status

In production.



Bell Boeing V-22 Osprey

(Bell Boeing)

Specifications (V-22B)

Powerplant

Two Allison 1400-AD-400 turboshafts

Power: 12 300 shp (9072 kW)

Dimensions

Length: 57 ft 4 in (17.5 m)

Rotor diameter: 30 ft (9.1 m) each

Height: 17 ft 4 in (5.28 m)

Weights

Empty: 31 885 lb (14 462 kg)

Max L/O: 55 000 lb (24 947 kg)

Payload: 20 000 lb (9072 kg)

Performance

Max speed: 115 mph (185 kmh) in helicopter mode;

316 mph (509 kmh) in fixed wing mode

Range: 1200 nm (2224 km)

Armament

Door-mounted machine guns; maritime versions may be adapted to carry torpedoes and depth charges

Operators

US (navy/marines/air force)

Manufacturer

Bell Helicopters (aircraft) and
Boeing Helicopters (USA)



Bell Boeing V-22 Osprey
(Bell Boeing)

Boeing CH-47 Chinook (USA)

Type: Heavy-lift helicopter

Accommodation: Two pilots, crew chief, 55 troops, 24 stretchers

Development/History

The 'mighty' Chinook first flew in 1961 to fulfil a US Army requirement for a heavy-lift helicopter. Viewed by the US Army as a 'Flying truck', it proved its worth in Vietnam supporting air mobile troops and flying supplies and artillery pieces to remote jungle fire bases. The large under-slung load capacity of the Chinook soon led it to being nicknamed 'Hooch' by US troops. Some 254 A-models were built for use during the Vietnam War, and more orders soon followed. A constant upgrade programme has significantly improved the capability of the US Army's Chinooks over the ensuing decades. Just under 500 were in service with the US Army, US Army Reserve and National Guard in 1997.

During the 1991 Gulf War CH-47Ds played a key role moving the air mobile forces of the 101st Airborne Division deep behind Iraqi lines. They also opened the way for US paratrooper forces to enter Bosnia in 1996 by lifting pontoon bridge sections into position across the Sava River. Foreign customers have also found the Chinook much to their liking, and sales have been brisk both from the main plant in Philadelphia and other licence production lines. Iran, Italy, Japan and the United Kingdom have been the largest customers for the Chinook, Britain using its aircraft extensively in the Falklands, Northern Ireland, the 1991 Gulf War and Bosnia. Iran found them invaluable during the 1980-88 war against Iraq, whilst Italy operated its helicopters freely in Somalia in 1993, and then during the evacuation of its citizens from Albania during the 1997 civil war.

Following Britain's example of using the Chinook to move



Boeing CH-47D

(Tom Ripley)

Specifications (for CH-47D)

Powerplant

Two Textron Lycoming T55-L-712 turboshafts
Power: 5000 shp (3474 kW)

Dimensions

Length: 51 ft (15.5 m)
Rotor diameter: 60 ft (18.3 m) each
Height: 18 ft 11 in (5.8 m)

Weights

Empty: 26,916 lb (12,210 kg)
Max T/O: 54,000 lb (24,494 kg)
Payload: 27,082 lb (12,284 kg)

Performance

Max speed: 177 mph (285 km/h)
Range: 613 nm (1126 km)

Armament

Door machine guns

its air mobile brigade, the Netherlands has ordered Chinooks to provide mobility for its new rapid reaction force. The US Army use their Chinooks for special forces operations, with night vision devices and in-flight refuelling equipment fitted to allow low-level penetration behind enemy lines at night. Britain's Royal Air Force is also procuring a version with similar capability for long range combat search and rescue missions.

Boeing's Chinook won the battle for international orders against Sikorsky's Sea Stallion, with more than 1000 built, or ordered, for the US Army and export by 1997.

Variants

CH-47A: Original US Army version, with T55-L-5 powerplants, rated to 1511 kW (2030 shp).

CH-47B: Upgraded US Army version with T55-PC turboshafts, rated to 2125 kW (2850 shp) and increased rotor diameter.

CH-47C: Further improved US Army version with T55-L-11A turboshafts, rated to 2798 kW (3750 shp), and extra fuel capacity.

CH-47D: US Army version with T55-L-712 turboshafts for better performance and triple-hook hook for improved handling of under-slung loads.

CH-147: Canadian version to CH-47C standard.

HC-17: Spanish version to CH-47C standard.

Chinook HC 1: British version to CH-47C standard, but with triple-hook capacity.

Chinook HC 1B: British version retrofitted with glass fibre blades.

Chinook HC 2: British version to CH-47D standard.



Boeing CH-47D

(Tim Ripley)

Boeing CH-47 Chinook (USA)

Chinook HC 3: British version to MH-47E standard.

MH-47D Special Operations aircraft: Interim upgrade for US Army special operations until fielding of MH-47E.

MH-47E: Special forces version with in-flight refuelling, night flying capability and T55-L-713 SS engines, each rated to 3264 kW (4378 shp).

Model 414: Export model to CH-47C standard.

International Chinook: Export model to CH-47D standard.

CH-47C Plus: Italian-built version with T55-L-412E powerplants and composite blades.

CH-47J: Japanese-built version to CH-47D standard.

BV214MR: Civilian version.

ICM CH-47D: Improved Cargo helicopter upgrade for US Army, possibly to be designated CH-46F.

Advanced Chinook: Proposed version with 5000 shp (3729 kW) class engines, redesigned rotors and additional fuel.

Status

In production.

Operators

Argentina (air force), Australia (army), Egypt, Greece (army),

Iran (army/air force), Italy (army), Japan (army/air force),

Morocco, Netherlands, Singapore, South Korea (army), Spain

(army), Taiwan, Thailand (army), UK (air force), USA (army).

Manufacturer

Vertol Aircraft Corporation/Boeing Vertol/Boeing Helicopters (USA), Kawasaki Heavy Industries (Japan), Elisberlin Meridionali/Agusta (Italy).



Boeing CH-47 HC.Mk 2

(Tom Ripley)



Boeing CH-47 HC.Mk 2

(Tim Alpay)

Boeing 107/CH-46 Sea Knight (USA)

Type: Medium-lift helicopter

Accommodation: Two pilots, crew chief, 25 troops

Development/History

The cambered rotor-bladed Vertol Model 107 made its first flight in 1958 and entered service with the US Marine Corps in 1964. Nicknamed the 'Frog', it saw extensive service as an assault helicopter during the Vietnam War. Subsequent operations in Grenada, the Persian Gulf, Somalia, Liberia and Haiti have seen the CH-46 in the centre of the action. An upgrade programme kept the aircraft flying through the 1970s, 80s and 90s as the mainstay of the Marine Corps' embarked helicopter fleet. The Pentagon is keen to replace the ageing, and increasingly unreliable, CH-46 with the Sikorsky UH-60. Delays in the V-22 programme mean the 'Frog' will have to soldier on into the 21st century.

US Navy fleet support squadrons are large users of the CH-46, operating from shore bases or supply ships. Foreign exports have been small, with Japanese production lines being the main centre of activity. One of the more famous exploits of the aircraft was its use by the Swedish Navy to hunt Soviet submarines in the Baltic Sea during the 1980s.

Variants

107 Model 11: Civilian version.

HRB-1/CH-46A: Original US Marine Corps assault version with two T58-G2-8B powerplants, each rated to 932 kW (1250 shp).

UH-46A: US Navy utility and cargo transport version.

CH-46D: Upgraded US Marine Corps version with T58-G2-10 turboshafts.

UH-46D: Upgraded US Navy version with T58-G2-10 turboshafts.



Boeing CH-46E Sea Knight

(Tim Ripley)

Specifications (for CH-46E)

Powerplant

Two General Electric T58-G2-10 turboshafts
Power: 3740 shp (2788 kW)

Max TQ: 23 000 lb (10 433 kg)

Payload: 9000 lb (4082 kg)

Dimensions

Length: 44 ft 10 in (13.7 m)

Rotor diameter: 51 ft (15.5 m) each

Height: 16 ft 8 in (5.1 m)

Performance

Max speed: 150 mph (256 km/h)

Range: 700 nm (1285 km)

Armaments

Door machine guns

Weights

Empty: 12 067 lb (5497 kg)



HH-46D: US Marine Corps rescue version.

CH-46F: Final production version for US Marine Corps, with improved avionics.

CH-46E: Upgrade B- and F-models for US Marine Corps, includes glass fibre rotor blades, improved avionics and TSO-C6-16 powerplants.

WH-46F: VIP version for US Marine Corps.

CV-107 (JMA): Japanese-built utility version, exported to Saudi Arabia.

Hkp 4: Swedish designation for CV-107.

CH-113 Labrador: Canadian search and rescue version.

CH-113A Voyageur: Canadian army version.

Status

No longer in production.

Operators

Canada, Japan (army/navy/air force), Sweden (navy), Saudi Arabia (air force), USA (navy/marines).

Manufacturer

Vertol Aircraft Corporation/Boeing Vertol/Boeing Helicopters (USA), Kawasaki Heavy Industries (Japan).

Boeing CH-46D Sea Knight

(Tim Ripley)

Boeing/Sikorsky RAH-66 Comanche (USA)

Type: Reconnaissance/attack helicopter

Accommodation: two pilots in tandem

Development/History

The US Army's much troubled scout helicopter replacement programme has received significant funding, but as yet production is still uncertain. Boeing and Sikorsky won the LHX contract to replace the Cobra, OH-6 and OH-58 in 1991, their first prototype flying in 1996. They have been contracted to supply six aircraft for testing to the US Army by 2000 under a \$1,699 billion contract. The second aircraft is to fly in 1998.

The Comanche has a number of unique features, including a bearingless main rotor and shrouded tail rotor. It is the first helicopter to be developed using 'stealth' technology to minimise its radar cross-section, heat signature and engine noise.

Variants

Nil

Status

In pre-production.

Operators

US Army.

Manufacturer

Boeing Helicopters and Sikorsky Aircraft (USA).



Boeing/Sikorsky RAH-66 Comanche

(Boeing/Sikorsky)

Specifications (for RAH-66)

Powerplant

Two UH-6C 1300/6H-801 turboshafts

Power: 2688 shp (2004 kW)

Dimensions

Length: 43 ft 4 in (13.2 m)

Rotor diameter: 39 ft (11.9 m)

Height: 11 ft 1 in (3.4 m)

Weights

Empty: 7240 lb (3285 kg)

Max TO: 10 112 lb (4587 kg)

Maxload: 2612 lb (1185 kg)

Performance

Max speed: 304 mph (328 knts)

Range: 1260 nm (2344 km) with external tanks

Armament

Under development



Boeing/Sikorsky RAH-66 Comanche

(Boeing Sikorsky)

Boeing OH-6 Cayuse/MD500/MD530 (USA)

Type: Light utility helicopter

Accommodation: One or two pilots, four passengers

Development/History

The OH-6 Cayuse was developed by the Hughes Helicopter Inc for the US Army's Light Observation Helicopter (LOH) requirement in the early 1980s. Soon nicknamed the 'Loach', it saw active service in Vietnam in large numbers. Hughes, and later McDonnell Douglas, have continued to develop and upgrade the basic design, with more than 4000 having being built by 2007.

Variants

Model 200/300C (Cage): Fairweather of 500 series, which lacks enclosed rear fuselage. Military versions designated OH-56. Schweizer Aircraft have since developed the design.

OH-6A (Model 300M) Cayuse: Original US Army light observation helicopter, known as the Loach.

OH-6B: Re-engined version with HC-A-720 powerplant, rated to 313.33 kW (420 shp).

OH-6C: Proposed five-bladed version with improved Allison 25-C70 engine, rated at 298 kW (400 shp). Commercial derivatives designated Model 500D and E.

OH-6J: Japanese-built version to OH-6A standard.

MH-6B: Special forces version.

MH-6C: Special forces version.

EH-6B: Special forces command post/electronic warfare version.

AH-6C: Special forces attack version.

Hughes 500: Civil version of the OH-6A/Model 300 with Allison 25B-C78A turboshaft, rated to 236.5 kW (317 shp).

Model 500C: Export version modified for 'hot-and-high' operation.



Boeing MD500 in Israeli service

(XDF Spokesman)

Specifications (for Model 500E)

Powerplant

One Allison 25B-C70B turboshaft

Power: 450 shp (333.6 kW)

Payload: (500E) 2000 lb (907 kg)

Performance

Max speed: 152 mph (243 km/h)

Range: 233 mi (401 km)

Dimensions

Length: 23 ft (7.01 m)

Rotor diameter: 26 ft 5 in (8.05 m)

Height: 8 ft 9 in (2.67 m)

Armament

10W wire-guided anti-tank missiles; Stinger air-to-air missiles; 30 mm cannon pod; 7.62 mm machine gun pod; low-flight rocket pods; 40 mm grenade launcher; Mk 44 or 46 target pods

Weights

Empty: 1445 lb (655 kg)

Max TO: 3000 lb (1361 kg)



Model 500M Defender: Commercial version of OH-6A.
OH-6D: Japan-built version based on up-engined Hughes 500, five-bladed main rotor and T-tail.
HWS00M: Italian-built version based on up-engined Hughes 500.
Model 500M(RSW): Export version for Spain with MAD boom.
Model 500MD Defender: Military version with armor and infra-red exhaust suppression.
Model 500D Scout Defender: Armed reconnaissance version.

Model 500M(JAW) Defender: Maritime version with search radar and MAD boom.
Model 500M(TOW) Defender: Anti-tank missile armed version.
Model 500M(MMS-TOW) Defender: Anti-tank missile version with mast-mounted sight.
Model 500MD Quiet Advanced Scout Defender: Four-bladed version with noise suppression.
Model 500MD Defender II: Armed version with quiet slow turning four-bladed rotor.

An OH-6 of the Danish army (APV)

Boeing OH-6 Cayuse/MD500/MD530 (USA)

Model 500E: Revised version with pointed nose, improved tailplane and Allison 25-C208 powerplant.

MH-500E: Italian-built version of 500E.

Model 500MD Defender: Specialist military version of Model 500E.

Model 520MK Black Tiger: Korean-built military version.

MD530F Lifter: Five-bladed main rotor fitted with pointed nose, powered by Allison 250-C30 turbo shaft, rated to 317 kW (425-shp).

EH-6E: Special forces command post/electronic warfare version with Allison 250-C30 powerplant.

MH-6E: Special forces version with Allison 250-C30 powerplant.

AH-6F: Special forces attack version Allison 250-C30 powerplant.

MD530MG Defender: Military version with Allison 250-C30 powerplant.

MD530 NightFox: Night attack version with improved sensors and powerplant.

MD530MD Paramilitary Defender: Specialist version powerplant for police and border patrol.

MD530H Lifter/MH-6H: Special forces version to MD530MG standard, with glass cockpit and 'people plank'.

AH-6G: Special forces attack version to MD530 standard.

MH-6J: Special forces version with improvements to MH-6H.

AH-6K: Special forces attack similar to MH-6H standard.



MD530H on test at Mesa, Arizona (APV)

Status

In production.

Operators

OH-6

Brazil (air force), Japan (army), Taiwan (air force).

MD500

Argentina (army/air force), Bolivia (air force), Colombia (air force), Costa Rica, Croatia, Cyprus, Denmark (army), El Salvador, Finland, Greece (air force), Indonesia (air force), Israel, Italy (air force), Kenya, Mauritania, Mexico (air force), North Korea, South Korea (army/navy), Taiwan (army).

MD530

Chile (army), Colombia, Mexico (air force).

Manufacturers

Hughes Tool Company/Hughes Helicopter Inc/McDonnell Douglas Helicopter Company/Boeing Helicopters (USA), Breda Nord/Siparia (Italy), Kawasaki Heavy Industries (Japan), Korean Air (South Korea), RACA (Argentina).



OH-6A Cayuse

(APN)

Boeing MD 520N/Explorer (USA)

Type: Light utility helicopter

Accommodation: One or two pilots, six passengers

Development/History

The NOTAR is a revolutionary tail-rotorless helicopter concept, which has been under development since 1981. As yet it has not been officially adopted by a military user, although US Army special forces are understood to have used NOTAR versions.

Variants

OH-6A, NOTAR: Experimental version, first ever NOTAR helicopter.

MD520N: Experimental version with NOTAR rotorless tail, five-bladed main rotor and Allison 250-C20R-2 turboshaft, rated to 335.7 kW (450 shp).

MD Explorer: Twin-engined NOTAR version, Military version called Combat Explorer.

MD600N: Wide-body single-engined NOTAR version, previously designated MD630N.

MD900: Light-seat version of Explorer.

MH-60/MH-6R: Suspected US special forces NOTAR versions.

Status

In production.

Operators

Nil.

Manufacturer

Hughes Helicopter Inc/McDonnell Douglas Helicopter Company/Boeing Helicopters (USA).

The revolutionary Boeing Combat Explorer is reported to be in service with the US Army Special Forces. (Boeing)

Specifications (for MD Explorer)

Powerplant

Two Pratt & Whitney Canada PW 206B turboshafts
Power: 1258 shp (908 kW)

Max T/O: 2600 lb (1180 kg)

Payload: Under-slung 3000lb (1361 kg)

Dimensions

Length: 37 ft 4 in (9.60 m)
Rotor diameter: 30 ft 10 in (9.34 m)
Height: 12 ft (3.66 m)

Performance

Max speed: 172 mph (278 km/h)
Range: 374 nm (692 km)

Weights

Empty: 3215 lb (1458 kg)

Armament

AGM-114 Hellfire laser-guided anti-tank missiles; machine gun pods; free-flight rocket pods



Boeing AH-64 Apache (USA)

Type: Attack helicopter

Accommodation: Pilot (rear), co-pilot/gunner (front)

Development/History

After the successful combat debut of the Cobra in Vietnam, the US Army began formulating requirements in the early 1970s for advanced attack helicopters. Bell Helicopters and Hughes Helicopter Inc were selected to develop competing designs and the latter company was declared the winning contender in 1976, although it was not until 1982 that the contract was issued for the first batch of heavily-armed and armoured AH-64A Apaches. Hughes was bought by McDonnell Douglas in 1984, just as the first Apache was being delivered. Since then the US Army has received some 421 A-models, and more than 800 have been sold to export customers.

The AH-64A showed its potential during NATO Reforger exercises during the late 1980s, but it was not until the 1989 US operation to seize Panama that the Apache first saw action.

In the 1991 Gulf War the Apache showed its full potential by flying deep strike missions behind Iraqi lines. A US Army task force used Apaches to fire the first missiles of Operation Desert Storm, destroying a key Iraqi radar site. Supporting the Coalition ground assault, Apache helicopters accounted for more than 500 Iraqi tanks, 120 APCs, 30 air defence systems, 120 artillery pieces, 325 other vehicles, 10 radars, 50 bunkers, 10 helicopters and 10 aircraft on the ground. Eight AH-64s were hit by enemy fire, but only one was shot down, with its crew surviving. Israeli forces have used the Apache extensively against Islamic guerrillas in southern Lebanon, and on a number of occasions they have employed Hellfire missiles to 'surgically' assassinate key enemy commanders.



Boeing AH-64A Apache of Royal Netherlands Air Force

(Boeing)

Specifications (for AH-64A)

Powerplant

Two General Electric T700-GE-700 turbo shafts

Power: 3302 shp (2530 kW)

Workload: n/a

Performance

Max speed: 227 mph (365 km/h)

Range: 260 nm (482 km)

Dimensions

Length: 51 ft (15.5 m)

Rotor diameter: 48 ft (14.6 m)

Height: 12 ft, 7 in (3.8 m)

Armament

One 30 mm M230 Chain Gun; AGM-114 Hellfire laser and millimeter radar guided anti-tank missiles; Meteor, Stinger or Starburst/Hellbreak air-to-air missiles; free-flight rockets

Weights

Empty: 11 225 lb (5096 kg)

Max LO: 21 000 lb (9525 kg)



Boeing AH-64A Apache
(Boeing)

Boeing AH-64 Apache (USA)

The intimidating presence of low-flying Apache helicopters in Bosnia from 1998 onwards was considered by US Army commanders to be instrumental in the success of their peacekeeping mission.

The US Army is upgrading its Apache fleet by introducing the Longbow millimetric radar and new radio frequency guided version of the Hellfire missile, which effectively allows for very long range engagements to be fought at night and in bad weather. All the US Army fleet will be modified to allow use of the mast-mounted Longbow radar, but only some 232 radar sets are being purchased. The Netherlands and Britain are the first export customers for the Longbow Apache. In preparation for deployment of the highly capable AH-64D, the Dutch have already received a number of old US Army A-models for use until new build machines are ready. Britain is setting up its own production line to produce its YAH-64D, which will feature unique engines, weapon systems and defensive aids - the first helicopter is due to make its premier flight in March 1999.

Variants

YAH-64A/Hughes Model 77: Experimental version.

AH-64A: Basic US Army version.

AH-64E/D: Proposed PAH version for German army.

AH-64D Longbow: Improved millimetric radar equipped version.

YAH-64D: UK-built Longbow version with Rolls-Royce/TurboMechs RTM322 engines.

AH-64C: US Army version upgraded to allow installation of Longbow radar. Now to be designated D-models



Boeing AH-64D Longbow Apache

(Boeing)

Piran (Cobra): Israeli name.
Sea Apache: Proposed naval version.

Status

In production.

Operators

Egypt (air force), Greece (army), Israel, Saudi Arabia (army), Netherlands (air force), UAE (Abu Dhabi), UK (army), USA (army).

Manufacturers

Boeing Helicopter Inc./McDonnell Douglas Helicopter Company/Boeing Helicopters (USA), Westland Helicopter (UK).

Boeing AH-64D
Longbow Apache
(Boeing)



Sikorsky S-58 Choctaw/Wessex (USA)

Type: Medium-lift helicopter

Accommodation: Two pilots, optional crew chief, 16 troops

Development/History

The first versions of the S-58 first flew in 1954, and the US armed forces operated large numbers until the UH-1 Huey entered service in the 1960s. The British-built version, the Wessex, also saw extensive service. Westland improved the Sikorsky single piston-engined design by installing single- and then twin-turboshafts. They are now withdrawing them from service, although Uruguay has recently bought up surplus British machines.

Variants (still in service)

Wessex HC 2: RAF utility and rescue version. Also operated by Uruguay.

Wessex HC 5: RAF transport and support helicopter.

Wessex HCC 4: RAF Royal Flight VIP version.

Wessex 60: Rescue version used by Uruguay.

CH-34: Transport version.

UH-340: Transport version.

S-58E: Twin-turboshaft engine-powered version.

Status

No longer in production.

Operators

Argentina (air force), UK (air force), Uruguay (navy), Laos, Taiwan (army) Thailand (air force), Turkey (air force).

Manufacturers

Sikorsky Aircraft (USA), Westland Helicopters (UK).



Westland Wessex HC Mk 5

(Tim Ripley)

Specifications (for Wessex HC 2)

Powerplant

Two Bristol Siddeley Orpheus Mk 110/111 turboshafts
Power: 2700 shp (2014 kW)

Dimensions

Length: 48 ft 4 in (14.7 m)
Length: 55 ft 10 in (17 m)
Rotor diameter: 62 ft (18.9 m)
Height: 16 ft 10 in (5.1 m)

Weights

Empty: 8304 lb (3767 kg)
Max T/O: 1350 lb (6123 kg)
Payload: 6000 lb (2720 kg)

Performance

Max speed: 140 mph (225 km/h)
Range: 214 nm (396 km)

Armament

7.62 mm door guns

Sikorsky S-61/SH-3 Sea King (USA)

Type: Medium-lift/naval helicopter

Accommodation: Two pilots, [SH-3] two sonar operators, 26 troops

Development/History

This Sikorsky design made its first flight in 1958, and the American company made several hundred for the United States Navy during the 1960s. The SH-3 proved a very sound maritime helicopter, and NATO navies ordered it in large numbers from American and local production lines.

Westland Helicopters in Britain began to develop its own versions from 1966, including anti-submarine, assault, airborne early warning and search and rescue. Production continued until the mid-1980s, with more than 300 being built for domestic and export markets.

Variants

YKSS-2: Prototype version.

HSS-2/SH-3A: Original US Navy production version for anti-submarine warfare (ASW), powered by T-58-GE-18 turboshafts rated at 537.5 hp (1250 shp), fitted with dipping sonar and capable of carrying torpedoes or nuclear depth charges.

OH-3A/B: Utility version without ASW equipment for US Navy and USN.

HH-3A: US Navy combat search and rescue version, featuring extra fuel tanks and Minigun armament.

HH-3A: Experimental version with turbojets and wings.

HH-3A: US Navy mine-sweeping version.

V-3A: US Marine Corps version for Presidential transport.

SH-3D: Improved US Navy ASW version with T58-GE-10 engines and improved mission systems, licence-built in UK, Italy and Japan.

VH-3D: US Marine Corps version for Presidential transport.



Sikorsky S-36

(US Navy)

Specifications (for SH-3H Sea King)

Powerplant

Two General Electric T58-GE-10 turboshafts

Power: 2600 shp (2088 kW)

Payload: 8000 lb (3628 kg)

Performance

Max speed: 190 mph (267 km/h)

Range: 542 nm (1005 km)

Dimensions

Length: 54 ft 9 in (16.7 m)

Rotor diameter: 62 ft (18.9 m)

Height: 15 ft 6 in (4.7 m)

Armament

Mk 44, 46, 50, A244/S, Sting Ray torpedoes; Mk 11 depth charges; Mk 57 and Lulu nuclear depth charges; Sea Eagle, AM39 Baret, M60 Mk 2 anti-ship missiles; GAU-2 7.62 mm Mini door gun; machine gun.

Weights

Empty: 11 865 lb (5382 kg)

Max T/O: 20 500 lb (9300 kg)

Sikorsky S-61/SH-3 Sea King (USA)

with T58-GE-10 powerplant.

SH-3G: US Navy improvement of H-model with extra cargo and passenger carrying capacity.

SH-3H: US Navy improvement of H-model with improved mission systems for ASW work.

UH-3H: US Navy utility version without ASW mission equipment.

SH-3D-75: ASW version.

SH-3H AEP: Spanish navy offshore early warning version with Searchwater radar.

S-61A: Export version for Denmark to SH-3A standard.

AS-61A-4: Search and rescue export version for Malaysia, known as *Rajah*.

S-61D-2: Brazilian export version to SH-3D standard, later upgraded to SH-3H standard.

S-61D-4: Argentinean export version to SH-3D standard.

Italian-built versions

ASH-3D: Naval version, with T58-GE-100 engines rated to 1125 kW (1500-shp), ASW mission equipment and equipped to fire Exocet and Marte Mk 2 anti-ship missiles.

ASH-3H: ASW version with improved mission equipment.

AS-61-15: VIP transport version, designated ASH10/15.

AS-61A-4: Export utility version with ASH-3D powerplant.

Canadian-built versions

CHS-2/CH-124A: ASW version to SH-3D standard.

CH-124B/C: Upgraded version with improved mission systems.



Sikorsky SH-3G

(US Navy)



Westland Sea King HC.60A 4 'Jungle'

(Royal Marines)

Sikorsky S-61/SH-3 Sea King (USA)



Westland Sea King HC.Mk 4 'Jungfrau'

(Tom Ripley)

Japanese-built versions

S-61B: ASW version to SH-3A, later a S-61B-2 with improved missile systems was fitted to SH-3H standard.
S-61A(JM): Utility, Antarctic survey and rescue version.

British-built versions

Sea King HAS 1: ASW version with Rolls-Royce Gnome H1400 turboshafts rated to 1050 kW (1400 shp).
Sea King HAS 2: Improved ASW version with updated Gnome H1400-1s.
Sea King HC 4: Assault and troop transport version.
Sea King HAS 5: Improved ASW version with sea radar and missile systems.
Sea King HAS 6: Improved ASW version.
Sea King HAR 3: Search and rescue version for RAF.
Sea King HAR 3A: Improved search and rescue version for RAF.
Sea King HAR 5: Royal Navy designation for its search and rescue version.
Sea King Mk 40: UK Ministry of Defence trials version.
Sea King Mk 41: Export version of Germany for search and rescue.
Sea King Mk 42: Export version for India to HAS 1 standard.
Sea King Mk 42A: Export version for India to HAS 2 standard.
Sea King Mk 42B: Export version for India with updated Gnome H1400-1T powerplants.
Sea King Mk 42C: Export version for India to HAR 3 standard.
Sea King Mk 43(NB): Export version to Norway for search



Westland Sea King HC Mk 5 'Jungle'

(Tim Ripley)

Sikorsky S-61/SH-3 Sea King (USA)

and rescue.

Sea King Mk 45A: Export version to Pakistan to HAS-12 standard.

Sea King Mk 47: Export ASW version for Egypt to HAS-2 standard.

Sea King Mk 48: Export rescue version for Belgium to HAR-3 standard.

Sea King Mk 56A: Export version for Australia to HAS-2 standard.

Sea King ASW 2A: Airborne early warning version with Searchwater radar.

Sea King ASW 7: Improved airborne early warning version with upgraded Searchwater radar.

Commando Mk 1 (Sea King Mk 78): Assault and troop transport version for Egypt.

Commando Mk 2 (Sea King Mk 73): Assault and troop transport version for Egypt.

Commando Mk 2A (Sea King Mk 92): Assault and troop transport version for Qatar.

Commando Mk 2C (Sea King Mk 92): WP version for Qatar.

Commando Mk 2E (Sea King Mk 73): Electronic warfare version for Egypt.

Commando Mk 3 (Sea King Mk 74): Naval version for Qatar, fitted to fire Exocet missiles.

Status

No longer in production

Operators

Argentina (navy), Australia (navy), Belgium, Brazil (navy),



Sea King HC.Mk 4 'Jungle' over Bosnia

(LA) (Photo: Terry Morgan)

Canada, Denmark (air force), Egypt, Germany (navy), India (navy), Iraq, Iran, Italy (navy/air force), Japan (navy), Malaysia (air force), Norway, Pakistan (navy), Peru (navy), Qatar, Saudi Arabia (air force), Spain (navy), Thailand (navy), Venezuela (army), UK (navy/air force), USA (navy)

Manufacturer

Sikorsky Aircraft (USA), Agusta (Italy), Westland Helicopters (UK), Mitsubishi Heavy Industries (Japan), United Aircraft (Canada)

Westland Sea King HC.6/Kn 4 'Jungles' in service with the Royal Navy

(Media Production CLEVELAND)



Sikorsky S-61N-1 Silver (USA)

Type: Passenger transport helicopter

Accommodation: Two pilots, 30 passengers

Development/History

A development of the Sea King largely for the civil market, this version has been employed by a number of military users for troop transport and rescue work. Civil operators have also chartered them to military customers in the Middle East and the Falklands.

Variants

S-61L: Civil version

S-61NR: Export search and rescue version for Argentina.

AS-61A-1: Italian-made export version for Malaysia.

Status

No longer in production.

Operators

Argentine Air Force, Malaysia Air Force, UK (MoD), United Nations.

Manufacturer

Sikorsky Aircraft (USA), Agusta (Italy).



Sikorsky S-61N-1 Silver

Specifications (for S-61N)

Powerplant

Two General Electric CT58-14B-1 turboshafts

Power: 3000 shp (2236 kW)

Dimensions

Length: 73 ft 10 in (22.3 m)

Rotor diameter: 62 ft (18.9 m)

Height: 17 ft (5.2 m)

Weights

Empty: 12 510 lb (5674 kg)

Max T/O: 22 000 lb (9980 kg)

Payload: 7850 lb (3560 kg)

Performance

Max speed: 146 mph (235 km/h)

Range: 430 nm (796 km)

Sikorsky S-61/HH-3 (USA)

Type: Medium-lift transport helicopter

Accommodation: Two pilots, 30 troops, 15 stretchers

Development/History

Known as the *Jolly Green Giant* during the Vietnam War, the HH-3 revolutionised combat search and rescue work by being the first in-service helicopter to employ in-flight refuelling. Eventually superseded by the bigger S-66 series in USAF service, the HH-3 found a niche in maritime rescue work with the US Coast Guard and Italian Air Force.

Variants

CH-3E: USAF utility and drone recovery version.

AS-61R Pelicani: Italian-built search and rescue version.

HH-3E *Jolly Green Giant*: USAF combat search and rescue version with in-flight refuelling.

MH-3E: USAF special forces version with in-flight refuelling.

HH-3F Pelicani: US Coast Guard search and rescue version.

WH-3E: USAF WP transport version.

Status

No longer in production.

Operators

Italian (air force), US (coast guard).

Manufacturer

Sikorsky Aircraft (USA), Agusta (Italy).



US Army HH-3E

(APN)

Specifications (CH-3E)

Powerplant

Two General Electric T58-G1-5 turbofans

Power: 3000-shp (2236 kW)

Dimensions

Length: 57 ft 3 in (17.4 m)

Rotor diameter: 62 ft (18.9 m)

Height: 18 ft 1 in (5.5 m)

Weights

Empty: 13 225 lb (6010 kg)

Max T/O: 22 000 lb (10 000 kg)

Payload: 5000 lb (2270 kg)

Performance

Max speed: 162 mph (261 km/h)

Range: 404 nm (748 km)

Armament

Door machine guns.

Sikorsky S-65A/CH-53 Sea Stallion (USA)

Type: Heavy-lift transport helicopter

Accommodation: Two pilots, crew chief, 37 troops, 24 stretchers

Development/History

Sikorsky's big-lift first flew in 1964, and was quickly adopted by the US Marine Corps as its heavy assault transport. Some 124 D-models were bought by the Marine Corps, and have remained in service through to the 1990s. The USAF adopted the aircraft as its principal long-range special operations and combat search and rescue helicopter, instigating several upgrades to maintain its deep penetration capabilities.

Variants

CH-53A: Original USMC version powered by General Electric T64-GE-16 turbo shafts.

TH-53A: USAF training version similar in capability to CH-53A.

HH-53B/C: USAF combat search and rescue version with in-flight refuelling probes.

CH-53C: USAF rescue version with out in-flight refuelling probe.

CH-53D: Improved USMC version with updated T64-GE-413 engines, each rated at 2927 kW (3925 shp).

HH-53B: US Navy minecopter, powered by two T64-GE-413s each rated at 3268 kW (4380 shp).

MH-53J Pave Low III: USAF special operations version, fitted with in-flight refuelling, night vision equipment and terrain following radar and powered by two T64-GE-7A each rated to 2935 kW (3936 shp).

S-65C-2/M: Austrian export version built to CH-53C standard, later sold to Israel.

S-65C-3: Israeli export version similar to USAF HH-53C.



Sikorsky/VFW-Fokker CH-53G Sea Stallion serving with the United Nations Special Commission in Iraq after the Gulf War

(Tim Ripley)

Specifications (for CH-53A)

Powerplant

Two General Electric T64-GE-16 turbo shafts

Power: 5424 shp (6680 kW)

Dimensions

Length: 67 ft 2 in (20.47 m)

Rotor diameter: 72 ft 3 in (22.02 m)

Height: 34 ft 11 in (7.6 m)

Weights

Empty: n/a

Normal TO: 35 000 lb (15 875 kg)

Payload: External 33 000 lb (5 887 kg)

Performance

Max speed: 195 mph (314 km/h)

Range: 257 nm (473 km) with auxiliary tanks

Armament

7.62 mm or 12.7 mm door guns



Sikorsky CH-53D Sea Stallion

(Tom Ripley)

Sikorsky S-65A/CH-53 Sea Stallion (USA)

CH-53 2000: Israeli upgrade also known as Yac'ar 2000, designed to extend life into the next century. Turkey is interested in buying this version.

CH-53G: German-built version.

Status

No longer in production.

Operators

Germany (Army), Iran, Israel, USA (Air Force/Marines).

Manufacturer

Sikorsky Aircraft (USA), WFF-Fokker (Germany).



Sikorsky NH-53J
Pave Low
(USAF/DoD)

Sikorsky S-80/CH-53E Super Stallion (USA)

Type: Heavy-lift transport helicopter

Accommodation: Two pilots, crew chief, 55 troops

Development/History

The S-80 series Super Stallion utilizes three engines to make it one of the most powerful heavy-lift helicopters in the world. The US Marine Corps and Navy began taking delivery in 1981, and some 177 were built until production ceased in 1995.

Mine clearing versions used by the US Navy and Japanese Maritime Self-Defence Force are operated from amphibious warfare ships or shore bases.

Variants:

CH-53E Sea Stallion: US Navy and Marine Corps Assault and heavy-lift version.

MH-53E Sea Dragon: US Navy mine-sweeping version.

S-80E: Proposed export version of CH-53E.

S-80M-1: Japanese mine-sweeping version.

Status

No longer in production.

Operator

USA (navy/marines), Japan (navy).

Manufacturer

Sikorsky Aircraft (USA).



Sikorsky CH-53E Sea Stallion

(Tim Ripley)

Specifications (for CH-53E)

Powerplant

Three General Electric T64-GE-416 turboshafts

Power: 13 140 shp (9738 kW)

Dimensions

Length: 73 ft 4 in (22.3 m)

Rotor diameter: 79 ft (24.1 m)

Height: 39 ft 5 in (11.9 m)

Weights

Empty: 33 220 lb (15 072 kg)

Max LTO: 69 750 lb (31 640 kg)

Payload: Under-flight 36 000 lb (16 330 kg)

Performance

Max speed: 150 mph (241 km/h)

Ferry Range: 1120 nm (2074 km)

Armament

7.62 mm or 12.7 mm door guns

Sikorsky S-80/CH-53E Super Stallion (USA)



Sikorsky CH-53E Sea Stallion

(Tim Ripley)

Sikorsky S-80/CH-53E Super Stallion (USA)



Sikorsky MH-53E Sea Dragon
(United Technologies/Sikorsky Aircraft)



Sikorsky MH-53E Sea Stallion
(United Technologies/Sikorsky Aircraft)

Sikorsky S-70/UH-60 Blackhawk (USA)

Type: Medium-lift utility helicopter

Accommodation: Two pilots, crew chief, 14 troops

Development/History

In the early 1970s the US Army began looking for a UH-1 Huey replacement which would take into account many of the lessons learnt from combat helicopter operations in Vietnam. Improved crash worthiness was a major criterion in the design, which first flew in 1974.

The first production version flew in 1978, and soon the UH-60A was in widespread service with the US Army, seeing combat in Grenada in 1983. An improved version capable of lifting a HUMVEE or a 155 mm howitzer under-slung was developed in the late 1980s, eventually being designated the UH-60L. In total the US Army has bought some 1400 against original plans for 2262, low rate production continues for the US Army and export.

Variants

UH-60A: Original US Army utility version.

UH-60B SOTAS: Proposed ground surveillance radar version.

UH-60L: US Army version with updated T700-G1-716C engines.

UH-60P: South Korean version to L-model standard.

UH-60Q Duster: Proposed medical evacuation version, with external hook.

EH-60A Quick Fix: Electronic warfare version.

EH-60C Quick Fix: Improved electronic warfare version.

MH-60A Vekro Hawk: US Army special forces version.

MH-60G: Pave Hawk USAF special forces version with in-flight refuelling.

HH-60G: USAF search and rescue version.

MH-60E: US Army special forces version with in-flight



Sikorsky UH-60L Blackhawk

(Tim Ripley)

Specifications (for UH-60A)

Powerplant

Two General Electric T700-G1-700 turboshafts

Power: 3244 shp (2420 kW)

Payload: 8000 lb (3629 kg) under-slung

Performance

Max speed: 164 mph (286 km/h)

Range: 319 nm (592 km); 1200 nm (2222 km) with max external fuel

Dimensions

Length: 50 ft (15.3 m)

Rotor diameter: 53 ft 8 in (16.4 m)

Height: 16 ft 10 in (5.1 m)

Armament

2.02 mm or 12.7 mm door guns and pods; free-flight rocket pods; AGM-114 Hellfire laser guided anti-tank missiles.

Weights

Empty: 11 264 lb (5118 kg)

Max TO: 20 250 lb (9185 kg)



Sikorsky S-70 Armed Blackhawk

(United Technologies/Sikorsky Aircraft)

Sikorsky S-70/UH-60 Blackhawk (USA)



Sikorsky HH-60G Pave Hawk

(United Technologies/Sikorsky Aircraft)

refueling probe.

MH-60L: US Army special forces version with in-flight refueling probe and updated T700-GE-710C engines.

UH-60M: US Presidential transport version.

S-70A-1: Saudi land forces version.

S-70A-1L: Saudi VIP transport/mobility version.

S-70A-6: Philippines export version.

S-70A-9: Australian-assembled version.

S-70A-11: Jordanian export version.

S-70A-12: Japanese search and rescue version, designated **UH-60J**.

S-70A-14: Brunei export version.

S-70A-16: Test bed for Rolls-Royce/Ingersoll Rand RTM 322.

S-70A-17: Turkish export version.

S-70A-19: Scotland-produced version, designated **WS-70**.

S-70A-21: Egypt export version.

S-70A-24: Mexican export version.

S-70A-26: Moroccan export version.

S-70A-27: Hong Kong export version.

S-70C: Chinese export version.

S-70C-2: Rescue version with hoist used by Taiwan and Brunei.

Status

In production.

Operators

Australia (army), Bahrain, Brazil (army), Brunei, Chile, Colombia (army/air force), Egypt, Israel, Greece (army), Hong Kong, Japan (army/air force), Jordan, Malaysia, Mexico,



Sikorsky UH-60L Blackhawk

(United Technologies/Sikorsky Aircraft)

Sikorsky S-70/UH-60 Blackhawk (USA)

Mexico, Philippines (air force),
Saudi Arabia (army), South
Korea (army), Taiwan (air force),
Turkey (army), Thailand (army),
USA (army/navy/air force).

Manufacturer

Sikorsky Aircraft (USA),
Mitsubishi Heavy Industries
(Japan), Westland Helicopters
(UK), Hawker de Havilland
(Australia), Korea Air (South
Korea).

Sikorsky S-70A
Blackhawk of Royal
Brunel Armed Forces
(United Technologies/
Sikorsky Aircraft)



Sikorsky S-70B/SH-60 Seahawk (USA)

Type: Maritime helicopter

Accommodation: Two pilots, mission specialist

Development/History

Finalised version of the S-70 series won the US Navy's LAMPS competition with a development contract being issue in 1977. The SH-60B has 80 per cent commonality with the UH-60, but includes many features necessary for operations at sea, including anti-corrosion treatment for the airframe, improved engines and a NOL recovery device to secure the helicopter to a rolling ship deck in heavy seas. The US Navy has continued to develop the basic design, including a anti-submarine version with dunking sonar and a specialist combat search and rescue variant. Moves are now in hand to standardise the fleet under the SH-60R programme.

Status

In production.

Variants

SH-60B Seahawk: Original US Navy light multi-purpose version (LAMPS) Mk III frigate and destroyer-borne helicopter, with APS-124 radar, NAD and sonobuoy launching systems.

SH-60F Orion Hawk: Carrier-borne (CV) inner sea zone anti-submarine helicopter, with Bendix dipping sonar and provision for three Mk 50 torpedoes.

S-70B-3(SH-60I): Japanese-built version of SH-60B.

SH-60R: US Navy programme to standardise B, F and H versions.

S-70B-2 (RAWS): Australian version with domestically-produced radar, sonobuoy and other systems. Also provision for Sea Skua and Penguin water-guided anti-ship missiles.



Sikorsky S-70B-8 Seahawk of Greek Navy

(United Technologies/Sikorsky Aircraft)

Specifications (for SH-60B)

Powerplant

Two General Electric T700-GE-401C turboshafts

Power: 2800 shp (2034 kW)

Max T/O: 21 000 lb (9525 kg)

Payload: n/a

Dimensions

Length: 50 ft 0.75 in (15.26 m)

Rotor diameter: 53 ft 0 in (16.36 m)

Height: 17 ft 5.18 in

Performance

Max speed: 145 mph (234 kmh)

Range: 50 nm (92.5 km) for 3-hour loiter

Armament

7.62 mm and 12.7 mm door guns; AGM-119R

Penguin anti-ship missiles; Mk 46 or Mk 50 torpedoes; free-flight rockets.

Weights

Empty: 13 640 lb (6181 kg)

Sikorsky S-70B/SH-60 Seahawk (USA)



S-70(M)-1 Thunderhawk: Taiwanese version of SH-60F. Local conversion to Sigint intelligence role has taken place.
HH-60H Rescue Hawk: US Navy specialised combat search and rescue version, with extra armament and night vision systems.
HH-60J Jayhawk: US Coast Guard search and rescue version.

S-70B-4: Greek export version.

S-70B-7: Thai naval version with PT6B-36B engines.

CH-60: Proposed US Navy utility version for support and vertical replenishment.

Maplehawk: Proposed Canadian rescue version.

Operators

Australia (navy), Ecuador (navy), Japan (navy), Spain (navy), Taiwan (navy), USA (navy/coast guard).

Manufacturers

Sikorsky Aircraft (USA), Mitsubishi Heavy Industries (Japan), ASTA (Australia).

Sikorsky SH-60B Seahawk
(United Technologies/
Sikorsky Aircraft)



Sikorsky SH-60B Seahawk

(United Technologies/Sikorsky Aircraft)

Sikorsky S-76 (USA)

Type: Medium-lift utility helicopter

Accommodation: Two pilots, 14 passengers

Development/History

This private venture product has sold well to a number of civil and military customers around the world, but it has not found favour with the US armed forces.

Variants

S-76: Original version powered by Allison 250-C30 turboshafts, rated to 485 kW (650 shp).

S-76 Mk II: Improved version.

S-76 Utility: Basic version.

AUH 76: Armed utility derivative, with provision for anti-aircraft rockets and guns.

S-76A/C: Version with S25609 (661 shp) turboshafts Arriel 1S1 powerplant.

S-76B: Production version with P56B-36A powerplant.

H-76B: Military version of S-76B, with weapons provision.

H-76Bc: Naval version.

HE24: Spanish designation.

Status

In production.

Operators

Chile (army), Guatemala, Honduras, Hong Kong, Iraq, Japan, Jordan, Philippines (air force), Spanish (air force), South Korea (army).

Manufacturer

Sikorsky Aircraft (USA) and Daewoo (Korea).



Sikorsky S-76C

(United Technologies/Sikorsky Aircraft)

Specifications (for H-76)

Powerplant

Two Pratt & Whitney Canada PT6B-36A turboshafts

Power: 1962 shp (1464 kW)

Dimensions

Length: 44 ft (13.4 m)

Rotor diameter: 44 ft (13.4 m)

Height: 14 ft 5 in (4.4 m)

Weights

Empty: 6561 lb (3012 kg)

Max T/O: 11 700 lb (5307 kg)

Payload: n/a

Performance

Max speed: 178 mph (287 km/h)

Range: 357 nm (661 km)

Armament

7.62 mm, 12.7 mm or 20 mm machine gun pods; Stinger air-to-air missiles; Hellfire laser-guided missiles; TOW wire-guided anti-tank missiles; fire-flight rockets

Glossary

ABW Airborne early warning.

ASW Air-to-surface vessel.

ASWW Anti-surface vessel-surface.

ASW Anti-submarine warfare.

avionics Aviation electronics, such as communication radio, radars, navigation systems and computers.

carbonfiber rotor Rotor in which flapping load/ing and pitch change movements are provided by the flexibility of the structural material and not by bearings. No rotor is rigid.

carbonfiber line filament of carbon/graphite used as strength element in composites.

CAS Clear air support.

CBM Cluster bomb unit.

CFRP Carbonfiber-reinforced plastic.

CO-IN Counter-insurgency.

comint Comenetic lines intelligence.

composite material Made of two constituents, such as filaments or short whiskers plus adhesive, forming binding matrix.

databus Electronic highway for passing digital data between aircraft sensors and system processors, usually MIL-STD-1553B or ARINC 429 (one way) and ARJ (two way) systems.

derated Engine restricted to power less than potential maximum (usually such engine is flat rated).

DF Direction Finder or direction finding.

downstroke Helicopter tail rotor with many slender blades rotating in short start.

FJR Forward-looking infra-red.

fly-by-light Flight control system in which signals pass between computers and actuators along fibre optic leads.

fly-by-wire Flight control system with electrical signalling (i.e. without mechanical interconnection between cockpit flying controls and control surfaces).

g Acceleration due to mean Earth gravity (i.e. of a body in free fall), or acceleration due to rapid change of direction of flight path.

GPS Global Positioning System.

gunship Helicopter designed for (anti-air) attack, normally with slim body carrying pilot and weapon operator only.

hardpoint Reinforced part of aircraft to which external load can be attached, e.g. weapon/tank pylon.

HMD Helmet-mounted display, hence HMS = sight.

hot and high Airborne combination of airfield height and high ambient temperature, which lengthens required take-off distance (TOD).

hp Horsepower.

HDD Head-up display.

HF Identification friend or foe.

IR Infra-red.

IRST Infra-red search and track.

J-STARS US Air Force/Naval Joint Surveillance Target Attack Radar System in Boeing E-8A.

JIDS Joint Tactical Information Distribution System.

Kevlar Aramid fibre used as look of

high-strength composite material.

km/h Kilometres per hour.

KN Kilowatt-hours, the metric unit for measuring power output of jet engine, least 1 ton per hour.

KW Kilowatts, the metric unit for measuring power output of a propeller-driven engine.

lb Pounds of static thrust, the measurement of a jet engine's static thrust.

LEDV Low-light TV (thus LED, low-light-level).

low observables Materials and structures designed to reduce aircraft signatures of all kinds.

m metre(s), the metric unit of length.

MAD Magnetic anomaly detector.

MFD Multi-function display.

MMS Mast-mounted sight.

MO Maximum permitted operating Mach number.

mph Miles per hour.

MaxTO Maximum take-off weight.

nm Nautical mile, 1.15072 miles (1.852 km).

NDE Nap-of-the-Earth (low-flying in military aircraft using natural cover of hills and trees etc).

NVG Night Vision Goggles.

optoelect Combination of optics and electronics in viewing and sighting systems.

port Left side, looking forward.

pylon Structure linking aircraft to external load (engine nozzle, drop tank, bomb etc).

radius The distance an aircraft can fly from base and return without intermediate landing.

RAM Radar absorbent material.

rigid rotor see bearingless rotor.

RFV Remotely-piloted vehicle.

SAR i) Search and rescue.

ii) synthetic aperture radar.

shp Shaft horsepower, measure of power transmitted via rotating shaft.

sigint Signals intelligence.

signature Characteristic "fingerprint" of all electromagnetic radiation (radar, IR etc).

single-shaft Gas turbine in which all compressors and turbines are on common shaft rotating together.

SLAR Side-looking airborne radar stabiliser fin (thus, horizontal stabiliser = tailplane).

starboard Flight side, looking forward, i.e. star, 1 Megapound, 1000 kg.

tail-rotor Aircraft with fixed wing and rotor that tilts up for hovering and forward for fast flight.

T-O Take-off.

ton Imperial (long) ton = 2240 lb or 2240 kg, US (short) ton = 2000 lb or 2000 kg.

turboshaft Gas turbine in which as much energy as possible is taken from gas jet and used to drive helicopter rotor.

UAV Unmanned air vehicle.

winglet Small auxiliary aerofoil, usually sharply tapered and often sweptback, at tip of wing.

Acknowledgements

I would like to thank the following for their help and advice during the preparation of this book: Jon Lake; Jennifer at Jane's Library; Peter Donaldson and Ian Pookes, *Defence Helicopter Magazine*; Peter Fehlsaad, *Jane's Intelligence Review*; Commander Ken Jay, Royal Navy; and Pauline Elliott, Centre for Defence and International Security Studies; Ian Drury, HarperCollins; Nigel Wessers, Royal United Services Institute; and Neil Tweedie and Mick Brooks at the Hotel Richmond.

Design: Rod Teasdale

Cover photographs: Peter Foster

Colour reproduction by Colourscan, Singapore

Printed in Italy

First published in Great Britain by HarperCollins Publishers in 1998

1 3 5 7 9 10 8 6 4 2

HarperCollins Publishers 1998

ISBN 0 00 472134 0

UK information address:

HarperCollins Publishers

77-85 Fulham Palace

Road

Hammersmith

London W6 8JB

US information address:

HarperCollins Publishers Inc

10 East 53rd Street

New York

NY 10022

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying or otherwise without prior permission of the publishers.