



[News](#) | [Features](#) | [Download](#) | [GitHub](#) | [Documentation](#) | [Tutorial](#) | [FAQ](#) | [Contact](#)

Useful links:
[Freecode](#)
[IceWalkers](#)

[The Linux Foundation](#)
[Linux Kernel Archives](#)
[Linux Kernel Mailing List](#)
[The Linux Documentation Project](#)



sa2 manual page

NAME

sa2 - Write a daily report in the /var/log/sa directory.

SYNOPSIS

/usr/lib/sa/sa2

DESCRIPTION

The sa2 command is a shell procedure variant of the sar command which writes a daily report in the /var/log/sa/sar dd file, where the dd parameter indicates the current day. It will also remove reports more than one week old by default. You can however keep reports for a longer (or a shorter) period by setting the HISTORY environment variable. Read the sysstat(5) manual page for details.

The sa2 command accepts most of the flags and parameters of the sar command.

The sa2 command is designed to be started automatically by the cron command.

EXAMPLES

To run the `sa2` command daily, place the following entry in your root crontab file:

```
5 19 * * 1-5 /usr/lib/sa/sa2 -A &
```

This will generate a daily report called `/var/log/sa/sar dd` .

FILES

`/var/log/sa/sar dd`

Indicate the daily report file, where the `dd` parameter is a number representing the day of the month.

AUTHOR

Sebastien Godard (sysstat <at> orange.fr)

SEE ALSO

[sar\(1\)](#), [sadc\(8\)](#), [sa1\(8\)](#), [sadf\(1\)](#), [sysstat\(5\)](#)

<http://pagesperso-orange.fr/sebastien.godard/>