



[News](#) | [Features](#) | [Download](#) | [GitHub](#) | [Documentation](#) | [Tutorial](#) | [FAQ](#) | [Contact](#)

Useful links:
[Freecode](#)
[IceWalkers](#)

[The Linux Foundation](#)
[Linux Kernel Archives](#)
[Linux Kernel Mailing List](#)
[The Linux Documentation Project](#)



sysstat manual page

NAME

sysstat - sysstat configuration file.

DESCRIPTION

This file is read by sa1(8) and sa2(8) shell scripts from the sysstat's set of tools. It consists of a sequence of shell variable assignments used to configure sysstat logging. The variables and their meanings are:

HISTORY

The number of days during which a daily data file or a report should be kept. Data files or reports older than this number of days will be removed by the sa2(8) shell script. Data files and reports are normally saved in the /var/log/sa directory, but if HISTORY is greater than 28, the scripts use a tree of directories under /var/log/sa.

COMPRESSAFTER

Number of days after which daily data files are to be compressed, either by gzip or bzip2.

SADC_OPTIONS

Options that should be passed to `sadc(8)`. With these options (see `sadc(8)` manual page), you can select some additional data which are going to be saved in daily data files. These options are used only when a new data file is created. They will be ignored with an already existing one.

FILES

`/etc/sysconfig/sysstat`

AUTHOR

Sebastien Godard (`sysstat <at> orange.fr`)

SEE ALSO

[`sadc\(8\)`](#), [`sa1\(8\)`](#), [`sa2\(8\)`](#)

<http://pagesperso-orange.fr/sebastien.godard/>