

Technology Impedances to Augmented Cognition

BY M. L. CUMMINGS

In a recent issue of *Ergonomics in Design* (Summer 2009), there was a debate as to whether systems should be controlled via psychophysiological operator cognitive state measures (commonly referred to as *augmented cognition*, or AugCog). Griffith was concerned that AugCog systems would circumvent human control, and that AugCog research in general ignored the parallel need to understand how humans could better complement computers. In response, Schmorow and Stanney, editors of *Augmented Cognition: A Practitioner's Guide* (2008), contended that augmented cognition is primarily about promoting synthesis between humans and computers and that psychophysiological measures are just one focus area of AugCog.

Having recently served on the National Academy of Sciences Committee for Opportunities in Neuroscience for Future Army Applications, I appreciated this debate, but a critical weakness in the AugCog effort not addressed by either side is the “elephant-in-the-room” technology chasm, which includes problems with signal detection and postprocessing algorithms.

Significant uncertainty is inherently present in command-and-control domains, where the bulk of AugCog research has taken place. When environmental uncertainty is coupled with the uncertainty inherent in all psychophysiological measures and their subsequent analyses, the outcomes of any resultant predictive models are predictions that are so broad that they are not useful, or the predictions carry so much uncertainty they cannot be trusted. In this article, I will discuss these issues in the context of previous AugCog experiments and highlight areas where advancements are needed.

A Historical View of AugCog Experiments

Under Defense Advanced Research Projects Agency (DARPA) management, the primary goal of AugCog was to develop “order of magnitude increases in available, net thinking power resulting from linked human-machine dyads [that] will provide such clear information superiority that few rational individuals or organizations would challenge under the consequences of mortality” (Schmorow & McBride, 2004, p. 129).

A critical weakness in the AugCog effort not addressed by either side is the “elephant-in-the-room” technology chasm.

This goal was proposed to occur through the use of neurologic and physiologic measures (e.g., respiration, heart rate, electroencephalography [EEG], functional optical imaging), in conjunction with traditional electromechanical computer input devices (e.g., mouse, joystick). In futuristic operational settings, an operator would wear a headset that would combine EEG, functional optical imaging, eye-tracking, and so on. Through measures generated by this headset, as well as those via galvanic skin response sensors, force feedback in input devices, pressure sensors in seats, and more, the system would enhance an operator's cognitive ability by dynamically controlling the rate, as well as the source, of information.

Proof of concept for the DARPA AugCog program occurred in two phases.

In the first phase, researchers attempted to detect changes in cognitive activity in near real time in an operationally relevant setting. In the second phase of this validation process, an operator's cognitive state was manipulated as a result of the measurement technologies developed from the first phase.

For Phase 1, one relatively large experiment/demonstration, the Technical Integration Experiment, was conducted with mixed results (St. John, Kobus, & Morrison, 2003). The objective of the experiment was to determine which psychophysiological measures could consistently detect changes in cognitive activity for a supervisory control task. Using 20 cognitive state gauges (CSGs) such as EEG, functional near-infrared (fNIR), and body posture measures, as well as input device measures (mouse pressure and mouse clicks), eight subjects completed a series of four simplified aircraft-monitoring and threat response tasks. No CSG was significant across the experiment's three independent variables. Moreover, the only CSGs that demonstrated statistically significant results across two independent variables were mouse clicks and mouse pressure (St. John, Kobus, Morrison, & Schmorow, 2004), which are indirect indicators of neural or physiologic activity.

A second set of four experiments was conducted to manipulate an operator's cognitive state as a result of near-real-time psychophysiological measurements (Dorneich, Ververs, Santosh, & Whitlow, 2005). The experiments took place in a video game environment, either at a desktop setting or in a motion capture laboratory. While navigating, participants (16 or fewer) identified friend from foes and monitored and responded to commu-

nications. A communications scheduler determined operator workload via a cognitive state profile (CSP) and prioritized incoming messages accordingly. The CSP was an amalgamation of signals from cardiac interbeat intervals, heart rate, pupil diameter and microvolt cardiac QRS waveform root mean square amplitude, EEG p300 signal, and EEG power at the frontal (FCZ) and central midline (CPZ) sites.

The authors claimed the CSP produced 100% improvement in message comprehension, 125% improvement in situation awareness, 150% increase in working memory, and increased survivability of over 350%. In addition, the authors claimed, admittedly with anecdotal evidence, that their cognitive state gauges could indicate operator inability to comprehend a message (Dorneich et al., 2005). Unfortunately, there is no clear published account of how the neurologic and physiologic variables were combined to form the CSP, so the ability to independently replicate and verify these results is not possible.

The U.S. Army conducted another related experiment, which focused on developing a mobile cognitive state classification test bed (Dorneich et al., 2007). This EEG-based system was not dry – that is, participants had to wear standard laboratory leads with conducting gel, which were then connected to a laptop computer worn in a backpack. The laptop supported the signal-processing algorithms, the communications scheduler, and other experimental testing elements. Eight participants with no military experience completed a one-hour navigation and communication task with a 35-pound backpack; however, the participant pool was reduced to four for a portion of the experiment. The communications scheduler prioritized messages based on whether the participants were in a low or high task load, showing mission performance improvement from 68% to 96% with cognitive state mitigation.

There were many common significant problems across these studies, and several were acknowledged by the authors (St. John et al., 2004), including issues with construct and external validity (e.g., many highly correlated independent variables), statistical concerns (e.g., low subject numbers, experiment-wise error rates),

significant missing data, and a well-known problem inherent in psychophysiological research: noisy data. Moreover, detecting and then classifying cognitive state changes correctly is extremely difficult, especially in highly dynamic command-and-control settings. Actual combat never adheres to a carefully planned script, and it is questionable whether the kind of limited a priori classification training used in these experiments will have any resemblance to real-world events, thus invalidating the usefulness of such an approach.

The ability to make reliable predictions in real time in a highly dynamic, stochastic setting typical of command-and-control environments is a fundamental obstacle for future AugCog success.

Given the number and severity of confounds for these experiments, the results can be considered preliminary at best. These results do not provide unequivocal scientific evidence that the reported cognitive state gauges can effectively detect change in cognitive activity in a complex human supervisory control task, much less provide accurate recommendations for future actions that can be guaranteed to be at least safe, if not effective.

Proof-of-Concept Demonstrations Are Not Scientific Proof

Although these experiments had problematic construct and statistical validity, they provided important information on a number of fronts (i.e., usability, sensor design, areas for algorithm improvement). However, care should be taken when extrapolating results from studies with such serious confounds, especially when making claims of scientific evidence. Moreover, these studies implicitly demonstrate the limitations of AugCog systems, which are rooted squarely in significant technological shortcomings.

The engineering obstacles in combining EEG, fNIR, and eye-tracking devices are substantial. Unless dramatic leaps are

made in the miniaturization of these technologies and signal-processing algorithms, the realization of a single headset that can perform all, or even a combination of these technologies, in a mobile environment is more than 20 years in the future. Weight is a critical consideration for dismounted soldiers, and a National Research Council study determined that any new device(s) should not add more than 1 kg to the helmet or 2 kg to the soldier's pack (National Research Council, 1997), which will require an almost eightfold decrease in weight from current technology.

Another major hurdle in the realization of any AugCog implementation will be the development of a wireless EEG device that is unobtrusive, does not require the use of conducting gel, and is able to process on-board signals, all while soldiers are in motion, under often hostile conditions. Some advancements have been made in wireless and dry EEGs, but the signals from these devices are substantially weaker than from the more traditional EEG devices and have fallen under significant scientific scrutiny (Greene, 2007; *Nature*, 2007).

In addition to hardware limitations, the ability to make reliable predictions in real time in a highly dynamic, stochastic setting typical of command-and-control environments is a fundamental obstacle for future AugCog success. The experiments described here were all necessarily simple and artificial, and the communications scheduler made changes in information presentation based on gross differences in perceived cognitive states. The amount of incoming information and large degrees of freedom of possible future states in real settings will mean that much more precision will be needed. Sensors and signal-processing algorithms will have to improve substantially for this to happen, and significant advances are also needed in decision-theoretic modeling. In addition, these models will have to be able to accommodate a significant range of individual variability across an almost limitless set of circumstances.

One final obstacle in achieving the general AugCog goal of enhancing operator performance through psychophysiological sensing and automation-based reasoning is determining that even if the system could change information streams

and incoming information volume for a single individual, how does the system know this change is correct, or even helpful, given the large, highly uncertain state space? This kind of predictive system assumes that it can determine an optimal balance of information for a given operator state. But operator states are inherently linked to the environment, which rarely can be represented in such system models. Before any kind of predictive system could be deployed that controlled inputs to an operator, this system would have to guarantee that it at least did no harm, and it is questionable that, given the current limitations in neuroscience and computer science, this is feasible.

Conclusion

A clearly stated goal of the Aug-Cog community is to enhance human information-processing capabilities through the design of adaptive interfaces via cognitive state estimation. This work is important and highly relevant today with the U.S. Department of Defense's increasing use of supervisory control systems, particularly unmanned systems. However, although researchers have demonstrated some interesting proofs of concept and made incremental progress in terms of hardware and software advances, the results are preliminary at best. Moreover, they do not suggest that the ultimate desired results are achievable in the near term.

For the general field of augmented cognition to make critical advances, significant focus (and funding) should be placed on hardware development and associated signal-processing efforts. Without critical advances in EEG and other neurologic and physiologic technologies, the AugCog effort cannot make significant progress or be operationalized. Furthermore, significant additional research is needed in the development of decision-theoretic models and predictive algorithms in dynamic, highly uncertain domains for open-loop systems with noisy sensor data.

References

Dorneich, M. C., Ververs, P. M., Santosh, M., & Whitlow, S. D. (2005, October). *A joint human-automation cognitive system to support rapid decision-making in hostile environments*. Paper presented at the IEEE International Conference on Systems, Man and Cybernetics, Waikoloa, Hawaii.

Dorneich, M. C., Whitlow, S. D., Mathan, S., Ververs, P., Erdogmus, D., Adami, A., et al. (2007). Supporting real-time cognitive state classification on a mobile individual. *Journal of Cognitive Engineering and Decision Making*, 1, 240–270.

Greene, K. (2007). Brain sensor for market research: A startup claims to read people's minds while they view ads. *Technology Review*, December. Available at <http://www.technologyreview.com/business/19833/page1/>

National Research Council. (1997). *Tactical display for soldiers: Human factors considerations*. Washington, DC: National Academy of Sciences.

Nature. (2007). Mind games. Vol. 450, 457–457.


Schmorrow, D., & McBride, D. (2004). Introduction. Special issue on augmented cognition. *International Journal of Human-Computer Interaction*, 17(2), 127–130.

Schmorrow, D. D., & Stanney, K. L. (2008). *Augmented cognition: A practitioner's guide*. Santa Monica, CA: Human Factors and Ergonomics Society.

St. John, M., Kobus, K. L., & Morrison, J. G. (2003). *DARPA augmented cognition technical integration experiment* (Tech. Rep. No. 1905). San Diego, CA: Space and Naval Warfare System Center.

St. John, M., Kobus, K. L., Morrison, J. G., & Schmorrow, D. (2004). Overview of the DARPA Augmented Cognition Technical Integration Experiment. *International Journal of Human-Computer Interaction*, 17(2), 131–149.



Mary (Missy) Cummings is an associate professor in the Massachusetts Institute of Technology Aeronautics and Astronautics department, director of the MIT Humans and Automation Laboratory, and a former U.S. Navy fighter pilot. 

ERGONOMICS IN DESIGN

Welcomes Your Submission!

Ergonomics in Design focuses exclusively on information about how human factors/ergonomics is applied to improve the design and functioning of any system, tool, environment, or product with which people interact.

Articles are welcome. We are particularly interested in how the application and/or the process by which it was implemented may benefit readers, whether they are working or merely interested in the field.

Feature articles should be 1,500–3,000 words in length. Guidelines for authors may be found at www.hfes.org/Web/PubPages/EIDGuidelines.pdf.

Send your submission to:

Ergonomics in Design

Human Factors and Ergonomics Society
P.O. Box 1369, Santa Monica, CA 90406-1369 USA

All submissions are peer reviewed (allow 8 weeks for review). Sample issues are available on request (call 310/394-1811).

HFES American National Standards

ANSI/HFES 100-2007: Human Factors Engineering of Computer Workstations

This American National Standard represents the culmination of a 20-year process that began with 100-1988. The content and breadth of coverage of the standard address changes in the arenas of workstation and computer design. The number and types of input devices have increased to include computer mice and other pointing devices, and the displays chapter has been expanded to cover color devices. The furniture chapter now provides four working postures for reference by designers. The integration chapter offers guidance regarding how individual elements that are ergonomically well designed can be integrated into a workplace system that is also ergonomically appropriate.

108 pages, 38 figures, 5 tables, section references, PDF on CD-ROM or print (8½ × 11"); \$50/CD or \$60/print, HFES members; \$85 nonmembers and institutions, plus shipping/handling.

Contents: Foreword; Purpose; General Scope; Conformance Policy; Cited Standards; Installed Systems; Input Devices; Visual Displays; Furniture

ANSI/HFES 200-2008: Human Factors Engineering of Software User Interfaces

The objective of HFES 200 is to provide design requirements and recommendations that will increase the accessibility, learnability, and ease of use of software. The ultimate beneficiaries are the end users of software, whose needs motivated the design recommendations in HFES 200. The application of this standard is intended to provide user interfaces that are more usable, accessible, and consistent and that enable greater productivity and satisfaction. HFES 200 consists of five parts, each of which can stand alone or in combination with the other parts for a comprehensive view of software user interfaces.

426 pages on CD-ROM, hundreds of tables and figures, appendixes, bibliographies. \$175 HFES members, \$200 nonmembers, plus \$5 shipping/handling; inquire about prices for print only.

Parts: Introduction; Accessibility; Interaction Techniques; Interactive Voice Response; Visual Presentation and Use of Color

Order online at <http://hfes.org/Publications>

or contact

Human Factors and Ergonomics Society
P.O. Box 1369, Santa Monica, CA 90406-1369 USA
310/394-1811, Fax 310/394-2410
store@hfes.org