

Insert pages similar to pages 1–8, and 13 of UL 1123 Appendix B and renumber accordingly.

The following is an example of the inside back cover:

PFDs -- IT'S YOUR CHOICE!		PFD Type	Application	Advantages
Requirements	All boats: Must be equipped with one wearable Type I, II, III or V PFD for each person on board.	Type I Inflatable & Inherently Buoyant Types	Calm water Open water Coastal Cruising General Boating	Best for cold water; 22 lbs. or more buoyancy; will float wearer in face up position.
Boats greater than 16 feet in length: In addition to above, must be equipped with one Type IV PFD.	Type II Inflatable & Inherently Buoyant Types	Inland waters or waters where there is a good chance of a rescue.	Good comfort; low cost; 15.5 lbs. or more buoyancy.	Good comfort; low cost; 15.5 lbs. or more buoyancy.
Inflatable PFD High performance in compact space, but causes regular user problems and maintenance.	Type III Inflatable & Inherently Buoyant Types	Calm inland waters where there is a good chance of a fast rescue.	Most comfort; small; allows wearer to swim; many sizes and colors; 15.5 lbs. or more buoyancy.	Most comfort; small; allows wearer to swim; many sizes and colors; 15.5 lbs. or more buoyancy.
Inherently Buoyant PFD Rugged; low performance, but sometimes less comfortable to wear.	Type IV Inherently Buoyant Only	Calm inland waters where wearer is always nearby.	Thickable; good backup to wearable PFDs; 16.5 lbs. or more buoyancy.	See pamphlet.
	Type V Inflatable & Inherently Buoyant Types		Special use. See its performance type marked on the label.	See pamphlet.