

(g)(8)(i) introductory text, line 11, the number "(8)" is corrected to read "(9)".

193. On page 41085, in the second column, in § 1915.1001, paragraph (g)(8)(i)(F), line 4, the number "(iv)" is corrected to read "(i)".

194. On page 41085, in the third column, in § 1915.1001, paragraph (g)(8)(ii)(B) is corrected to read:

* * * * *

(g) * * *
(8) * * *
(ii) * * *

(B) Wet methods shall be used to remove roofing materials that are not intact, or that will be rendered not intact during removal, unless such wet methods are not feasible or will create safety hazards.

* * * * *

195. On page 41085, in the third column, in § 1915.1001, paragraph (g)(8)(ii)(D) is corrected to read:

* * * * *

(g) * * *
(8) * * *
(ii) * * *

(D) When removing built-up roofs with asbestos-containing roofing felts and an aggregate surface using a power roof cutter, all dust resulting from the cutting operation shall be collected by a HEPA dust collector, or shall be HEPA vacuumed by vacuuming along the cut line. When removing built-up roofs with asbestos-containing roofing felts and a smooth surface using a power roof cutter, the dust resulting from the cutting operation shall be collected either by a HEPA dust collector or HEPA vacuuming along the cut line, or by gently sweeping and then carefully and completely wiping up the still-wet dust and debris left along the cut line. The dust and debris shall be immediately bagged or placed in covered containers.

* * * * *

196. On page 41085, in the third column, in § 1915.1001, paragraph (g)(8)(ii)(E) is corrected to read:

* * * * *

(g) * * *
(8) * * *
(ii) * * *

(E) Asbestos-containing material that has been removed from a roof shall not be dropped or thrown to the ground. Unless the material is carried or passed to the ground by hand, it shall be lowered to the ground via covered, dust-tight chute, crane or hoist:

(I) Any ACM that is not intact shall be lowered to the ground as soon as is practicable, but in any event no later than the end of the work shift. While the material remains on the roof it shall either be kept wet, placed in an

impermeable waste bag, or wrapped in plastic sheeting.

(2) Intact ACM shall be lowered to the ground as soon as is practicable, but in any event no later than the end of the work shift.

* * * * *

197. On page 41085, in the third column, in § 1915.1001, a new paragraph (g)(8)(ii)(H) is added to read:

* * * * *

(g) * * *
(8) * * *
(ii) * * *

(H) Notwithstanding any other provision of this section, removal or repair of sections of intact roofing less than 25 square feet in area does not require use of wet methods or HEPA vacuuming as long as manual methods which do not render the material non-intact are used to remove the material and no visible dust is created by the removal method used. In determining whether a job involves less than 25 square feet, the employer shall include all removal and repair work performed on the same roof on the same day.

* * * * *

198. On page 41085, in the third column, in § 1915.1001, paragraph (g)(8)(iii) introductory text is corrected to read:

* * * * *

(g) * * *
(8) * * *

(iii) When removing cementitious asbestos-containing siding and shingles or transite panels containing ACM on building exteriors (other than roofs, where paragraph (g)(8)(ii) of this section applies) the employer shall ensure that the following work practices are followed:

* * * * *

199. On page 41086, in the first column, in § 1915.1001, paragraph (g)(8)(v)(A), line 2 is corrected by adding the word "to" after the word "prior".

200. On page 41086, in the second column, in § 1915.1001, paragraph (g)(9)(iii), line 9 is corrected by adding the words "or another isolation method" after the word "section".

201. On page 41086, in the second column, in § 1915.1001, paragraph (g)(9)(iv), line 4, the number "(4)" is corrected to read "(2)".

202. On page 41086, in the second column, in § 1915.1001, paragraph (g)(9)(v), line 7, the words "paragraph (e)(4)(iii)" are corrected to read "paragraph (f)(2)(iii)".

203. On page 41086, in the second column, in § 1915.1001, paragraph (g)(10) introductory text, line 5, the number "(8)" is corrected to read "(9)".

204. On page 41086, in the third column, in § 1915.1001, paragraph

(g)(11)(ii), line 19 is corrected by adding the words "to this section" after the words "Appendix L".

205. On page 41086, in the third column, in § 1915.1001, a new paragraph (g)(12) is added to read:

* * * * *

(g) * * *

(12) Alternative methods of compliance for installation, removal, repair, and maintenance of certain roofing materials. Notwithstanding any other provision of this section, an employer who complies with all provisions of this paragraph (g)(12) when installing, removing, repairing, or maintaining intact roof cements, mastics, coatings, or flashings which contain asbestos fibers encapsulated or coated by bituminous or resinous compounds shall be deemed to be in compliance with this section. If an employer does not comply with all provisions of this paragraph (g)(12), or if during the course of the job the material does not remain intact, the provisions of paragraph (g)(8) of this section apply instead of this paragraph (g)(12).

(i) Before work begins and as needed during the job, a qualified person who is capable of identifying asbestos hazards in the workplace and selecting the appropriate control strategy for asbestos exposure, and who has the authority to take prompt corrective measures to eliminate such hazards, shall conduct an inspection of the worksite and determine that the roofing material is intact and will likely remain intact.

(ii) All employees performing work covered by this paragraph (g)(12) shall be trained in a training program that meets the requirements of paragraph (k)(9)(viii) of this section.

(iii) The material shall not be sanded, abraded, or ground. Manual methods which do not render the material non-intact shall be used.

(iv) Material that has been removed from a roof shall not be dropped or thrown to the ground. Unless the material is carried or passed to the ground by hand, it shall be lowered to the ground via covered, dust-tight chute, crane or hoist. All such material shall be removed from the roof as soon as is practicable, but in any event no later than the end of the work shift.

(v) Where roofing products which have been labeled as containing asbestos pursuant to paragraph (k)(8) of this section are installed on non-residential roofs during operations covered by this paragraph (g)(12), the employer shall notify the building owner of the