

Appendix A to Subpart II of Part 63—VOC Data Sheet ¹*Properties of the Coating "As Supplied" by the Manufacturer*²

Coating Manufacturer: _____

Coating Identification: _____

Batch Identification: _____

* Incorporation by reference—see § 63.14.

¹ Adapted from EPA-340/1-86-016 (July 1986), p. II-2.² The subscript "s" denotes each value is for the coating "as supplied" by the manufacturer.

Supplied To: _____

Properties of the coating as supplied ¹ to the customer:A. Coating Density: (D_c)_s _____ g/L[] ASTM D1475-90 * [] Other ³B. Total Volatiles: (m_v)_s _____ Mass Percent[] ASTM D2369-93 * [] Other ³C. Water Content: 1. (m_w)_s _____ Mass Percent

[] ASTM D3792-91 * [] ASTM

D4017-90 * [] Other ³2. (v_w)_s _____ Volume Percent³ Explain the other method used under "Remarks."[] Calculated [] Other ³D. Organic Volatiles: (m_o)_s _____ Mass PercentE. Nonvolatiles: (v_n)_s _____ Volume Percent[] Calculated [] Other ³F. VOC Content (VOC)_s:

1. _____ g/L solids (nonvolatiles)

2. _____ g/L coating (less water and exempt compounds)

G. Thinner Density: D_{th} _____ g/LASTM _____ [] Other ³

Remarks: (use reverse side)

Signed: _____ Date: _____

BILLING CODE 6560-50-P