

immediate use: *Provided*, That on a nautical school ship of 1,000 gross tons and under only one of the fire extinguishers may be required.

(b) In boiler and machinery spaces, at least two fire hydrants must have a fire hose of a length that allows each part of the boiler and machinery spaces to be reached by the combination nozzle.

(c) Each fire hose under paragraph (b) of this section must have a combination solid stream and water spray nozzle that meets subpart 162.027 of this chapter. A combination nozzle and a low-velocity spray applicator previously approved under subpart 162.027 of this chapter may remain so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection.

* * * * *

§ 167.45–55 [Removed]

121. Section 167.45–55 is removed.

Subpart 167.50—[Removed]

122. Subpart 167.50 is removed.

123. In § 167.55–5, paragraph (i) is removed, paragraph (j) is redesignated as paragraph (i) and the new paragraph (i)(1) is revised to read as follows:

§ 167.55–5 Marking of fire and emergency equipment, etc.

* * * * *

(i) * * *

(1) All lifeboats, rigid type oars and paddles, life preservers, EPIRB and life buoys shall be painted or branded with the name of the nautical school ship.

* * * * *

§ 167.65–3 [Removed]

124. Section 167.65–3 is removed.

§ 167.65–10 [Removed]

125. Section 167.65–10 is removed.

126. Section 167.65–15 is revised to read as follows:

§ 167.65–15 Routing instructions; strict compliance with.

All licensed masters, officers, and certificated seamen on nautical school ships must comply strictly with routing instructions issued by competent naval authority.

§ 167.65–30 [Removed]

137. Section 167.65–30 is removed.

§ 167.65–45 [Amended]

128. In § 167.65–45, paragraphs (a), (b), and (c) are removed and the paragraph designation “(d)” is removed from paragraph (d).

129. Section 167.65–50 is revised to read as follows:

§ 167.65–50 Posting placards of lifesaving signals.

On all vessels to which this subpart applies there shall be readily available to the deck officer of the watch placard containing instructions for the use of the lifesaving signals set for in Regulation 16, Chapter V, of the International Convention for Safety of Life at Sea, 1974. These signals shall be used by vessels or persons in distress when communicating with lifesaving stations and maritime rescue units.

PART 168—CIVILIAN NAUTICAL SCHOOL VESSELS

130. The authority citation for Part 168 is revised to read as follows:

Authority: 46 U.S.C. 3305, 3306; 48 CFR 1.46.

131. Subpart 168.15 is revised to read as follows:

Subpart 168.15—Accommodations

Sec.

168.15–1	Intent.
168.15–5	Locations.
168.15–10	Construction.
168.15–15	Size.
168.15–20	Equipment.
168.15–25	Washrooms.
168.15–30	Toilet rooms.
168.15–35	Hospital space.
168.15–40	Lighting.
168.15–45	Heating.
168.15–50	Ventilation.
168.15–55	Screening.
168.15–60	Inspection.

§ 168.15–1 Intent.

It is the intent of this subpart to provide minimum standards for the size, ventilation, plumbing, and sanitation of quarters assigned to the members of the crew, passengers, cadets, students, instructors, or any other persons at any time quartered on board any such vessel.

§ 168.15–5 Location.

(a) Quarters shall be located so that sufficient fresh air and light are obtainable compatible with accepted practice or good arrangement and construction.

(b) Quarters shall not be located forward of the collision bulkhead, nor shall such section or sections of any deck occupied by quarters be below the deepest load line except in special case.

§ 168.15–10 Construction.

(a) The accommodations provided must be securely constructed, properly lighted, heated, drained, ventilated, equipped, located, arranged, and insulated from undue noise, heat and odors.

(b) All accommodations shall be constructed and arranged so that they

can be kept in a clean, workable, and sanitary condition.

§ 168.15–15 Size.

(a) Sleeping accommodations shall be divided into rooms, no one of which shall berth more than 6 persons. The purpose for which each space is to be used and the number of persons it may accommodate, shall be marked.

(b) Each room shall be of such size that there is at least 1.8 m² (20 ft³) of deck area and a volume of at least 4.2 m³ (150 ft²) for each person accommodated. In measuring sleeping quarters, any furnishings contained therein are not to be deducted from the total volume or from the deck area.

§ 168.15–20 Equipment.

(a) Each person shall have a separate berth and not more than 1 berth shall be placed above another. The berths shall be of metal framework. The overall size of a berth shall not be less than 68 cm (27 in) wide by 190 cm (75 in) long. Where 2 tiers of berths are fitted, the bottom of the lower berth must not be less than 30 cm (12 in) above the deck, and the bottom of the upper must not be less than 76 cm (30 in) both from the bottom of the lower and from the deck overhead. The berths shall not be obstructed by pipes, ventilating ducts, or other installations.

(b) A metal locker shall be provided for each person accommodated in a room.

§ 168.15–25 Washrooms.

(a) There shall be provided 1 shower for each 10 persons or fraction thereof and 1 wash basin for each 6 persons or fraction thereof to be accommodated. The persons to be accommodated shall include all persons who do not occupy rooms to which private facilities are attached.

(b) All wash basins and showers shall be equipped with proper plumbing including hot and cold running fresh water.

§ 168.15–30 Toilet rooms.

(a) There shall be provided 1 toilet for each 10 persons or fraction thereof to be accommodated. The persons to be accommodated shall include all persons who do not occupy rooms to which private facilities are attached.

(b) The toilet rooms shall be located convenient to the sleeping quarters of the persons to which they are allotted but shall not open directly into such quarters except when they are provided as private or semiprivate facilities.

(c) Where more than one toilet is located in a space or compartment, each toilet shall be separated by partitions.