

BAT EFFLUENT LIMITATIONS—Continued

Stream	Pollutant parameter	BAT effluent limitations
Option 2: (A) All coastal areas except Cook Inlet (B) Cook Inlet	Cadmium	3 mg/kg dry weight maximum in the stock barite.
	Toxicity	Minimum 96-hour LC50 of the SPP shall be 3 percent by volume. ³
Option 3: All coastal areas	Free Oil ¹	No discharge.
	Diesel Oil	No discharge.
	Mercury	1 mg/kg dry weight maximum in the stock barite.
	Cadmium	3 mg/kg dry weight maximum in the stock barite.
	Toxicity	Minimum 96-hour LC50 of the SPP shall be 10 percent to 100 percent by volume. ³
Well Treatment, Workover and Completion Fluids:		No discharge.
Option 1: (A) All coastal areas except freshwater of Texas and Louisiana. (B) Freshwaters of Texas and Louisiana ...	Free Oil ¹	No discharge.
Option 2: (A) All coastal areas except Cook Inlet (B) Cook Inlet	Oil and Grease	The maximum for any one day shall not exceed 42 mg/l, and the 30-day average shall not exceed 29 mg/l.
Produced Sand		No discharge.
Deck Drainage	Free Oil ²	No discharge.
Domestic Waste	Foam	No discharge.

¹ As determined by the static sheen test

² As determined by the presence of a film or sheen upon or a discoloration of the surface of the receiving water (visual sheen).

³ As determined by the toxicity test (see appendix 2 of 40 CFR part 435, subpart A).

§ 435.44 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point

source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT):

BCT EFFLUENT LIMITATIONS

Stream	Pollutant parameter	BCT effluent limitations
Produced Water (all facilities)	Oil & Grease	The maximum for any one day shall not exceed 72 mg/l and the 30-day average shall not exceed 48 mg/l.
Drilling Fluids and Drill Cuttings: All facilities except Cook Inlet		No discharge.
	Cook Inlet	Free Oil
Well Treatment, Workover and Completion Fluids.		No discharge. ¹
		Free Oil
Produced Sand		No discharge.
Deck Drainage	Free Oil	No discharge. ²
Sanitary Waste: Sanitary M10	Residual Chlorine	Minimum of 1 mg/l maintained as close to this concentration as possible.
	Sanitary M91M	Floating Solids
Domestic Waste	Floating Solids and garbage.	No discharge of Floating Solids or garbage. ³

¹ As determined by static sheen test 40 CFR part 435, subpart A, appendix 1.

² As determined by the presence of a film or sheen upon or a discoloration of the surface of the receiving water (visual sheen).

³ As defined in 40 CFR 435.41(1).

§ 435.45 Standards of performance for new sources (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):